

PyRCS

An open-source tool for collecting railway codes used in different UK rail industry systems

Release 0.3.1

Qian Fu

School of Engineering

University of Birmingham

First release: August 2019

Last updated: June 2022

© Copyright 2019-2022, Qian Fu

Table of Contents

1	About PyRCS	1
2	Installation	2
3	Sub-packages and modules	3
3.1	Sub-packages	3
3.1.1	line_data	3
	elr_mileage	4
	elec	14
	loc_id	28
	lor_code	38
	line_name	46
	trk_diagr	50
	bridge	52
3.1.2	other_assets	56
	sig_box	56
	tunnel	70
	viaduct	75
	station	79
	depot	83
	feature	95
3.2	Modules	107
3.2.1	parser	108
	Preprocess contents	108
	Extract information	111
3.2.2	converter	118
	Convert mileage data	118
	Convert other data	124
3.2.3	collector	125
	LineData	125
	OtherAssets	128
3.2.4	utils	130
	Validate inputs	131
	Print messages	134
	Save and retrieve pre-packed data	136

4	License	141
5	Use of data	142
6	Acknowledgement	143
7	Tutorial	144
7.1	Location identifiers	144
7.1.1	Location identifiers given a specific initial letter	145
7.1.2	All available location identifiers	146
7.2	ELRs and mileages	147
7.2.1	Engineer's Line References (ELRs)	147
7.2.2	Mileage file of a given ELR	149
7.3	Railway station data	150
7.3.1	Railway station locations given a specific initial letter	151
7.3.2	All available railway station locations	151
	Python Module Index	153
	Index	154

Chapter 1

About PyRCS

PyRCS is an open-source Python package for collecting and handling various codes (used in different UK rail industry systems), which are made available from [Railway Codes](#) website. This tool is intended for those, such as researchers and practitioners, who are the website users or work with the UK's railway codes by using Python programming language. It can facilitate access to, and manipulation of, the relevant data.

The *installation* of PyRCS includes a set of pre-packed data. When users request data of a category that is specified on the [Railway Codes](#) website, the pre-packed data of the category is loaded by default. Beyond that, it also offers capabilities to directly access the most up-to-date data on the data source website, and update the relevant pre-packed data as well.

Chapter 2

Installation

To install the latest release of pyrcs from [PyPI](#) via `pip`:

```
pip install --upgrade pyrcs
```

To install the most recent version of pyrcs hosted on [GitHub](#):

```
pip install --upgrade git+https://github.com/mikeqfu/pyrcs.git
```

Note:

- If using a [virtual environment](#), make sure it is activated.
 - It is recommended to add `pip install` the option `--upgrade` (or `-U`) to ensure that you are getting the latest stable release of the package.
 - For more general instructions on the installation of Python packages, please refer to the official guide on [Installing Packages](#).
-

To check whether pyrcs has been correctly installed, try to import the package via an interpreter shell:

```
>>> import pyrcs
>>> pyrcs.__version__ # Check the latest version
```

The latest version is: 0.3.1

Chapter 3

Sub-packages and modules

3.1 Sub-packages

<i>line_data</i>	A sub-package for collecting codes of <i>line data</i> .
<i>other_assets</i>	A sub-package of modules for collecting codes of <i>other assets</i> .

3.1.1 line_data

A sub-package for collecting codes of *line data*.

(See also *LineData*.)

Sub-modules

<i>elr_mileage</i>	Collect <i>Engineer's Line References (ELRs)</i> .
<i>elec</i>	Collect section codes for overhead line electrification (OLE) installations.
<i>loc_id</i>	Collect <i>CRS, NLC, TIPLOC and STANOX</i> codes.
<i>lor_code</i>	Collect <i>Line of Route (LOR/PRIDE)</i> codes.
<i>line_name</i>	Collect <i>railway line names</i> .
<i>trk_diagr</i>	Collect <i>British railway track diagrams</i> .
<i>bridge</i>	Collect data of <i>British railway bridges</i> .

elr_mileage

Collect Engineer's Line References (ELRs).

Class

<code>ELRMileages</code> ([<code>data_dir</code> , <code>update</code> , <code>verbose</code>])	A class for collecting data of Engineer's Line References (ELRs).
---	---

ELRMileages

class `pyrcs.line_data.elr_mileage.ELRMileages`(*data_dir=None, update=False, verbose=True*)

A class for collecting data of Engineer's Line References (ELRs).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last update date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import ELRMileages # from pyrcs import ELRMileages

>>> em = ELRMileages()

>>> print(em.NAME)
Engineer's Line References (ELRs)

>>> print(em.URL)
http://www.railwaycodes.org.uk/elrs/elr0.shtm
```

Attributes

<i>KEY</i>	Key of the <code>dict</code> -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

ELRMileages.KEY

`ELRMileages.KEY = 'ELRs and mileages'`

Key of the `dict`-type data

ELRMileages.KEY_TO_LAST_UPDATED_DATE

`ELRMileages.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'`

Key of the data of the last updated date

ELRMileages.NAME

`ELRMileages.NAME = "Engineer's Line References (ELRs)"`

Name of the data

ELRMileages.URL

`ELRMileages.URL = 'http://www.railwaycodes.org.uk/elrs/elr0.shtm'`

URL of the main web page of the data

Methods

<i>collect_elr_by_initial</i> (initial[, update, ...])	Collect Engineer's Line References (ELRs) for a given initial letter from source web page.
<i>collect_mileage_file</i> (elr[, parsed, ...])	Collect mileage file for the given ELR from source web page.
<i>fetch_elr</i> ([update, dump_dir, verbose])	Fetch data of ELRs and their associated mileages.
<i>fetch_mileage_file</i> (elr[, update, dump_dir, ...])	Fetch the mileage file for a given ELR.
<i>get_conn_mileages</i> (start_elr, end_elr[, update])	Get a connection point between two ELR-and-mileage pairs.
<i>search_conn</i> (start_elr, start_em, end_elr, end_em)	Search for connection between two ELR-and-mileage pairs.

ELRMileages.collect_elr_by_initial

`ELRMileages.collect_elr_by_initial(initial, update=False, verbose=False)`

Collect Engineer's Line References (ELRs) for a given initial letter from source web page.

Parameters

- **initial** (*str*) – initial letter of an ELR, e.g. 'a', 'z'
- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to True

Returns

data of ELRs whose names start with the given initial letter and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.line_data import ELRMileages # from pyrcs import ELRMileages

>>> em = ELRMileages()

>>> elrs_a_codes = em.collect_elr_by_initial(initial='a')
>>> type(elrs_a_codes)
dict
>>> list(elrs_a_codes.keys())
['A', 'Last updated date']

>>> elrs_a_codes_dat = elrs_a_codes['A']
>>> type(elrs_a_codes_dat)
pandas.core.frame.DataFrame
>>> elrs_a_codes_dat.head()
   ELR  ...      Notes
0  AAL  ...    Now NAJ3
1  AAM  ...  Formerly AML
2  AAV  ...
3  ABB  ...    Now AHB
4  ABB  ...

[5 rows x 5 columns]

>>> elrs_q_codes = em.collect_elr_by_initial(initial='Q')
>>> elrs_q_codes_dat = elrs_q_codes['Q']
>>> elrs_q_codes_dat.head()
   ELR  ...      Notes
0  QAB  ...  Duplicates ALB?
1  QBL  ...
2  QDS  ...
3  QLT  ...
4  QLT1 ...
```

(continues on next page)

(continued from previous page)

[5 rows x 5 columns]

ELRMileages.collect_mileage_file

```
ELRMileages.collect_mileage_file(elr, parsed=True, confirmation_required=True,
                                dump_it=False, verbose=False)
```

Collect mileage file for the given ELR from source web page.

Parameters

- **elr** (*str*) – ELR, e.g. 'CJD', 'MLA', 'FED'
- **parsed** (*bool*) – whether to parse the scraped mileage data
- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **dump_it** (*bool*) – whether to save the collected data as a pickle file, defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

mileage file for the given *elr*

Return type

dict

Note:

- In some cases, mileages are unknown hence left blank, e.g. ANI2, Orton Junction with ROB (~3.05)
- Mileages in parentheses are not on that ELR, but are included for reference, e.g. ANL, (8.67) NORTHOLT [London Underground]
- As with the main ELR list, mileages preceded by a tilde (~) are approximate.

Examples:

```
>>> from pyrcs.line_data import ELRMileages # from pyrcs import ELRMileages
>>> em = ELRMileages()
>>> cjd_mileage_file = em.collect_mileage_file(elr='CJD')
To collect mileage file of "CJD"
? [No]|Yes: yes
>>> type(cjd_mileage_file)
dict
```

(continues on next page)

(continued from previous page)

```

>>> list(cjd_mileage_file.keys())
['ELR', 'Line', 'Sub-Line', 'Mileage', 'Notes']
>>> cjd_mileage_file['Mileage']
Mileage ... Link_1_Mile_Chain
0    0.0000 ...
1    0.0528 ...          91.48
2    1.1540 ...
3    2.0000 ...
4    2.1562 ...          0.00
5    6.0022 ...
6    8.0308 ...
7   10.0748 ...
8   12.0968 ...
9   14.0968 ...
10  16.1452 ...
11  19.1408 ...
12  19.1540 ...
13  23.0770 ...
14  26.1078 ...
15  28.1276 ...
16  32.1188 ...
17  32.1188 ...
18  38.1276 ...
19  43.0572 ...
20  46.0704 ...
21  49.1188 ...
22  49.1320 ...          0.00
23  55.1606 ...
24  64.0594 ...

[25 rows x 8 columns]

>>> gam_mileage_file = em.collect_mileage_file(elr='GAM')
To collect mileage file of "GAM"
? [No]|Yes: yes
>>> gam_mileage_file['Mileage']
Mileage Mileage_Note Miles_Chains ... Link_1 Link_1_ELR Link_1_Mile_Chain
0    8.1518          8.69 ...    None
1   10.0264         10.12 ...    None

[2 rows x 8 columns]

>>> sld_mileage_file = em.collect_mileage_file(elr='SLD')
To collect mileage file of "SLD"
? [No]|Yes: yes
>>> sld_mileage_file['Mileage']
Mileage Mileage_Note Miles_Chains ... Link_1 Link_1_ELR Link_1_Mile_Chain
0   31.0088         31.04 ...    MVN2          MVN2
1   31.0682         31.31 ...    None
2   31.1474         31.67 ...    None
3   32.1078         32.49 ...    None
4   32.1232         32.56 ...    None

[5 rows x 8 columns]

>>> elr_mileage_file = em.collect_mileage_file(elr='ELR')
To collect mileage file of "ELR"

```

(continues on next page)

(continued from previous page)

```
? [No]|Yes: yes
>>> elr_mileage_file['Mileage']
   Mileage Mileage_Note ... Link_1_ELR Link_1_Mile_Chain
0  122.0044          ...      GRS3
1  122.0682          ...              0.00
2  122.0726          ...      SPI      0.00
3  122.0836          ...
4  124.0792          ...
5  127.1716  Approximate ...
6  128.0088          ...
7  128.0154          ...      MAB
8  130.0946          ...
9  133.1254          ...
10 134.1694          ...
11 138.0770          ...
12 139.1694          ...      MAB      149.43
13 140.1122          ...      LOB      150.13
14 141.0000          ...
15 143.0792          ...
16 143.0792          ...
17 145.1078          ...
18 146.0594          ...
19 147.1650          ...
20 148.1166          ...
21 149.1452          ...
22 150.1056          ...
23 151.1606          ...
24 154.0088          ...
25 154.0704          ...
26 154.1078          ...
27 154.1628          ...
28 154.1650          ...      MAC3      109.53

[29 rows x 8 columns]
```

ELRMileages.fetch_elr

ELRMileages.fetch_elr(update=False, dump_dir=None, verbose=False)

Fetch data of ELRs and their associated mileages.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

data of all available ELRs and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.line_data import ELMileages # from pyrcs import ELMileages

>>> em = ELMileages()

>>> elrs_codes = em.fetch_elr()
>>> type(elrs_codes)
dict
>>> list(elrs_codes.keys())
['ELRs and mileages', 'Last updated date']

>>> print(em.KEY)
ELRs

>>> elrs_codes_dat = elrs_codes[em.KEY]
>>> type(elrs_codes_dat)
pandas.core.frame.DataFrame
>>> elrs_codes_dat.head()
  ELR  ...      Notes
0  AAL  ...    Now NAJ3
1  AAM  ...  Formerly AML
2  AAV  ...
3  ABB  ...    Now AHB
4  ABB  ...

[5 rows x 5 columns]
```

ELRMileages.fetch_mileage_file

`ELRMileages.fetch_mileage_file(elr, update=False, dump_dir=None, verbose=False)`

Fetch the mileage file for a given ELR.

Parameters

- **elr** (*str*) – elr: ELR, e.g. 'CJD', 'MLA', 'FED'
- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to None
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

mileage file (codes), line name and, if any, additional information/notes

Return type

dict

Examples:

```

>>> from pyrcs.line_data import ELRMileages # from pyrcs import ELRMileages

>>> em = ELRMileages()

>>> # Get the mileage file of 'AAL' (Now 'NAJ3')
>>> aal_mileage_file = em.fetch_mileage_file(elr='AAL')
>>> type(aal_mileage_file)
dict
>>> list(aal_mileage_file.keys())
['ELR', 'Line', 'Sub-Line', 'Mileage', 'Notes', 'Formerly']

>>> aal_mileage_file['ELR']
'NAJ3'
>>> aal_mileage_file['Formerly']
'AAL'
>>> aal_mileage_file['Mileage']
Mileage Mileage_Note ... Link_1_ELR Link_1_Mile_Chain
0  0.0000          ...      NAJ2          33.69
1  0.0594          ...      GUA          164.75
2  1.0396          ...
3  3.0682          ...
4  6.0704          ...
5  8.0572          ...      BSG          0.00
6  8.0990          ...      WEJ
7  9.0594          ...
8  13.0264         ...
9  17.0858         ...
10 17.0968         ...
11 18.0572         ...      DCL          81.10
12 18.0638         ...      DCL          81.12

[13 rows x 8 columns]

>>> # Get the mileage file of 'MLA'
>>> mla_mileage_file = em.fetch_mileage_file(elr='MLA')
>>> type(mla_mileage_file)
dict
>>> list(mla_mileage_file.keys())
['ELR', 'Line', 'Sub-Line', 'Mileage', 'Notes']

>>> mla_mileage_file_mileages = mla_mileage_file['Mileage']
>>> type(mla_mileage_file_mileages)
dict
>>> list(mla_mileage_file_mileages.keys())
['Current measure', 'Original measure']

>>> mla_mileage_file_mileages['Original measure']
Mileage Mileage_Note ... Link_3_ELR Link_3_Mile_Chain
0  4.1386          ...      NEM4          0.00
1  5.0616          ...
2  5.1122          ...

[3 rows x 14 columns]

>>> mla_mileage_file_mileages['Current measure']
Mileage Mileage_Note Miles_Chains ... Link_1 Link_1_ELR Link_1_Mile_Chain
0  0.0000          0.00 ... MRL2 (4.44) MRL2          4.44

```

(continues on next page)

(continued from previous page)

```

1  0.0572          0.26 ...      None
2  0.1540          0.70 ...      None
3  0.1606          0.73 ...      None

[4 rows x 8 columns]
```

ELRMileages.get_conn_mileages

`ELRMileages.get_conn_mileages(start_elr, end_elr, update=False, **kwargs)`

Get a connection point between two ELR-and-mileage pairs.

Namely, find the end and start mileages for the start and end ELRs, respectively.

Note: This function may not be able to find the connection for every pair of ELRs. See [Example 2](#) below.

Parameters

- `start_elr (str)` – start ELR
- `end_elr (str)` – end ELR
- `update (bool)` – whether to do an update check (for the package data), defaults to `False`
- `kwargs` – [optional] parameters of the method
`ELRMileages.fetch_mileage_file()`

Returns

connection ELR and mileages between the given `start_elr` and `end_elr`

Return type

tuple

Example 1:

```

>>> from pyrcs.line_data import ELRMileages # from pyrcs import ELRMileages

>>> em = ELRMileages()

>>> conn = em.get_conn_mileages(start_elr='NAY', end_elr='LTN2')
>>> (s_dest_mlg, c_elr, c_orig_mlg, c_dest_mlg, e_orig_mlg) = conn

>>> print(s_dest_mlg)
5.1606
>>> print(c_elr)
NOL
>>> print(c_orig_mlg)
5.1606
>>> print(c_dest_mlg)
0.0638
```

(continues on next page)

(continued from previous page)

```
>>> print(e_orig_mlg)
123.1320
```

Example 2:

```
>>> from pyrcs.line_data import ELMileages # from pyrcs import ELMileages

>>> em = ELMileages()

>>> conn = em.get_conn_mileages(start_elr='MAC3', end_elr='DBP1', dump_dir="tests")
>>> conn
(' ', ' ', ' ', ' ', ' ')
```

ELRMileages.search_conn

static ELMileages.**search_conn**(start_elr, start_em, end_elr, end_em)

Search for connection between two ELR-and-mileage pairs.

Parameters

- **start_elr** (*str*) – start ELR
- **start_em** (*pandas.DataFrame*) – mileage file of the start ELR
- **end_elr** (*str*) – end ELR
- **end_em** (*pandas.DataFrame*) – mileage file of the end ELR

Returns

connection (<end mileage of the start ELR>, <start mileage of the end ELR>)

Return type

tuple

Examples:

```
>>> from pyrcs.line_data import ELMileages # from pyrcs import ELMileages

>>> em = ELMileages()

>>> elr_1 = 'AAM'
>>> mileage_file_1 = em.collect_mileage_file(elr_1, confirmation_required=False)
>>> mf_1_mileages = mileage_file_1['Mileage']

>>> mf_1_mileages.head()
   Mileage  Mileage_Note  ...  Link_2_ELR  Link_2_Mile_Chain
0    0.0000             ...
1    0.0154             ...
2    0.0396             ...
3    1.1012             ...
4    1.1408             ...

[5 rows x 11 columns]
```

(continues on next page)

(continued from previous page)

```

>>> elr_2 = 'ANZ'
>>> mileage_file_2 = em.collect_mileage_file(elr_2, confirmation_required=False)
>>> mf_2_mileages = mileage_file_2['Mileage']

>>> mf_2_mileages.head()
  Mileage Mileage_Note Miles_Chains  ...      Link_1 Link_1_ELR Link_1_Mile_Chain
0  84.0924              84.42  ...      BEA      BEA
1  84.1364              84.62  ...  AAM (0.18)      AAM              0.18

[2 rows x 8 columns]

>>> elr_1_dest, elr_2_orig = em.search_conn(elr_1, mf_1_mileages, elr_2, mf_2_mileages)

>>> elr_1_dest
'0.0396'
>>> elr_2_orig
'84.1364'

```

elec

Collect [section codes for overhead line electrification \(OLE\) installations](#).

Class

<i>Electrification</i> ([data_dir, update, verbose])	A class for collecting section codes for overhead line electrification (OLE) installations .
--	--

Electrification

class pyrcs.line_data.elec.Electrification(data_dir=None, update=False, verbose=True)

A class for collecting [section codes for overhead line electrification \(OLE\) installations](#).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last update date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification

>>> elec = Electrification()

>>> print(elec.NAME)
Section codes for overhead line electrification (OLE) installations

>>> print(elec.URL)
http://www.railwaycodes.org.uk/electrification/mast_prefix0.shtm
```

Attributes

<i>KEY</i>	Key of the dict-type data
<i>KEY_TO_ENERGY_TARIFF_ZONES</i>	Key of the dict-type data of the ' <i>UK railway electrification tariff zones</i> '
<i>KEY_TO_INDEPENDENT_LINES</i>	Key of the dict-type data of the ' <i>independent lines</i> '
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>KEY_TO_NATIONAL_NETWORK</i>	Key of the dict-type data of the ' <i>national network</i> '
<i>KEY_TO_OHNS</i>	Key of the dict-type data of the ' <i>overhead line electrification neutral sections (OHNS)</i> '
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

Electrification.KEY

Electrification.KEY = 'Electrification'

Key of the dict-type data

Electrification.KEY_TO_ENERGY_TARIFF_ZONES

Electrification.KEY_TO_ENERGY_TARIFF_ZONES = 'National network energy tariff zones'

Key of the dict-type data of the '*UK railway electrification tariff zones*'

Electrification.KEY_TO_INDEPENDENT_LINES

```
Electrification.KEY_TO_INDEPENDENT_LINES = 'Independent lines'
```

Key of the dict-type data of the *'independent lines'*

Electrification.KEY_TO_LAST_UPDATED_DATE

```
Electrification.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'
```

Key of the data of the last updated date

Electrification.KEY_TO_NATIONAL_NETWORK

```
Electrification.KEY_TO_NATIONAL_NETWORK = 'National network'
```

Key of the dict-type data of the *'national network'*

Electrification.KEY_TO_OHNS

```
Electrification.KEY_TO_OHNS = 'National network neutral sections'
```

Key of the dict-type data of the *'overhead line electrification neutral sections (OHNS)'*

Electrification.NAME

```
Electrification.NAME = 'Section codes for overhead line electrification (OLE) installations'
```

Name of the data

Electrification.URL

```
Electrification.URL =  
'http://www.railwaycodes.org.uk/electrification/mast_prefix0.shtm'
```

URL of the main web page of the data

Methods

<code>collect_etz_codes</code> ([confirmation_required, ...])	Collect OLE section codes for national network energy tariff zones from source web page.
<code>collect_indep_lines_codes</code> ([...])	Collect OLE section codes for independent lines from source web page.
<code>collect_national_network_codes</code> ([...])	Collect OLE section codes for national network from source web page.
<code>collect_ohns_codes</code> ([confirmation_required, ...])	Collect codes for overhead line electrification neutral sections (OHNS) from source web page.
<code>fetch_codes</code> ([update, dump_dir, verbose])	Fetch OLE section codes listed in the Electrification catalogue.
<code>fetch_etz_codes</code> ([update, dump_dir, verbose])	Fetch OLE section codes for national network energy tariff zones .
<code>fetch_indep_lines_codes</code> ([update, dump_dir, ...])	Fetch OLE section codes for independent lines .
<code>fetch_national_network_codes</code> ([update, ...])	Fetch OLE section codes for national network .
<code>fetch_ohns_codes</code> ([update, dump_dir, verbose])	Fetch codes for overhead line electrification neutral sections (OHNS).
<code>get_indep_line_catalogue</code> ([update, verbose])	Get a catalogue for independent lines .

Electrification.collect_etz_codes

Electrification.`collect_etz_codes`(*confirmation_required=True, verbose=False*)

Collect OLE section codes for [national network energy tariff zones](#) from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

OLE section codes for national network energy tariff zones

Return type

dict or None

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification
>>> elec = Electrification()
```

(continues on next page)

(continued from previous page)

```

>>> rail_etz_codes = elec.collect_etz_codes()
To collect section codes for OLE installations: national network energy tariff zones
? [No]|Yes: yes

>>> type(rail_etz_codes)
dict
>>> list(rail_etz_codes.keys())
['National network energy tariff zones', 'Last updated date']

>>> elec.KEY_TO_ENERGY_TARIFF_ZONES
'National network energy tariff zones'

>>> rail_etz_codes_dat = rail_etz_codes[elec.KEY_TO_ENERGY_TARIFF_ZONES]
>>> type(rail_etz_codes_dat)
dict
>>> list(rail_etz_codes_dat.keys())
['Railtrack', 'Network Rail']

>>> rail_etz_codes_dat['Railtrack']['Codes']

```

	Code	Energy tariff zone
0	EA	East Anglia
1	EC	East Coast Main Line
2	GE	Great Eastern †
3	LT	LTS †
4	MD	Midland Main Line
5	ME	Merseyside †
6	MS	Merseyside (North West DC traction)
7	NE	North East
8	NL	North London (DC traction)
9	SC	Scotland
10	SO	South
11	SW	South West
12	WA	West Anglia †
13	WC	West Coast/North West

Electrification.collect_indep_lines_codes

Electrification.**collect_indep_lines_codes**(*confirmation_required=True, verbose=False*)

Collect OLE section codes for **independent lines** from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

OLE section codes for independent lines

Return type

dict or None

Examples:

```

>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification

>>> elec = Electrification()

>>> indep_lines_codes = elec.collect_indep_lines_codes()
To collect section codes for OLE installations: independent lines
? [No]|Yes: yes
>>> type(indep_lines_codes)
dict
>>> list(indep_lines_codes.keys())
['Independent lines', 'Last updated date']

>>> elec.KEY_TO_INDEPENDENT_LINES
'Independent lines'

>>> indep_lines_codes_dat = indep_lines_codes[elec.KEY_TO_INDEPENDENT_LINES]
>>> type(indep_lines_codes_dat)
dict
>>> len(indep_lines_codes_dat)
22
>>> list(indep_lines_codes_dat.keys())
['Beamish Tramway',
 'Birkenhead Tramway',
 'Black Country Living Museum [Tipton]',
 'Blackpool Tramway',
 'Brighton and Rottingdean Seashore Electric Railway [Magnus Volk's 'Daddy Long Legs'...',
 'Channel Tunnel',
 'Croydon Tramlink',
 'East Anglia Transport Museum [Lowestoft]',
 'Edinburgh Tramway',
 'Heath Park Tramway [Cardiff]',
 'Heaton Park Tramway [Manchester]',
 'Iarnród Éireann',
 'Luas [Dublin]',
 'Manchester Metrolink',
 'Manx Electric Railway',
 'Midland Metro [West Midlands]',
 'Nottingham Express Transit',
 'Seaton Tramway',
 'Sheffield Supertram',
 'Snaefell Mountain Railway',
 'Summerlee, Museum of Scottish Industrial Life Tramway',
 'Tyne & Wear Metro']

>>> indep_lines_codes_dat['Beamish Tramway']
{'Codes': None, 'Notes': 'Masts do not appear labelled.'}

```

Electrification.collect_national_network_codes

Electrification.collect_national_network_codes(*confirmation_required=True*,
verbose=False)

Collect OLE section codes for *national network* from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to *True*
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to *False*

Returns

OLE section codes for National network

Return type

dict or None

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification
>>> elec = Electrification()
>>> nn_codes = elec.collect_national_network_codes()
To collect section codes for OLE installations: national network
? [No]|Yes: yes
>>> type(nn_codes)
dict
>>> list(nn_codes.keys())
['National network', 'Last updated date']

>>> elec.KEY_TO_NATIONAL_NETWORK
'National network'

>>> nn_codes_dat = nn_codes[elec.KEY_TO_NATIONAL_NETWORK]
>>> type(nn_codes_dat)
dict
>>> list(nn_codes_dat.keys())
['Traditional numbering system [distance and sequence]',
 'New numbering system [km and decimal]',
 'Codes not certain [confirmation is welcome]',
 'Suspicious data',
 'An odd one to complete the record',
 'LBSC/Southern Railway overhead system',
 'Codes not known']

>>> tns_codes = nn_codes_dat['Traditional numbering system [distance and sequence]']
>>> type(tns_codes)
dict
>>> list(tns_codes.keys())
['Codes', 'Notes']
>>> tns_codes_dat = tns_codes['Codes']
>>> tns_codes_dat.head()
Code ... Datum
```

(continues on next page)

(continued from previous page)

```

0   A   ...           Fenchurch Street
1   A   ...           Newbridge Junction
2   A   ...           Fenchurch Street
3   A   ... Guide Bridge Station Junction
4   AB  ...

```

```
[5 rows x 4 columns]
```

Electrification.collect_ohns_codes

Electrification.collect_ohns_codes(*confirmation_required=True, verbose=False*)

Collect codes for [overhead line electrification neutral sections](#) (OHNS) from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

OHNS codes

Return type

dict or None

Examples:

```

>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification

>>> elec = Electrification()

>>> ohl_ns_codes = elec.collect_ohns_codes()
To collect section codes for OLE installations: national network neutral sections
? [No]|Yes: yes

>>> type(ohl_ns_codes)
dict
>>> list(ohl_ns_codes.keys())
['National network neutral sections', 'Last updated date']

>>> elec.KEY_TO_OHNS
'National network neutral sections'

>>> ohl_ns_codes_dat = ohl_ns_codes[elec.KEY_TO_OHNS]
>>> type(ohl_ns_codes_dat)
dict
>>> list(ohl_ns_codes_dat.keys())
['Codes', 'Notes']
>>> ohl_ns_codes_dat['Codes']
      ELR      OHNS Name  ...  Tracks      Dates
0  ARG1      Rutherglen  ...

```

(continues on next page)

(continued from previous page)

```

1  ARG2  Finnieston East  ...    Down
2  ARG2  Finnieston West  ...      Up
3  AYR1  Shields Junction ...    Up Ayr
4  AYR1  Shields Junction ...    Down Ayr
..  ...  ...             ...      ...
436 WWD   Law Junction   ...
437 WWD   Holytown Junction ...    Installed October 2018
438 XRC   Royal Oak     ...    Westbound
439 YKR   Yoker         ...    Installed ??, removed ≈11 March 1979
440 YKR   Dalmuir       ...    Installed ??, removed ≈11 March 1979

[441 rows x 5 columns]
```

Electrification.fetch_codes

Electrification.**fetch_codes**(*update=False, dump_dir=None, verbose=False*)

Fetch OLE section codes listed in the [Electrification](#) catalogue.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

section codes for overhead line electrification (OLE) installations

Return type

dict

Examples:

```

>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification
>>> elec = Electrification()
>>> elec_codes = elec.fetch_codes()
>>> type(elec_codes)
dict
>>> list(elec_codes.keys())
['Electrification', 'Last updated date']

>>> elec.KEY
'Electrification'

>>> elec_codes_dat = elec_codes[elec.KEY]
>>> type(elec_codes_dat)
dict
>>> list(elec_codes_dat.keys())
```

(continues on next page)

(continued from previous page)

```
['National network energy tariff zones',
 'Independent lines',
 'National network',
 'National network neutral sections']
```

Electrification.fetch_etz_codes

Electrification.fetch_etz_codes(update=False, dump_dir=None, verbose=False)

Fetch OLE section codes for national network energy tariff zones.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

OLE section codes for national network energy tariff zones

Return type

dict

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification

>>> elec = Electrification()

>>> rail_etz_codes = elec.fetch_etz_codes()
>>> type(rail_etz_codes)
dict
>>> list(rail_etz_codes.keys())
['National network energy tariff zones', 'Last updated date']

>>> elec.KEY_TO_ENERGY_TARIFF_ZONES
'National network energy tariff zones'

>>> rail_etz_codes_dat = rail_etz_codes[elec.KEY_TO_ENERGY_TARIFF_ZONES]
>>> type(rail_etz_codes_dat)
dict
>>> list(rail_etz_codes_dat.keys())
['Railtrack', 'Network Rail']

>>> rail_etz_codes_dat['Railtrack']['Codes']
Code          Energy tariff zone
0    EA              East Anglia
1    EC      East Coast Main Line
2    GE      Great Eastern †
3    LT              LTS †
```

(continues on next page)

(continued from previous page)

```

4 MD Midland Main Line
5 ME Merseyside †
6 MS Merseyside (North West DC traction)
7 NE North East
8 NL North London (DC traction)
9 SC Scotland
10 SO South
11 SW South West
12 WA West Anglia †
13 WC West Coast/North West

```

Electrification.fetch_indep_lines_codes

Electrification.fetch_indep_lines_codes(*update=False, dump_dir=None, verbose=False*)

Fetch OLE section codes for [independent lines](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

OLE section codes for independent lines

Return type

dict

Examples:

```

>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification
>>> elec = Electrification()
>>> indep_lines_codes = elec.fetch_indep_lines_codes()
>>> type(indep_lines_codes)
dict
>>> list(indep_lines_codes.keys())
['Independent lines', 'Last updated date']
>>> elec.KEY_TO_INDEPENDENT_LINES
'Independent lines'
>>> indep_lines_codes_dat = indep_lines_codes[elec.KEY_TO_INDEPENDENT_LINES]
>>> type(indep_lines_codes_dat)
dict
>>> len(indep_lines_codes_dat)
22
>>> list(indep_lines_codes_dat.keys())

```

(continues on next page)

(continued from previous page)

```

['Beamish Tramway',
 'Birkenhead Tramway',
 'Black Country Living Museum [Tipton]',
 'Blackpool Tramway',
 'Brighton and Rottingdean Seashore Electric Railway [Magnus Volk's 'Daddy Long Legs'...
 'Channel Tunnel',
 'Croydon Tramlink',
 'East Anglia Transport Museum [Lowestoft]',
 'Edinburgh Tramway',
 'Heath Park Tramway [Cardiff]',
 'Heaton Park Tramway [Manchester]',
 'Iarnród Éireann',
 'Luas [Dublin]',
 'Manchester Metrolink',
 'Manx Electric Railway',
 'Midland Metro [West Midlands]',
 'Nottingham Express Transit',
 'Seaton Tramway',
 'Sheffield Supertram',
 'Snaefell Mountain Railway',
 'Summerlee, Museum of Scottish Industrial Life Tramway',
 'Tyne & Wear Metro']

>>> indep_lines_codes_dat['Beamish Tramway']
{'Codes': None, 'Notes': 'Masts do not appear labelled.'}

```

Electrification.fetch_national_network_codes

Electrification.fetch_national_network_codes(*update=False, dump_dir=None, verbose=False*)

Fetch OLE section codes for [national network](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

OLE section codes for National network

Return type

dict or `None`

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification
```

(continues on next page)

(continued from previous page)

```

>>> elec = Electrification()

>>> nn_codes = elec.fetch_national_network_codes()
>>> type(nn_codes)
dict
>>> list(nn_codes.keys())
['National network', 'Last updated date']

>>> elec.KEY_TO_NATIONAL_NETWORK
'National network'

>>> nn_codes_dat = nn_codes[elec.KEY_TO_NATIONAL_NETWORK]
>>> type(nn_codes_dat)
dict
>>> list(nn_codes_dat.keys())
['Traditional numbering system [distance and sequence]',
 'New numbering system [km and decimal]',
 'Codes not certain [confirmation is welcome]',
 'Suspicious data',
 'An odd one to complete the record',
 'LBSC/Southern Railway overhead system',
 'Codes not known']

>>> tns_codes = nn_codes_dat['Traditional numbering system [distance and sequence]']
>>> type(tns_codes)
dict
>>> list(tns_codes.keys())
['Codes', 'Notes']
>>> tns_codes_dat = tns_codes['Codes']
>>> tns_codes_dat.head()
   Code  ...                               Datum
0    A  ...           Fenchurch Street
1    A  ...       Newbridge Junction
2    A  ...           Fenchurch Street
3    A  ...  Guide Bridge Station Junction
4   AB  ...

[5 rows x 4 columns]

```

Electrification.fetch_ohns_codes

Electrification.**fetch_ohns_codes**(*update=False, dump_dir=None, verbose=False*)

Fetch codes for [overhead line electrification neutral sections](#) (OHNS).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

OHNS codes

Return type

dict

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification

>>> elec = Electrification()

>>> ohl_ns_codes = elec.fetch_ohns_codes()

>>> type(ohl_ns_codes)
dict
>>> list(ohl_ns_codes.keys())
['National network neutral sections', 'Last updated date']

>>> elec.KEY_TO_OHNS
'National network neutral sections'

>>> ohl_ns_codes_dat = ohl_ns_codes[elec.KEY_TO_OHNS]
>>> type(ohl_ns_codes_dat)
dict
>>> list(ohl_ns_codes_dat.keys())
['Codes', 'Notes']
>>> ohl_ns_codes_dat['Codes']
      ELR      OHNS Name  ...  Tracks      Dates
0   ARG1      Rutherglen  ...      Down
1   ARG2  Finnieston East  ...      Up
2   ARG2  Finnieston West  ...      Up Ayr
3   AYR1  Shields Junction  ...  Down Ayr
4   AYR1  Shields Junction  ...      ...
..   ...      ...      ...      ...
436  WWD      Law Junction  ...
437  WWD  Holytown Junction  ...      Installed October 2018
438  XRC      Royal Oak  ...  Westbound
439  YKR      Yoker  ...      Installed ??, removed ≈11 March 1979
440  YKR      Dalmuir  ...      Installed ??, removed ≈11 March 1979

[441 rows x 5 columns]
```

Electrification.get_indep_line_catalogue

Electrification.get_indep_line_catalogue(update=False, verbose=False)

Get a catalogue for independent lines.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *False*

Returns

a list of independent line names

Return type

pandas.DataFrame

Examples:

```
>>> from pyrcs.line_data import Electrification # from pyrcs import Electrification
>>> from pyhelpers.settings import pd_preferences

>>> pd_preferences(max_columns=1)

>>> elec = Electrification()

>>> indep_line_cat = elec.get_indep_line_catalogue()
>>> indep_line_cat.head()

```

		Feature	...
0		Beamish Tramway	...
1		Birkenhead Tramway	...
2		Black Country Living Museum	...
3		Blackpool Tramway	...
4	Brighton and Rottingdean Seashore Electric Rai...		...

```

[5 rows x 3 columns]

```

loc_id

Collect CRS, NLC, TIPLOC and STANOX codes.

Class

<code>LocationIdentifiers([data_dir, update, verbose])</code>	A class for collecting data of location identifiers (including other systems' station codes).
---	---

LocationIdentifiers

```
class pyrcs.line_data.loc_id.LocationIdentifiers(data_dir=None, update=False,
                                                  verbose=True)
```

A class for collecting data of [location identifiers](#) (including [other systems'](#) station codes).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- `catalogue` (*dict*) – catalogue of the data
- `last_updated_date` (*str*) – last updated date
- `data_dir` (*str*) – path to the data directory
- `current_data_dir` (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> print(lid.NAME)
CRS, NLC, TIPOLOC and STANOX codes

>>> print(lid.URL)
http://www.railwaycodes.org.uk/crs/crs0.shtm
```

Attributes

<i>KEY</i>	Key of the <i>dict</i> -type data
<i>KEY_TO_ADDITIONAL_NOTES</i>	Key of the <i>dict</i> -type data of <i>additional notes</i>
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>KEY_TO_MSCEN</i>	Key of the <i>dict</i> -type data of the ' <i>multiple station codes explanatory note</i> '
<i>KEY_TO_OTHER_SYSTEMS</i>	Key of the <i>dict</i> -type data of the ' <i>other systems</i> '
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

LocationIdentifiers.KEY

`LocationIdentifiers.KEY = 'LocationID'`

Key of the *dict*-type data

LocationIdentifiers.KEY_TO_ADDITIONAL_NOTES

`LocationIdentifiers.KEY_TO_ADDITIONAL_NOTES = 'Additional notes'`

Key of the *dict*-type data of *additional notes*

LocationIdentifiers.KEY_TO_LAST_UPDATED_DATE

`LocationIdentifiers.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'`

Key of the data of the last updated date

LocationIdentifiers.KEY_TO_MSCEN

`LocationIdentifiers.KEY_TO_MSCEN = 'Multiple station codes explanatory note'`

Key of the dict-type data of the '*multiple station codes explanatory note*'

LocationIdentifiers.KEY_TO_OTHER_SYSTEMS

`LocationIdentifiers.KEY_TO_OTHER_SYSTEMS = 'Other systems'`

Key of the dict-type data of the '*other systems*'

LocationIdentifiers.NAME

`LocationIdentifiers.NAME = 'CRS, NLC, TIPLOC and STANOX codes'`

Name of the data

LocationIdentifiers.URL

`LocationIdentifiers.URL = 'http://www.railwaycodes.org.uk/crs/crs0.shtm'`

URL of the main web page of the data

Methods

<code>collect_codes_by_initial(initial[, update, ...])</code>	Collect CRS , NLC , TIPLOC , STANME and STANOX codes for a given initial letter.
<code>collect_explanatory_note([...])</code>	Collect note about CRS code from source web page.
<code>collect_other_systems_codes([...])</code>	Collect data of other systems ' station codes from source web page.
<code>fetch_codes([update, dump_dir, verbose])</code>	Fetch CRS , NLC , TIPLOC , STANME and STANOX codes and other systems ' station codes.
<code>fetch_explanatory_note([update, dump_dir, ...])</code>	Fetch multiple station codes explanatory note.
<code>fetch_other_systems_codes([update, ...])</code>	Fetch data of other systems ' station codes.
<code>make_xref_dict(keys[, initials, main_key, ...])</code>	Make a dict/dataframe for location code data for the given keys.

LocationIdentifiers.collect_codes_by_initial

`LocationIdentifiers.collect_codes_by_initial(initial, update=False, verbose=False)`

Collect CRS, NLC, TIPLOC, STANME and STANOX codes for a given initial letter.

Parameters

- **initial** (*str*) – initial letter of station/junction name or certain word for specifying URL
- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of locations beginning with the given initial letter and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> loc_a = lid.collect_codes_by_initial(initial='a')
>>> type(loc_a)
dict
>>> list(loc_a.keys())
['A', 'Additional notes', 'Last updated date']

>>> loc_a_codes = loc_a['A']

>>> type(loc_a_codes)
pandas.core.frame.DataFrame
>>> loc_a_codes.head()
   Location CRS  ... STANME_Note STANOX_Note
0           Aachen  ...
1  Abbeyhill Junction  ...
2  Abbeyhill Signal E811  ...
3  Abbeyhill Turnback Sidings  ...
4  Abbey Level Crossing (Staffordshire)  ...

[5 rows x 12 columns]
```

LocationIdentifiers.collect_explanatory_note

`LocationIdentifiers.collect_explanatory_note(confirmation_required=True, verbose=False)`

Collect note about CRS code from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to `True`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of multiple station codes explanatory note

Return type

dict or `None`

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> exp_note = lid.collect_explanatory_note()
To collect data of Multiple station codes explanatory note
? [No]|Yes: yes
>>> type(exp_note)
dict
>>> list(exp_note.keys())
['Multiple station codes explanatory note', 'Notes', 'Last updated date']

>>> lid.KEY_TO_MSCEN
'Multiple station codes explanatory note'
>>> exp_note_dat = exp_note[lid.KEY_TO_MSCEN]

>>> type(exp_note_dat)
pandas.core.frame.DataFrame
>>> exp_note_dat
```

	Location	CRS	CRS_alt1	CRS_alt2
0	Glasgow Central	GLC	GCL	
1	Glasgow Queen Street	GLQ	GQL	
2	Heworth	HEW	HEZ	
3	Highbury & Islington	HHY	HII	XHZ
4	Lichfield Trent Valley	LTV	LIF	
5	Liverpool Lime Street	LIV	LVL	
6	Liverpool South Parkway	LPY	ALE	
7	London St Pancras	STP	SPL	SPX
8	Retford	RET	XRO	
9	Smethwick Galton Bridge	SGB	GTI	
10	Tamworth	TAM	TAH	
11	Willesden Junction	WIJ	WJH	WJL
12	Worcestershire Parkway	WOP	WPH	

LocationIdentifiers.collect_other_systems_codes

LocationIdentifiers.collect_other_systems_codes(*confirmation_required=True*,
verbose=False)

Collect data of *other systems' station codes* from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

codes of other systems

Return type

dict or None

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> os_codes = lid.collect_other_systems_codes()
To collect data of Other systems
? [No]|Yes: yes
>>> type(os_codes)
dict
>>> list(os_codes.keys())
['Other systems', 'Last updated date']

>>> lid.KEY_TO_OTHER_SYSTEMS
'Other systems'

>>> os_codes_dat = os_codes[lid.KEY_TO_OTHER_SYSTEMS]
>>> type(os_codes_dat)
collections.defaultdict
>>> list(os_codes_dat.keys())
['C  ras Iompair   ireann (Republic of Ireland)',
 'Crossrail',
 'Croydon Tramlink',
 'Docklands Light Railway',
 'Manchester Metrolink',
 'Translink (Northern Ireland)',
 'Tyne & Wear Metro']
```

LocationIdentifiers.fetch_codes

`LocationIdentifiers.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch CRS, NLC, TIPLOC, STANME and STANOX codes and other systems' station codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of location codes and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> loc_dat = lid.fetch_codes()
>>> type(loc_dat)
dict
>>> list(loc_dat.keys())
['LocationID', 'Other systems', 'Additional notes', 'Last updated date']

>>> lid.KEY
'LocationID'

>>> loc_codes = loc_dat['LocationID']

>>> type(loc_codes)
pandas.core.frame.DataFrame
>>> loc_codes.head()

```

	Location	CRS	...	STANME_Note	STANOX_Note
0	Aachen		...		
1	Abbeyhill Junction		...		
2	Abbeyhill Signal E811		...		
3	Abbeyhill Turnback Sidings		...		
4	Abbey Level Crossing (Staffordshire)		...		

```
[5 rows x 12 columns]
```

LocationIdentifiers.fetch_explanatory_note

`LocationIdentifiers.fetch_explanatory_note(update=False, dump_dir=None, verbose=False)`

Fetch multiple station codes explanatory note.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of multiple station codes explanatory note

Return type

dict

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> exp_note = lid.fetch_explanatory_note()
>>> type(exp_note)
dict
>>> list(exp_note.keys())
['Multiple station codes explanatory note', 'Notes', 'Last updated date']

>>> lid.KEY_TO_MSCEN
'Multiple station codes explanatory note'
>>> exp_note_dat = exp_note[lid.KEY_TO_MSCEN]
>>> type(exp_note_dat)
pandas.core.frame.DataFrame
>>> exp_note_dat
```

	Location	CRS	CRS_alt1	CRS_alt2
0	Glasgow Central	GLC	GCL	
1	Glasgow Queen Street	GLQ	GQL	
2	Heworth	HEW	HEZ	
3	Highbury & Islington	HHY	HII	XHZ
4	Lichfield Trent Valley	LTV	LIF	
5	Liverpool Lime Street	LIV	LVL	
6	Liverpool South Parkway	LPY	ALE	
7	London St Pancras	STP	SPL	SPX
8	Retford	RET	XRO	
9	Smethwick Galton Bridge	SGB	GTI	
10	Tamworth	TAM	TAH	
11	Willesden Junction	WIJ	WJH	WJL
12	Worcestershire Parkway	WOP	WPH	

LocationIdentifiers.fetch_other_systems_codes

LocationIdentifiers.fetch_other_systems_codes(*update=False, dump_dir=None, verbose=False*)

Fetch data of *other systems'* station codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to *None*
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to *False*

Returns

codes of other systems

Return type

dict

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> os_dat = lid.fetch_other_systems_codes()

>>> type(os_dat)
dict
>>> list(os_dat.keys())
['Other systems', 'Last updated date']

>>> lid.KEY_TO_OTHER_SYSTEMS
'Other systems'

>>> os_codes = os_dat[lid.KEY_TO_OTHER_SYSTEMS]
>>> type(os_codes)
collections.defaultdict
>>> list(os_codes.keys())
['C  ras Iompair   ireann (Republic of Ireland)',
 'Crossrail',
 'Croydon Tramlink',
 'Docklands Light Railway',
 'Manchester Metrolink',
 'Translink (Northern Ireland)',
 'Tyne & Wear Metro']
```

LocationIdentifiers.make_xref_dict

`LocationIdentifiers.make_xref_dict(keys, initials=None, main_key=None, as_dict=False, drop_duplicates=False, dump_it=False, dump_dir=None, verbose=False)`

Make a dict/dataframe for location code data for the given keys.

Parameters

- **keys** (*str* or *list*) – one or a sublist of ['CRS', 'NLC', 'TIPLOC', 'STANOX', 'STANME']
- **initials** (*str* or *list* or *None*) – one or a sequence of initials for which the codes are used, defaults to *None*
- **main_key** (*str* or *None*) – key of the returned dictionary (when *as_dict=True*), defaults to *None*
- **as_dict** (*bool*) – whether to return a dictionary, defaults to *False*
- **drop_duplicates** (*bool*) – whether to drop duplicates, defaults to *False*
- **dump_it** (*bool*) – whether to save the location codes dictionary, defaults to *False*
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to *None*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *False*

Returns

dictionary or a data frame for location code data for the given keys

Return type

dict or `pandas.DataFrame` or *None*

Examples:

```
>>> from pyrcs.line_data import LocationIdentifiers
>>> # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> stanox_dictionary = lid.make_xref_dict(keys='STANOX')
>>> type(stanox_dictionary)
pandas.core.frame.DataFrame
>>> stanox_dictionary.head()
```

	Location
STANOX	
00005	Aachen
04309	Abbeyhill Junction
04311	Abbeyhill Signal E811
04308	Abbeyhill Turnback Sidings
88601	Abbey Wood

(continues on next page)

(continued from previous page)

```

>>> s_t_dictionary = lid.make_xref_dict(keys=['STANOX', 'TIPLOC'], initials='a')
>>> type(s_t_dictionary)
pandas.core.frame.DataFrame
>>> s_t_dictionary.head()

```

	Location
STANOX TIPLOC	
00005 AACHEN	Aachen
04309 ABHLJN	Abbeyhill Junction
04311 ABHL811	Abbeyhill Signal E811
04308 ABHLTB	Abbeyhill Turnback Sidings
88601 ABWD	Abbey Wood

```

>>> ks = ['STANOX', 'TIPLOC']
>>> ini = 'b'
>>> main_k = 'Data'
>>> s_t_dictionary = lid.make_xref_dict(ks, ini, main_k, as_dict=True)
>>> type(s_t_dictionary)
dict
>>> list(s_t_dictionary.keys())
['Data']
>>> list(s_t_dictionary['Data'].keys())[:5]
[('55115', ''),
 ('23490', 'BABWTHL'),
 ('38306', 'BACHE'),
 ('66021', 'BADESCL'),
 ('81003', 'BADMTN')]

```

lor_code

Collect [Line of Route \(LOR/PRIDE\)](#) codes.

Class

LOR ([data_dir, update, verbose])	A class for collecting data of Line of Route (LOR/PRIDE) .
---	--

LOR

class pyrcs.line_data.lor_code.LOR(data_dir=None, update=False, verbose=True)

A class for collecting data of [Line of Route \(LOR/PRIDE\)](#).

Note: ‘LOR’ and ‘PRIDE’ stands for ‘Line Of Route’ and ‘Possession Resource Information Database’, respectively.

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to None

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to True

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> print(lor.NAME)
Possession Resource Information Database (PRIDE)/Line Of Route (LOR) codes

>>> print(lor.URL)
http://www.railwaycodes.org.uk/pride/pride0.shtm
```

Attributes

<i>KEY</i>	Key of the dict-type data
<i>KEY_ELC</i>	Key of the dict-type data of <i>ELR/LOR converter</i>
<i>KEY_P</i>	Key of the dict-type data of prefixes
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>SHORT_NAME</i>	Short name of the data
<i>URL</i>	URL of the main web page of the data

LOR.KEY

`LOR.KEY = 'LOR'`

Key of the dict-type data

LOR.KEY_ELC

```
LOR.KEY_ELC = 'ELR/LOR converter'
```

Key of the dict-type data of *ELR/LOR converter*

LOR.KEY_P

```
LOR.KEY_P = 'Key to prefixes'
```

Key of the dict-type data of prefixes

LOR.KEY_TO_LAST_UPDATED_DATE

```
LOR.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'
```

Key of the data of the last updated date

LOR.NAME

```
LOR.NAME = 'Possession Resource Information Database (PRIDE)/Line Of Route  
(LOR) codes'
```

Name of the data

LOR.SHORT_NAME

```
LOR.SHORT_NAME = 'Line of Route (LOR/PRIDE) codes'
```

Short name of the data

LOR.URL

```
LOR.URL = 'http://www.railwaycodes.org.uk/pride/pride0.shtm'
```

URL of the main web page of the data

Methods

<code>collect_codes_by_prefix(prefix[, update, ...])</code>	Collect PRIDE/LOR codes by a given prefix.
<code>collect_elr_lor_converter([...])</code>	Collect ELR/LOR converter from source web page.
<code>fetch_codes([update, dump_dir, verbose])</code>	Fetch data of PRIDE/LOR codes.
<code>fetch_elr_lor_converter([update, dump_dir, ...])</code>	Fetch data of ELR/LOR converter.
<code>get_keys_to_prefixes([prefixes_only, ...])</code>	Get the keys to PRIDE/LOR code prefixes.
<code>get_page_urls([update, verbose])</code>	Get URLs to PRIDE/LOR codes with different prefixes.

LOR.collect_codes_by_prefix

`LOR.collect_codes_by_prefix(prefix, update=False, verbose=False)`

Collect PRIDE/LOR codes by a given prefix.

Parameters

- **prefix** (*str*) – prefix of LOR codes
- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

LOR codes for the given prefix

Return type

dict or None

Examples:

```
>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> lor_codes_cy = lor.collect_codes_by_prefix(prefix='CY')
>>> type(lor_codes_cy)
dict
>>> list(lor_codes_cy.keys())
['CY', 'Notes', 'Last updated date']

>>> cy_codes = lor_codes_cy['CY']
>>> type(cy_codes)
pandas.core.frame.DataFrame
>>> cy_codes.head()
   Code  ... Line Name Note
0  CY240  ...      None
```

(continues on next page)

(continued from previous page)

```

1  CY1540  ...      None

[2 rows x 5 columns]

>>> lor_codes_nw = lor.collect_codes_by_prefix(prefix='NW')
>>> type(lor_codes_nw)
dict
>>> list(lor_codes_nw.keys())
['NW/NZ', 'Notes', 'Last updated date']
>>> nw_codes = lor_codes_nw['NW/NZ']
>>> nw_codes.head()
   Code  ... Line Name Note
0  NW1001  ...      None
1  NW1002  ...      None
2  NW1003  ...      None
3  NW1004  ...      None
4  NW1005  ...      None

[5 rows x 5 columns]

>>> lor_codes_xr = lor.collect_codes_by_prefix(prefix='XR')
>>> xr_codes = lor_codes_xr['XR']
>>> type(xr_codes)
dict
>>> list(xr_codes.keys())
['Current codes', 'Past codes']
>>> xr_codes['Current codes']['XR'].head()
   Code  ... Line Name Note
0  XR001  ...      None
1  XR002  ...      None

[2 rows x 5 columns]

```

LOR.collect_elr_lor_converter

`LOR.collect_elr_lor_converter(confirmation_required=True, verbose=False)`

Collect [ELR/LOR converter](#) from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

data of ELR/LOR converter

Return type

dict or None

Examples:

```

>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> elr_lor_conv = lor.collect_elr_lor_converter()
To collect data of ELR/LOR converter
? [No]|Yes: yes
>>> type(elr_lor_conv)
dict
>>> list(elr_lor_conv.keys())
['ELR/LOR converter', 'Last updated date']

>>> elr_loc_conv_data = elr_lor_conv['ELR/LOR converter']
>>> type(elr_loc_conv_data)
pandas.core.frame.DataFrame
>>> elr_loc_conv_data.head()
   ELR  ...                                     LOR_URL
0  AAV  ...  http://www.railwaycodes.org.uk/pride/pridesw.s...
1  ABD  ...  http://www.railwaycodes.org.uk/pride/pridegw.s...
2  ABE  ...  http://www.railwaycodes.org.uk/pride/prideIn.s...
3  ABE1 ...  http://www.railwaycodes.org.uk/pride/prideIn.s...
4  ABE2 ...  http://www.railwaycodes.org.uk/pride/prideIn.s...

[5 rows x 6 columns]

```

LOR.fetch_codes

`LOR.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of PRIDE/LOR codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

LOR codes

Return type

dict

Examples:

```

>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> lor_codes_dat = lor.fetch_codes()
>>> type(lor_codes_dat)

```

(continues on next page)

(continued from previous page)

```
dict
>>> l_codes = lor_codes_dat['LOR']
>>> type(l_codes)
dict
>>> list(l_codes.keys())
['CY', 'EA', 'GW', 'LN', 'MD', 'NW/NZ', 'SC', 'SO', 'SW', 'XR']

>>> cy_codes = l_codes['CY']
>>> type(cy_codes)
dict
>>> list(cy_codes.keys())
['CY', 'Notes', 'Last updated date']
>>> cy_codes['CY']
   Code  ... Line Name Note
0  CY240  ...      None
1  CY1540 ...      None

[2 rows x 5 columns]
```

LOR.fetch_elr_lor_converter

LOR.fetch_elr_lor_converter(update=False, dump_dir=None, verbose=False)

Fetch data of [ELR/LOR converter](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to None
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of ELR/LOR converter

Return type

dict

Examples:

```
>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> elr_lor_conv = lor.fetch_elr_lor_converter()
>>> type(elr_lor_conv)
dict
>>> list(elr_lor_conv.keys())
['ELR/LOR converter', 'Last updated date']

>>> elr_loc_conv_data = elr_lor_conv['ELR/LOR converter']
```

(continues on next page)

(continued from previous page)

```

>>> type(elr_loc_conv_data)
pandas.core.frame.DataFrame
>>> elr_loc_conv_data.head()
   ELR  ...                                     LOR_URL
0  AAV  ...  http://www.railwaycodes.org.uk/pride/pridesw.s...
1  ABD  ...  http://www.railwaycodes.org.uk/pride/pridegw.s...
2  ABE  ...  http://www.railwaycodes.org.uk/pride/prideIn.s...
3  ABE1 ...  http://www.railwaycodes.org.uk/pride/prideIn.s...
4  ABE2 ...  http://www.railwaycodes.org.uk/pride/prideIn.s...

[5 rows x 6 columns]

```

LOR.get_keys_to_prefixes

`LOR.get_keys_to_prefixes(prefixes_only=True, update=False, verbose=False)`

Get the keys to PRIDE/LOR code prefixes.

Parameters

- **prefixes_only** (*bool*) – whether to get only prefixes, defaults to True
- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to True

Returns

keys to LOR code prefixes

Return type

list or dict or None

Examples:

```

>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> keys_to_pfx = lor.get_keys_to_prefixes()

>>> print(keys_to_pfx)
['CY', 'EA', 'GW', 'LN', 'MD', 'NW', 'NZ', 'SC', 'SO', 'SW', 'XR']

>>> keys_to_pfx = lor.get_keys_to_prefixes(prefixes_only=False)
>>> type(keys_to_pfx)
dict
>>> list(keys_to_pfx.keys())
['Key to prefixes', 'Last updated date']

>>> keys_to_pfx_codes = keys_to_pfx['Key to prefixes']
>>> type(keys_to_pfx_codes)
pandas.core.frame.DataFrame
>>> keys_to_pfx_codes.head()

```

(continues on next page)

(continued from previous page)

	Prefixes	Name
0	CY	Wales
1	EA	South Eastern: East Anglia area
2	GW	Great Western (later known as Western)
3	LN	London & North Eastern
4	MD	North West: former Midlands lines

LOR.get_page_urls

`LOR.get_page_urls(update=False, verbose=False)`

Get URLs to [PRIDE/LOR codes](#) with different prefixes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to True

Returns

a list of URLs of web pages hosting LOR codes for each prefix

Return type

list or None

Examples:

```
>>> from pyrcs.line_data import LOR # from pyrcs import LOR

>>> lor = LOR()

>>> lor_urls = lor.get_page_urls()

>>> lor_urls[:2]
['http://www.railwaycodes.org.uk/pride/pridecy.shtm',
 'http://www.railwaycodes.org.uk/pride/prideea.shtm']
```

line_name

Collect [railway line names](#).

Class

<i>LineNames</i> ([data_dir, update, verbose])	A class for collecting data of railway line names .
--	---

LineNames

class pyrcs.line_data.line_name.LineNames(*data_dir=None, update=False, verbose=True*)

A class for collecting data of [railway line names](#).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last update date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import LineNames # from pyrcs import LineNames

>>> ln = LineNames()

>>> print(ln.NAME)
Railway line names

>>> print(ln.URL)
http://www.railwaycodes.org.uk/misc/line_names.shtm
```

Attributes

<i>KEY</i>	Key of the dict -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

LineNames.KEY

LineNames.KEY = 'Line names'

Key of the `dict`-type data

LineNames.KEY_TO_LAST_UPDATED_DATE

LineNames.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'

Key of the data of the last updated date

LineNames.NAME

LineNames.NAME = 'Railway line names'

Name of the data

LineNames.URL

LineNames.URL = 'http://www.railwaycodes.org.uk/line/line_names.shtm'

URL of the main web page of the data

Methods

<code>collect_codes</code> ([confirmation_required, verbose])	Collect data of <code>railway line names</code> from source web page.
<code>fetch_codes</code> ([update, dump_dir, verbose])	Fetch data of <code>railway line names</code> .

LineNames.collect_codes

LineNames.collect_codes(confirmation_required=True, verbose=False)

Collect data of `railway line names` from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to `True`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

railway line names and routes data and date of when the data was last updated

Return type

`dict` or `None`

Examples:

```

>>> from pyrcs.line_data import LineNames # from pyrcs import LineNames

>>> ln = LineNames()

>>> line_names_codes = ln.collect_codes()
To collect British railway line names
? [No]|Yes: yes
>>> type(line_names_codes)
dict
>>> list(line_names_codes.keys())
['Line names', 'Last updated date']

>>> ln.KEY
'Line names'

>>> line_names_codes_dat = line_names_codes[ln.KEY]
>>> type(line_names_codes_dat)
pandas.core.frame.DataFrame
>>> line_names_codes_dat.head()
   Line name  ... Route_note
0   Abbey Line  ...      None
1  Airedale Line  ...      None
2   Argyle Line  ...      None
3  Arun Valley Line  ...      None
4  Atlantic Coast Line  ...      None

[5 rows x 3 columns]

```

LineNames.fetch_codes

`LineNames.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of [railway line names](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str* or *None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

railway line names and routes data and date of when the data was last updated

Return type

dict

Examples:

```

>>> from pyrcs.line_data import LineNames # from pyrcs import LineNames

>>> ln = LineNames()

>>> line_names_codes = ln.fetch_codes()
>>> type(line_names_codes)
dict
>>> list(line_names_codes.keys())
['Line names', 'Last updated date']

>>> ln.KEY
'Line names'

>>> line_names_codes_dat = line_names_codes[ln.KEY]

>>> type(line_names_codes_dat)
pandas.core.frame.DataFrame
>>> line_names_codes_dat.head()
   Line name  ... Route_note
0   Abbey Line  ...      None
1  Airedale Line  ...      None
2   Argyle Line  ...      None
3  Arun Valley Line  ...      None
4  Atlantic Coast Line  ...      None

[5 rows x 3 columns]

```

trk_diagr

Collect British railway track diagrams.

Class

<i>TrackDiagrams</i> ([data_dir, update, verbose])	A class for collecting data of British railway track diagrams.
--	--

TrackDiagrams

class pyrcs.line_data.trk_diagr.**TrackDiagrams**(data_dir=None, update=False, verbose=True)

A class for collecting data of British railway track diagrams.

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to None
- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to True

Variables

- `catalogue` (*dict*) – catalogue of the data
- `last_updated_date` (*str*) – last updated date
- `data_dir` (*str*) – path to the data directory
- `current_data_dir` (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import TrackDiagrams # from pyrcs import TrackDiagrams

>>> td = TrackDiagrams()

>>> print(td.NAME)
Railway track diagrams

>>> print(td.URL)
http://www.railwaycodes.org.uk/line/diagrams0.shtm
```

Attributes

<i>KEY</i>	Key of the <i>dict</i> -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

TrackDiagrams.KEY

```
TrackDiagrams.KEY = 'Track diagrams'
```

Key of the *dict*-type data

TrackDiagrams.KEY_TO_LAST_UPDATED_DATE

```
TrackDiagrams.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'
```

Key of the data of the last updated date

TrackDiagrams.NAME

```
TrackDiagrams.NAME = 'Railway track diagrams'
```

Name of the data

TrackDiagrams.URL

TrackDiagrams.URL = 'http://www.railwaycodes.org.uk/line/diagrams0.shtm'

URL of the main web page of the data

Methods

bridge

Collect data of British railway bridges.

Class

<i>Bridges</i> ([data_dir, verbose])	A class for collecting data of railway bridges.
--------------------------------------	---

Bridges

class pyrcs.line_data.bridge.**Bridges**(data_dir=None, verbose=True)

A class for collecting data of railway bridges.

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to True

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last update date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.line_data import Bridges # from pyrcs import Bridges
>>> bdg = Bridges()
>>> print(bdg.NAME)
Railway bridges
>>> print(bdg.URL)
http://www.railwaycodes.org.uk/bridges/bridges0.shtm
```

Attributes

<i>KEY</i>	Key of the dict -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

Bridges.KEY

`Bridges.KEY = 'Bridges'`
Key of the [dict](#)-type data

Bridges.KEY_TO_LAST_UPDATED_DATE

`Bridges.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'`
Key of the data of the last updated date

Bridges.NAME

`Bridges.NAME = 'Railway bridges'`
Name of the data

Bridges.URL

`Bridges.URL = 'http://www.railwaycodes.org.uk/bridges/bridges0.shtm'`
URL of the main web page of the data

Methods

<i>collect_codes</i> ([confirmation_required, verbose])	Collect codes of railway bridges from source web page.
<i>fetch_codes</i> ([update, dump_dir, verbose])	Fetch codes of railway bridges .

Bridges.collect_codes

`Bridges.collect_codes(confirmation_required=True, verbose=False)`

Collect codes of railway bridges from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of railway bridges and date of when the data was last updated

Return type

dict or None

Examples:

```
>>> from pyrcs.line_data import Bridges # from pyrcs import Bridges

>>> bdg = Bridges()

>>> bdg_codes = bdg.collect_codes()
To collect data of railway bridges
? [No]|Yes: yes

>>> type(bdg_codes)
dict
>>> list(bdg_codes.keys())
['East Coast Main Line',
 'West Coast Main Line',
 'Scotland',
 'Elizabeth Line',
 'London Overground',
 'Anglia',
 'London Underground',
 'Key to text presentation conventions']

>>> bdg_codes['Key to text presentation conventions']
{'Bold': 'Existing bridges',
 'Bold italic': 'Existing locations',
 'Light italic': 'Former/historical locations',
 'Red': 'Stations',
 'Deep red': 'Level crossings',
 'Brown': 'Ventilation shafts',
 'Purple': 'Junctions',
 'Black, grey': 'Bridges and culverts',
 'Green': 'Tunnel portals',
 'Bright blue': 'Viaducts',
 'Deep blue': 'Boundaries'}
```

Bridges.fetch_codes

`Bridges.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch codes of [railway bridges](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of railway bridges and date of when the data was last updated

Return type

dict or `None`

Examples:

```
>>> from pyrcs.line_data import Bridges # from pyrcs import Bridges

>>> bdg = Bridges()

>>> bdg_codes = bdg.fetch_codes()

>>> type(bdg_codes)
dict
>>> list(bdg_codes.keys())
['East Coast Main Line',
 'West Coast Main Line',
 'Scotland',
 'Elizabeth Line',
 'London Overground',
 'Anglia',
 'London Underground',
 'Key to text presentation conventions']

>>> bdg_codes['Key to text presentation conventions']
{'Bold': 'Existing bridges',
 'Bold italic': 'Existing locations',
 'Light italic': 'Former/historical locations',
 'Red': 'Stations',
 'Deep red': 'Level crossings',
 'Brown': 'Ventilation shafts',
 'Purple': 'Junctions',
 'Black, grey': 'Bridges and culverts',
 'Green': 'Tunnel portals',
 'Bright blue': 'Viaducts',
 'Deep blue': 'Boundaries'}
```

3.1.2 other_assets

A sub-package of modules for collecting codes of [other assets](#).

(See also [OtherAssets](#).)

Sub-modules

sig_box	Collect data of signal box prefix codes.
tunnel	Collect data of railway tunnel lengths.
viaduct	Collect codes of railway viaducts .
station	Collect railway station data.
depot	Collect data of depot codes .
feature	Collect codes of infrastructure features.

sig_box

Collect data of [signal box](#) prefix codes.

Class

SignalBoxes ([data_dir , update , verbose])	A class for collecting data of signal box prefix codes.
---	---

SignalBoxes

class `pyrcs.other_assets.sig_box.SignalBoxes(data_dir=None, update=False, verbose=True)`

A class for collecting data of [signal box](#) prefix codes.

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to None
- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to True

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> print(sb.NAME)
Signal box prefix codes

>>> print(sb.URL)
http://www.railwaycodes.org.uk/signal/signal_boxes0.shtm
```

Attributes

<code>KEY</code>	Key of the dict-type data
<code>KEY_TO_BELL_CODES</code>	Key of the dict-type data of 'bell codes'
<code>KEY_TO_IRELAND</code>	Key of the dict-type data of 'Ireland'
<code>KEY_TO_LAST_UPDATED_DATE</code>	Key of the data of the last updated date
<code>KEY_TO_NON_NATIONAL_RAIL</code>	Key of the dict-type data of 'non-national rail'
<code>KEY_TO_WRMASD</code>	Key of the dict-type data of 'WR (Western region) MAS (multiple aspect signalling) dates'
<code>NAME</code>	Name of the data
<code>URL</code>	URL of the main web page of the data

SignalBoxes.KEY

`SignalBoxes.KEY = 'Signal boxes'`
 Key of the dict-type data

SignalBoxes.KEY_TO_BELL_CODES

`SignalBoxes.KEY_TO_BELL_CODES = 'Bell codes'`
 Key of the dict-type data of 'bell codes'

SignalBoxes.KEY_TO_IRELAND

`SignalBoxes.KEY_TO_IRELAND = 'Ireland'`
 Key of the dict-type data of 'Ireland'

SignalBoxes.KEY_TO_LAST_UPDATED_DATE

```
SignalBoxes.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'
```

Key of the data of the last updated date

SignalBoxes.KEY_TO_NON_NATIONAL_RAIL

```
SignalBoxes.KEY_TO_NON_NATIONAL_RAIL = 'Non-National Rail'
```

Key of the dict-type data of *'non-national rail'*

SignalBoxes.KEY_TO_WRMASD

```
SignalBoxes.KEY_TO_WRMASD = 'WR MAS dates'
```

Key of the dict-type data of *'WR (Western region) MAS (multiple aspect signalling) dates'*

SignalBoxes.NAME

```
SignalBoxes.NAME = 'Signal box prefix codes'
```

Name of the data

SignalBoxes.URL

```
SignalBoxes.URL = 'http://www.railwaycodes.org.uk/signal/signal_boxes0.shtm'
```

URL of the main web page of the data

Methods

<code>collect_bell_codes</code> ([confirmation_required, ...])	Collect data of bell codes from source web page.
<code>collect_ireland_codes</code> ([...])	Collect data of Irish signal cabin prefix codes from source web page.
<code>collect_non_national_rail_codes</code> ([...])	Collect signal box prefix codes of non-national rail from source web page.
<code>collect_prefix_codes</code> (initial[, update, verbose])	Collect signal box prefix codes beginning with a given initial letter from source web page.
<code>collect_wr_mas_dates</code> ([...])	Collect data of WR (western region) MAS (multiple aspect signalling) dates from source web page.
<code>fetch_bell_codes</code> ([update, dump_dir, verbose])	Fetch data of bell codes .
<code>fetch_ireland_codes</code> ([update, dump_dir, verbose])	Fetch data of Irish signal cabin prefix codes .
<code>fetch_non_national_rail_codes</code> ([update, ...])	Fetch signal box prefix codes of non-national rail .
<code>fetch_prefix_codes</code> ([update, dump_dir, verbose])	Fetch data of signal box prefix codes.
<code>fetch_wr_mas_dates</code> ([update, dump_dir, verbose])	Fetch data of WR (western region) MAS (multiple aspect signalling) dates.

SignalBoxes.collect_bell_codes

`SignalBoxes.collect_bell_codes(confirmation_required=True, verbose=False)`

Collect data of **bell codes** from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

bell codes for the signal box prefix codes

Return type

dict or None

Examples:

```
>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes
>>> sb = SignalBoxes()
```

(continues on next page)

(continued from previous page)

```

>>> sb_bell_codes = sb.collect_bell_codes()
To collect data of Bell codes
? [No]|Yes: yes
>>> type(sb_bell_codes)
dict
>>> list(sb_bell_codes.keys())
['Bell codes', 'Last updated date']

>>> sb.KEY_TO_BELL_CODES
'Bell codes'

>>> sb_bell_codes_dat = sb_bell_codes[sb.KEY_TO_BELL_CODES]
>>> type(sb_bell_codes_dat)
collections.OrderedDict
>>> list(sb_bell_codes_dat.keys())
['Network Rail codes',
 'Southern Railway codes',
 'Lancashire & Yorkshire Railway codes']

>>> sb_nr_bell_codes = sb_bell_codes_dat['Network Rail codes']
>>> type(sb_nr_bell_codes)
dict
>>> list(sb_nr_bell_codes.keys())
['Codes', 'Notes']
>>> sb_nr_bell_codes_dat = sb_nr_bell_codes['Codes']
>>> type(sb_nr_bell_codes_dat)
pandas.core.frame.DataFrame
>>> sb_nr_bell_codes_dat.head()
   Code                                     Meaning
0      1                               Call attention
1    1-1                Answer telephone [withdrawn 2007]
2  1-1-6        Police assistance urgently required
3    1-2  Signaller required on telephone [added 2007]
4  1-2-1                Train approaching

```

SignalBoxes.collect_ireland_codes

SignalBoxes.collect_ireland_codes(*confirmation_required=True, verbose=False*)

Collect data of [Irish signal cabin prefix codes](#) from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

signal box prefix codes of Ireland

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> ireland_sb_codes = sb.collect_ireland_codes()
To collect data of signal box prefix codes of Ireland
? [No]|Yes: yes
>>> type(ireland_sb_codes)
dict
>>> list(ireland_sb_codes.keys())
['Ireland', 'Notes', 'Last updated date']

>>> sb.KEY_TO_IRELAND
'Ireland'

>>> ireland_sb_codes_dat = ireland_sb_codes[sb.KEY_TO_IRELAND]
>>> type(ireland_sb_codes_dat)
pandas.core.frame.DataFrame
>>> ireland_sb_codes_dat.head()
   Code Signal Cabin      Note
0    AD      Adelaide
1    AN      Antrim
2    AE      Athlone
3  AE R      Distant signals
4    XG      Level crossing signals

```

SignalBoxes.collect_non_national_rail_codes

`SignalBoxes.collect_non_national_rail_codes(confirmation_required=True, verbose=False)`

Collect signal box prefix codes of **non-national rail** from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

signal box prefix codes of non-national rail

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> nnr_codes = sb.collect_non_national_rail_codes()
To collect data of non-national rail signal box prefix codes

```

(continues on next page)

(continued from previous page)

```

? [No] | Yes: yes

>>> type(nnr_codes)
dict
>>> list(nnr_codes.keys())
['Non-National Rail', 'Last updated date']

>>> sb.KEY_TO_NON_NATIONAL_RAIL
'Non-National Rail'

>>> nnr_codes_dat = nnr_codes[sb.KEY_TO_NON_NATIONAL_RAIL]
>>> type(nnr_codes_dat)
dict
>>> list(nnr_codes_dat.keys())
['Croydon Tramlink signals',
 'Docklands Light Railway signals',
 'Edinburgh Tramway signals',
 'Glasgow Subway signals',
 'London Underground signals',
 'Luas signals',
 'Manchester Metrolink signals',
 'Midland Metro signals',
 'Nottingham Tram signals',
 'Sheffield Supertram signals',
 'Tyne & Wear Metro signals',
 "Heritage, minor and miniature railways and other 'special' signals"]

>>> lu_signals_codes = nnr_codes_dat['London Underground signals']
>>> type(lu_signals_codes)
dict
>>> list(lu_signals_codes.keys())
['Codes', 'Notes']
>>> type(lu_signals_codes['Codes'])
pandas.core.frame.DataFrame
>>> lu_signals_codes['Codes'].head()
  Code  ... Became or taken over by (where known)
0  BMX  ...                                     -
1   A   ...                                     -
2   S   ...                                     -
3   X   ...                                     -
4   R   ...                                     -

[5 rows x 5 columns]

```

SignalBoxes.collect_prefix_codes

SignalBoxes.collect_prefix_codes(*initial*, *update=False*, *verbose=False*)

Collect signal box prefix codes beginning with a given initial letter from source web page.

Parameters

- **initial** (*str*) – initial letter of signal box name (for specifying a target URL)
- **update** (*bool*) – whether to do an update check (for the package data),

defaults to False

- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

data of signal box prefix codes beginning with the given initial letter and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> sb_a_codes = sb.collect_prefix_codes(initial='a')

>>> type(sb_a_codes)
dict
>>> list(sb_a_codes.keys())
['A', 'Last updated date']

>>> sb_a_codes_dat = sb_a_codes['A']
>>> type(sb_a_codes_dat)
pandas.core.frame.DataFrame
>>> sb_a_codes_dat.head()
   Code  Signal Box  ...  Closed  Control to
0  AF  Abbey Foregate Junction  ...  16 February 1992  Nuneaton (NN)
1  AJ  Abbey Junction  ...  16 February 1992  Nuneaton (NN)
2  R  Abbey Junction  ...  16 February 1992  Nuneaton (NN)
3  AW  Abbey Wood  ...  13 July 1975  Dartford (D)
4  AE  Abbey Works East  ...  1 November 1987  Port Talbot (PT)

[5 rows x 8 columns]
```

SignalBoxes.collect_wr_mas_dates

SignalBoxes.collect_wr_mas_dates(*confirmation_required=True, verbose=False*)

Collect data of **WR** (western region) **MAS** (multiple aspect signalling) dates from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

data of WR (western region) MAS (multiple aspect signalling) dates

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> sb_wr_mas_dates = sb.collect_wr_mas_dates()
To collect data of WR MAS dates
? [No]|Yes: yes
>>> type(sb_wr_mas_dates)
dict
>>> list(sb_wr_mas_dates.keys())
['WR MAS dates', 'Last updated date']

>>> sb.KEY_TO_WRMASD
'WR MAS dates'

>>> sb_wr_mas_dates_dat = sb_wr_mas_dates[sb.KEY_TO_WRMASD]
>>> type(sb_wr_mas_dates_dat)
collections.defaultdict
>>> list(sb_wr_mas_dates_dat.keys())
['Paddington-Hayes',
 'Birmingham',
 'Plymouth',
 'Reading-Hayes',
 'Newport Multiple Aspect Signalling',
 'Old Oak Common (original scheme)',
 'Port Talbot Multiple Aspect Signalling',
 'Reading Multiple Aspect Signalling',
 'Original Barry amalgamation',
 'Cornwall',
 'Cardiff Multiple Aspect Signalling',
 'Central Wales',
 'Gloucester Multiple Aspect Signalling',
 'Swindon Multiple Aspect Signalling',
 'Bristol Division (miscellaneous schemes)',
 'Old Oak Common (new panel)',
 'Western Valleys',
 'London Division (miscellaneous schemes)',
 'Cardiff Valleys',
 'Newport Extension',
 'Barry centralisation',
 'Slough/Reading (developments)',
 'Bristol Multiple Aspect Signalling',
 'Port Talbot Multiple Aspect Signalling (extensions and developments)',
 'Miscellaneous',
 'Old Oak Common (rationalisation)',
 'Centralisation schemes',
 'Bristol (developments)',
 'Devon',
 'Didcot/Swindon/Bristol reversible working',
 'Reading West extension',
 'Carmarthen-Whitland']

>>> sb_wr_mas_dates_dat['Paddington-Hayes']

```

(continues on next page)

(continued from previous page)

	Stage	Date	Area
0	1A	12 April 1953	Hayes-Hanwell
1	1B	20 March 1955	Hanwell-Acton Middle
2	1C	1 February 1959	Acton West-Friars Junction

SignalBoxes.fetch_bell_codes

`SignalBoxes.fetch_bell_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of bell codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – name of package data folder, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of bell codes

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> sb_bell_codes = sb.fetch_bell_codes()
>>> type(sb_bell_codes)
dict
>>> list(sb_bell_codes.keys())
['Bell codes', 'Last updated date']

>>> sb.KEY_TO_BELL_CODES
'Bell codes'

>>> sb_bell_codes_dat = sb_bell_codes[sb.KEY_TO_BELL_CODES]
>>> type(sb_bell_codes_dat)
collections.OrderedDict
>>> list(sb_bell_codes_dat.keys())
['Network Rail codes',
 'Southern Railway codes',
 'Lancashire & Yorkshire Railway codes']

>>> sb_nr_bell_codes = sb_bell_codes_dat['Network Rail codes']
>>> type(sb_nr_bell_codes)
dict
>>> list(sb_nr_bell_codes.keys())
['Codes', 'Notes']
```

(continues on next page)

(continued from previous page)

```

>>> sb_nr_bell_codes_dat = sb_nr_bell_codes['Codes']
>>> type(sb_nr_bell_codes_dat)
pandas.core.frame.DataFrame
>>> sb_nr_bell_codes_dat.head()
   Code                                     Meaning
0      1                               Call attention
1    1-1          Answer telephone [withdrawn 2007]
2  1-1-6      Police assistance urgently required
3    1-2  Signaller required on telephone [added 2007]
4  1-2-1                Train approaching

```

SignalBoxes.fetch_ireland_codes

SignalBoxes.fetch_ireland_codes(update=False, dump_dir=None, verbose=False)

Fetch data of Irish signal cabin prefix codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str* or *None*) – name of package data folder, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

signal box prefix codes of Ireland

Return type

dict

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> ireland_sb_codes = sb.fetch_ireland_codes()
>>> type(ireland_sb_codes)
dict
>>> list(ireland_sb_codes.keys())
['Ireland', 'Notes', 'Last updated date']

>>> sb.KEY_TO_IRELAND
'Ireland'

>>> ireland_sb_codes_dat = ireland_sb_codes[sb.KEY_TO_IRELAND]
>>> type(ireland_sb_codes_dat)
pandas.core.frame.DataFrame
>>> ireland_sb_codes_dat.head()
   Code Signal Cabin                                     Note
0    AD      Adelaide
1    AN      Antrim

```

(continues on next page)

(continued from previous page)

```

2   AE      Athlone
3   AE R          Distant signals
4   XG          Level crossing signals

```

SignalBoxes.fetch_non_national_rail_codes

SignalBoxes.fetch_non_national_rail_codes(update=False, dump_dir=None, verbose=False)

Fetch signal box prefix codes of **non-national rail**.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str* or *None*) – name of package data folder, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

signal box prefix codes of non-national rail

Return type

dict

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> nnr_codes = sb.fetch_non_national_rail_codes()

>>> type(nnr_codes)
dict
>>> list(nnr_codes.keys())
['Non-National Rail', 'Last updated date']

>>> sb.KEY_TO_NON_NATIONAL_RAIL
'Non-National Rail'

>>> nnr_codes_dat = nnr_codes[sb.KEY_TO_NON_NATIONAL_RAIL]
>>> type(nnr_codes_dat)
dict
>>> list(nnr_codes_dat.keys())
['Croydon Tramlink signals',
 'Docklands Light Railway signals',
 'Edinburgh Tramway signals',
 'Glasgow Subway signals',
 'London Underground signals',
 'Luas signals',
 'Manchester Metrolink signals',
 'Midland Metro signals',
 'Nottingham Tram signals',

```

(continues on next page)

(continued from previous page)

```

'Sheffield Supertram signals',
'Tyne & Wear Metro signals',
"Heritage, minor and miniature railways and other 'special' signals"]

>>> lu_signals_codes = nnr_codes_dat['London Underground signals']
>>> type(lu_signals_codes)
dict
>>> list(lu_signals_codes.keys())
['Codes', 'Notes']
>>> type(lu_signals_codes['Codes'])
pandas.core.frame.DataFrame
>>> lu_signals_codes['Codes'].head()
   Code  ... Became or taken over by (where known)
0  BMX  ...                                     -
1    A  ...                                     -
2    S  ...                                     -
3    X  ...                                     -
4    R  ...                                     -

[5 rows x 5 columns]

```

SignalBoxes.fetch_prefix_codes

SignalBoxes.fetch_prefix_codes(update=False, dump_dir=None, verbose=False)

Fetch data of signal box prefix codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str* or *None*) – name of package data folder, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

data of location codes and date of when the data was last updated

Return type

dict

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> sb_prefix_codes = sb.fetch_prefix_codes()

>>> type(sb_prefix_codes)
dict
>>> list(sb_prefix_codes.keys())
['Signal boxes', 'Last updated date']

```

(continues on next page)

(continued from previous page)

```

>>> sb.KEY
'Signal boxes'

>>> sb_prefix_codes_dat = sb_prefix_codes[sb.KEY]
>>> type(sb_prefix_codes_dat)
pandas.core.frame.DataFrame
>>> sb_prefix_codes_dat.head()
   Code      Signal Box  ...      Closed      Control to
0  AF  Abbey Foregate Junction  ...      16 February 1992  Nuneaton (NN)
1  AJ      Abbey Junction  ...      16 February 1992  Nuneaton (NN)
2  R      Abbey Junction  ...      16 February 1992  Nuneaton (NN)
3  AW      Abbey Wood  ...      13 July 1975  Dartford (D)
4  AE      Abbey Works East  ...      1 November 1987  Port Talbot (PT)

[5 rows x 8 columns]

```

SignalBoxes.fetch_wr_mas_dates

SignalBoxes.fetch_wr_mas_dates(update=False, dump_dir=None, verbose=False)

Fetch data of **WR** (western region) **MAS** (multiple aspect signalling) dates.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str or None*) – name of package data folder, defaults to None
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of **WR** (western region) **MAS** (multiple aspect signalling) dates

Return type

dict

Examples:

```

>>> from pyrcs.other_assets import SignalBoxes # from pyrcs import SignalBoxes

>>> sb = SignalBoxes()

>>> sb_wr_mas_dates = sb.fetch_wr_mas_dates()
>>> type(sb_wr_mas_dates)
dict
>>> list(sb_wr_mas_dates.keys())
['WR MAS dates', 'Last updated date']

>>> sb.KEY_TO_WRMASD
'WR MAS dates'

>>> sb_wr_mas_dates_dat = sb_wr_mas_dates[sb.KEY_TO_WRMASD]

```

(continues on next page)

(continued from previous page)

```

>>> type(sb_wr_mas_dates_dat)
collections.defaultdict
>>> list(sb_wr_mas_dates_dat.keys())
['Paddington-Hayes',
 'Birmingham',
 'Plymouth',
 'Reading-Hayes',
 'Newport Multiple Aspect Signalling',
 'Old Oak Common (original scheme)',
 'Port Talbot Multiple Aspect Signalling',
 'Reading Multiple Aspect Signalling',
 'Original Barry amalgamation',
 'Cornwall',
 'Cardiff Multiple Aspect Signalling',
 'Central Wales',
 'Gloucester Multiple Aspect Signalling',
 'Swindon Multiple Aspect Signalling',
 'Bristol Division (miscellaneous schemes)',
 'Old Oak Common (new panel)',
 'Western Valleys',
 'London Division (miscellaneous schemes)',
 'Cardiff Valleys',
 'Newport Extension',
 'Barry centralisation',
 'Slough/Reading (developments)',
 'Bristol Multiple Aspect Signalling',
 'Port Talbot Multiple Aspect Signalling (extensions and developments)',
 'Miscellaneous',
 'Old Oak Common (rationalisation)',
 'Centralisation schemes',
 'Bristol (developments)',
 'Devon',
 'Didcot/Swindon/Bristol reversible working',
 'Reading West extension',
 'Carmarthen-Whitland']

>>> sb_wr_mas_dates_dat['Paddington-Hayes']

```

	Stage	Date	Area
0	1A	12 April 1953	Hayes-Hanwell
1	1B	20 March 1955	Hanwell-Acton Middle
2	1C	1 February 1959	Acton West-Friars Junction

tunnel

Collect data of railway tunnel lengths.

Class

<i>Tunnels</i> ([data_dir, update, verbose])	A class for collecting data of railway tunnel lengths .
--	---

Tunnels

class `pyrcs.other_assets.tunnel.Tunnels`(*data_dir=None, update=False, verbose=True*)

A class for collecting data of [railway tunnel lengths](#).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.other_assets import Tunnels # from pyrcs import Tunnels

>>> tunl = Tunnels()

>>> print(tunl.NAME)
Railway tunnel lengths

>>> print(tunl.URL)
http://www.railwaycodes.org.uk/tunnels/tunnels0.shtm
```

Attributes

<i>KEY</i>	Key of the dict -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

Tunnels.KEY

```
Tunnels.KEY = 'Tunnels'
```

Key of the `dict`-type data

Tunnels.KEY_TO_LAST_UPDATED_DATE

```
Tunnels.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'
```

Key of the data of the last updated date

Tunnels.NAME

```
Tunnels.NAME = 'Railway tunnel lengths'
```

Name of the data

Tunnels.URL

```
Tunnels.URL = 'http://www.railwaycodes.org.uk/tunnels/tunnels0.shtm'
```

URL of the main web page of the data

Methods

<code>collect_codes_by_page</code> (page_no[, update, verbose])	Collect data of <code>railway tunnel lengths</code> for a page number from source web page.
<code>fetch_codes</code> ([update, dump_dir, verbose])	Fetch data of <code>railway tunnel lengths</code> .
<code>parse_length</code> (x)	Parse data in 'Length' column, i.e. convert miles/yards to metres.

Tunnels.collect_codes_by_page

```
Tunnels.collect_codes_by_page(page_no, update=False, verbose=False)
```

Collect data of `railway tunnel lengths` for a page number from source web page.

Parameters

- **page_no** (*int* or *str*) – page number; valid values include 1, 2, 3 and 4
- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

data of tunnel lengths on page page_no and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Tunnels # from pyrcs import Tunnels

>>> tunl = Tunnels()

>>> tunl_len_1 = tunl.collect_codes_by_page(page_no=1)
>>> type(tunl_len_1)
dict
>>> list(tunl_len_1.keys())
['Page 1 (A-F)', 'Last updated date']

>>> tunl_len_1_codes = tunl_len_1['Page 1 (A-F)']
>>> type(tunl_len_1_codes)
pandas.core.frame.DataFrame
>>> tunl_len_1_codes.head()
   Name Other names, remarks ... Length (metres) Length (note)
0  Abbotscliffe                ...      1775.7648
1  Abercanaid      see Merthyr ...           NaN  Unavailable
2  Aberchalder      see Loch Oich ...           NaN  Unavailable
3  Aberdovey No 1  also called Frongoch ...      182.8800
4  Aberdovey No 2  also called Morfor ...      200.2536

[5 rows x 11 columns]

>>> tunl_len_4 = tunl.collect_codes_by_page(page_no=4)
>>> type(tunl_len_4)
dict
>>> list(tunl_len_4.keys())
['Page 4 (others)', 'Last updated date']

>>> tunl_len_4_codes = tunl_len_4['Page 4 (others)']
>>> type(tunl_len_4_codes)
dict
>>> list(tunl_len_4_codes.keys())
['Tunnels on industrial and other minor lines',
 'Large bridges that are not officially tunnels but could appear to be so']

>>> tunl_len_4_dat = tunl_len_4_codes['Tunnels on industrial and other minor lines']
>>> type(tunl_len_4_dat)
pandas.core.frame.DataFrame
>>> tunl_len_4_dat.head()
   Name Other names, remarks ... Length (metres) Length (note)
0  Ashes Quarry                ...      56.6928
1  Ashey Down Quarry            ...      33.8328
2  Baileycroft Quarry No 1      ...      28.3464
3  Baileycroft Quarry No 2      ...      21.0312
4  Basfords Hill                ...      46.6344

[5 rows x 6 columns]
```

Tunnels.fetch_codes

`Tunnels.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of [railway tunnel lengths](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – name of a folder where the pickle file is to be saved, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of railway tunnel lengths (including the name, length, owner and relative location) and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Tunnels # from pyrcs import Tunnels

>>> tunl = Tunnels()

>>> tunl_len_codes = tunl.fetch_codes()

>>> type(tunl_len_codes)
dict
>>> list(tunl_len_codes.keys())
['Tunnels', 'Last updated date']

>>> tunl.KEY
'Tunnels'

>>> tunl_len_codes_dat = tunl_len_codes[tunl.KEY]
>>> type(tunl_len_codes_dat)
dict
>>> list(tunl_len_codes_dat.keys())
['Page 1 (A-F)', 'Page 2 (G-P)', 'Page 3 (Q-Z)', 'Page 4 (others)']

>>> page_1 = tunl_len_codes_dat['Page 1 (A-F)']
>>> type(page_1)
pandas.core.frame.DataFrame
>>> page_1.head()
   Name  Other names, remarks  ... Length (metres) Length (note)
0  Abbotscliffe              ...      1775.7648
1  Abercanaid      see Merthyr  ...           NaN  Unavailable
2  Aberchalder      see Loch Oich  ...           NaN  Unavailable
3  Aberdovey No 1  also called Frongoch  ...      182.8800
4  Aberdovey No 2  also called Morfor  ...      200.2536

[5 rows x 11 columns]
```

Tunnels.parse_length

static Tunnels.parse_length(*x*)

Parse data in 'Length' column, i.e. convert miles/yards to metres.

Parameters

x (*str* or *None*) – raw length data

Returns

parsed length data and, if any, additional information associated with it

Return type

tuple

Examples:

```
>>> from pyrcs.other_assets import Tunnels # from pyrcs import Tunnels

>>> tunl = Tunnels()

>>> tunl.parse_length('')
(nan, 'Unavailable')

>>> tunl.parse_length('1m 182y')
(1775.7648, None)

>>> tunl.parse_length('formerly 0m236y')
(215.7984, 'Formerly')

>>> tunl.parse_length('0.325km (0m 356y)')
(325.5264, '0.325km')

>>> tunl.parse_length("0m 48yd- (['0m 58yd'])")
(48.4632, '43.89-53.04 metres')
```

viaduct

Collect codes of [railway viaducts](#).

Class

Viaducts([*data_dir*, *update*, *verbose*])

A class for collecting codes of [railway viaducts](#).

Viaducts

class `pyrcs.other_assets.viaduct.Viaducts`(*data_dir=None, update=False, verbose=True*)

A class for collecting codes of [railway viaducts](#).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.other_assets import Viaducts # from pyrcs import Viaducts

>>> vdct = Viaducts()

>>> print(vdct.NAME)
Railway viaducts

>>> print(vdct.URL)
http://www.railwaycodes.org.uk/viaducts/viaducts0.shtm
```

Attributes

<i>KEY</i>	Key of the dict -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

Viaducts.KEY

```
Viaducts.KEY = 'Viaducts'
```

Key of the `dict`-type data

Viaducts.KEY_TO_LAST_UPDATED_DATE

```
Viaducts.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'
```

Key of the data of the last updated date

Viaducts.NAME

```
Viaducts.NAME = 'Railway viaducts'
```

Name of the data

Viaducts.URL

```
Viaducts.URL = 'http://www.railwaycodes.org.uk/viaducts/viaducts0.shtm'
```

URL of the main web page of the data

Methods

<code>collect_codes_by_page</code> (page_no[, update, verbose])	Collect data of <code>railway viaducts</code> for a given page number from source web page.
<code>fetch_codes</code> ([update, dump_dir, verbose])	Fetch data of <code>railway viaducts</code> .

Viaducts.collect_codes_by_page

```
Viaducts.collect_codes_by_page(page_no, update=False, verbose=False)
```

Collect data of `railway viaducts` for a given page number from source web page.

Parameters

- **page_no** (*int* or *str*) – page number; valid values include 1, 2, 3, 4, 5, and 6
- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

data of railway viaducts on page `page_no` and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Viaducts # from pyrcs import Viaducts

>>> vdct = Viaducts()

>>> vdct_1_codes = vdct.collect_codes_by_page(page_no=1)
>>> type(vdct_1_codes)
dict
>>> list(vdct_1_codes.keys())
['Page 1 (A-C)', 'Last updated date']

>>> vdct_1_codes_dat = vdct_1_codes['Page 1 (A-C)']
>>> type(vdct_1_codes_dat)
pandas.core.frame.DataFrame
>>> vdct_1_codes_dat.head()
   Name  ... Spans
0    7 Arches  ...    7
1    36 Arch  ...   36
2    42 Arch  ...
3    A698    ...    5
4  Abattoir Road  ...    8

[5 rows x 7 columns]
```

Viaducts.fetch_codes

`Viaducts.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of [railway viaducts](#).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – name of a folder where the pickle file is to be saved, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of railway viaducts and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Viaducts # from pyrcs import Viaducts

>>> vdct = Viaducts()
```

(continues on next page)

(continued from previous page)

```

>>> vdct_codes = vdct.fetch_codes()
>>> type(vdct_codes)
dict
>>> list(vdct_codes.keys())
['Viaducts', 'Last updated date']

>>> vdct.KEY
'Viaducts'

>>> vdct_codes_dat = vdct_codes[vdct.KEY]
>>> type(vdct_codes_dat)
dict
>>> list(vdct_codes_dat.keys())
['Page 1 (A-C)',
 'Page 2 (D-G)',
 'Page 3 (H-K)',
 'Page 4 (L-P)',
 'Page 5 (Q-S)',
 'Page 6 (T-Z)']

>>> vdct_codes_dat_6 = vdct_codes_dat['Page 6 (T-Z)']
>>> type(vdct_codes_dat_6)
pandas.core.frame.DataFrame
>>> vdct_codes_dat_6.head()

```

	Name	Notes	...	End mileage	Spans
0	Tadcaster	crosses River Wharfe; grade II listed	...		11
1	Taff	see Red Bridge	...		
2	Taff		...		
3	Taff River	also called Afon Taff	...	170m	42ch
4	Taffs Well	see River Taff	...		

```

[5 rows x 7 columns]

```

station

Collect railway station data.

Class

Stations([data_dir, update, verbose])

A class for collecting railway station data.

Stations

class pyrcs.other_assets.station.Stations(*data_dir=None, update=False, verbose=True*)

A class for collecting [railway station data](#).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.other_assets import Stations

>>> stn = Stations()

>>> print(stn.NAME)
Railway station data

>>> print(stn.URL)
http://www.railwaycodes.org.uk/stations/station0.shtm
```

Attributes

<i>KEY</i>	Key of the dict -type data
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>KEY_TO_STN</i>	Key of the dict-type data of ' <i>Mileages, operators and grid coordinates</i> '
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

Stations.KEY

`Stations.KEY = 'Stations'`

Key of the `dict`-type data

Stations.KEY_TO_LAST_UPDATED_DATE

`Stations.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'`

Key of the data of the last updated date

Stations.KEY_TO_STN

`Stations.KEY_TO_STN = 'Mileages, operators and grid coordinates'`

Key of the `dict`-type data of *'Mileages, operators and grid coordinates'*

Stations.NAME

`Stations.NAME = 'Railway station data'`

Name of the data

Stations.URL

`Stations.URL = 'http://www.railwaycodes.org.uk/stations/station0.shtm'`

URL of the main web page of the data

Methods

<code>collect_locations_by_initial(initial[, ...])</code>	Collect <code>data of railway station locations</code> (mileages, operators and grid coordinates) for a given initial letter.
<code>fetch_locations([update, dump_dir, verbose])</code>	Fetch <code>data of railway station locations</code> (mileages, operators and grid coordinates).

Stations.collect_locations_by_initial

`Stations.collect_locations_by_initial(initial, update=False, verbose=False)`

Collect `data of railway station locations` (mileages, operators and grid coordinates) for a given initial letter.

Parameters

- `initial (str)` – initial letter of locations of the railway station data

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of railway station locations beginning with the given initial letter and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Stations # from pyrcs import Stations

>>> stn = Stations()

>>> stn_locations_a = stn.collect_locations_by_initial(initial='a')
>>> type(stn_locations_a)
dict
>>> list(stn_locations_a.keys())
['A', 'Last updated date']

>>> stn_locations_a_codes = stn_locations_a['A']
>>> type(stn_locations_a_codes)
pandas.core.frame.DataFrame
>>> stn_locations_a_codes.head()
   Station  ... Former Operator
0  Abbey Wood  ... London & South Eastern Railway from 1 April 20...
1  Abbey Wood  ...
2    Aber  ... Keolis Amey Operations/Gweithrediadau Keolis A...
3  Abercynon  ... Keolis Amey Operations/Gweithrediadau Keolis A...
4  Abercynon North  ... [Cardiff Railway Company from 13 October 1996 ...

[5 rows x 13 columns]
```

Stations.fetch_locations

`Stations.fetch_locations(update=False, dump_dir=None, verbose=False)`

Fetch data of railway station locations (mileages, operators and grid coordinates).

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – name of a folder where the pickle file is to be saved, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of railway station locations and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Stations # from pyrcs import Stations

>>> stn = Stations()

>>> stn_location_codes = stn.fetch_locations()
>>> type(stn_location_codes)
dict
>>> list(stn_location_codes.keys())
['Mileages, operators and grid coordinates', 'Last updated date']

>>> stn.KEY_TO_STN
'Mileages, operators and grid coordinates'

>>> stn_location_codes_dat = stn_location_codes[stn.KEY_TO_STN]
>>> type(stn_location_codes_dat)
pandas.core.frame.DataFrame
>>> stn_location_codes_dat.head()
   Station  ... Former Operator
0  Abbey Wood  ... London & South Eastern Railway from 1 April 20...
1  Abbey Wood  ...
2    Aber  ... Keolis Amey Operations/Gweithrediadau Keolis A...
3  Abercynon  ... Keolis Amey Operations/Gweithrediadau Keolis A...
4  Abercynon North  ... [Cardiff Railway Company from 13 October 1996 ...

[5 rows x 13 columns]
```

depot

Collect data of [depot codes](#).

Class

<i>Depots</i> ([<i>data_dir</i> , <i>update</i> , <i>verbose</i>])	A class for collecting data of depot codes .
--	--

Depots

class `pyrcs.other_assets.depot.Depots`(*data_dir=None*, *update=False*, *verbose=True*)

A class for collecting data of [depot codes](#).

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the catagloue data), defaults to *False*

- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to True

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> print(depots.NAME)
Depot codes

>>> print(depots.URL)
http://www.railwaycodes.org.uk/depots/depots0.shtm
```

Attributes

<i>KEY</i>	Key of the <i>dict</i> -type data
<i>KEY_TO_1950_SYSTEM</i>	Key of the dict-type data of 1950 system (pre-TOPS) codes
<i>KEY_TO_GWR</i>	Key of the dict-type data of GWR codes
<i>KEY_TO_LAST_UPDATED_DATE</i>	Key of the data of the last updated date
<i>KEY_TO_PRE_TOPS</i>	Key of the dict-type data of four digit pre-TOPS codes
<i>KEY_TO_TOPS</i>	Key of the dict-type data of two character TOPS codes
<i>NAME</i>	Name of the data
<i>URL</i>	URL of the main web page of the data

Depots.KEY

`Depots.KEY = 'Depots'`
Key of the *dict*-type data

Depots.KEY_TO_1950_SYSTEM

`Depots.KEY_TO_1950_SYSTEM = '1950 system (pre-TOPS) codes'`

Key of the dict-type data of 1950 system (pre-TOPS) codes

Depots.KEY_TO_GWR

`Depots.KEY_TO_GWR = 'GWR codes'`

Key of the dict-type data of GWR codes

Depots.KEY_TO_LAST_UPDATED_DATE

`Depots.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'`

Key of the data of the last updated date

Depots.KEY_TO_PRE_TOPS

`Depots.KEY_TO_PRE_TOPS = 'Four digit pre-TOPS codes'`

Key of the dict-type data of four digit pre-TOPS codes

Depots.KEY_TO_TOPS

`Depots.KEY_TO_TOPS = 'Two character TOPS codes'`

Key of the dict-type data of two character TOPS codes

Depots.NAME

`Depots.NAME = 'Depot codes'`

Name of the data

Depots.URL

`Depots.URL = 'http://www.railwaycodes.org.uk/depots/depots0.shtm'`

URL of the main web page of the data

Methods

<code>collect_1950_system_codes([...])</code>	Collect 1950 system (pre-TOPS) codes from source web page.
<code>collect_gwr_codes([confirmation_required, ...])</code>	Collect Great Western Railway (GWR) depot codes from source web page.
<code>collect_pre_tops_codes([...])</code>	Collect four-digit pre-TOPS codes from source web page.
<code>collect_tops_codes([confirmation_required, ...])</code>	Collect two-character TOPS codes from source web page.
<code>fetch_1950_system_codes([update, dump_dir, ...])</code>	Fetch data of 1950 system (pre-TOPS) codes.
<code>fetch_codes([update, dump_dir, verbose])</code>	Fetch data of depot codes.
<code>fetch_gwr_codes([update, dump_dir, verbose])</code>	Fetch data of Great Western Railway (GWR) depot codes.
<code>fetch_pre_tops_codes([update, dump_dir, verbose])</code>	Fetch data of four-digit pre-TOPS codes.
<code>fetch_tops_codes([update, dump_dir, verbose])</code>	Fetch data of two-character TOPS codes.

Depots.collect_1950_system_codes

`Depots.collect_1950_system_codes(confirmation_required=True, verbose=False)`

Collect 1950 system (pre-TOPS) codes from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to `True`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of 1950 system (pre-TOPS) codes and date of when the data was last updated

Return type

dict or `None`

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots
>>> depots = Depots()
>>> s1950_codes = depots.collect_1950_system_codes()
To collect data of 1950 system (pre-TOPS) codes
? [No] | Yes: yes
>>> type(s1950_codes)
```

(continues on next page)

(continued from previous page)

```
dict
>>> list(s1950_codes.keys())
['1950 system (pre-TOPS) codes', 'Last updated date']

>>> depots.KEY_TO_1950_SYSTEM
'1950 system (pre-TOPS) codes'

>>> s1950_codes_dat = s1950_codes[depots.KEY_TO_1950_SYSTEM]

>>> type(s1950_codes_dat)
pandas.core.frame.DataFrame
>>> s1950_codes_dat.head()
   Code      Depot name      Notes
0   1A      Willesden  From 1950.  Became WN from 6 May 1973
1   1B      Camden    From 1950.  To 3 January 1966
2   1C      Watford   From 1950.  Became WJ from 6 May 1973
3   1D  Devons Road, Bow  Previously 13B to 9 June 1950.  Became 1J from...
4   1D      Marylebone  Previously 14F to 31 August 1963.  Became ME f...
```

Depots.collect_gwr_codes

Depots.collect_gwr_codes(*confirmation_required=True, verbose=False*)

Collect [Great Western Railway \(GWR\) depot codes](#) from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of GWR depot codes and date of when the data was last updated

Return type

dict or None

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> gwr_codes = depots.collect_gwr_codes()
To collect data of GWR codes
? [No]|Yes: yes
>>> type(gwr_codes)
dict
>>> list(gwr_codes.keys())
['GWR codes', 'Last updated date']

>>> depots.KEY_TO_GWR
'GWR codes'
```

(continues on next page)

(continued from previous page)

```

>>> gwr_codes_dat = gwr_codes[depots.KEY_TO_GWR]
>>> type(gwr_codes_dat)
dict
>>> list(gwr_codes_dat.keys())
['Alphabetical codes', 'Numerical codes']

>>> gwr_alpha_codes = gwr_codes_dat['Alphabetical codes']
>>> type(gwr_alpha_codes)
pandas.core.frame.DataFrame
>>> gwr_alpha_codes.head()
   Code  Depot name
0  ABEEG  Aberbeeg
1   ABG   Aberbeeg
2   AYN  Abercynon
3  ABDR   Aberdare
4   ABH  Aberystwyth

```

Depots.collect_pre_tops_codes

`Depots.collect_pre_tops_codes(confirmation_required=True, verbose=False)`

Collect **four-digit pre-TOPS codes** from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of four-digit pre-TOPS codes and date of when the data was last updated

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> fdpt_codes = depots.collect_pre_tops_codes()
To collect data of four digit pre-TOPS codes
? [No] | Yes: yes
>>> type(fdpt_codes)
dict
>>> list(fdpt_codes.keys())
['Four digit pre-TOPS codes', 'Last updated date']

>>> depots.KEY_TO_PRE_TOPS
'Four digit pre-TOPS codes'

```

(continues on next page)

(continued from previous page)

```

>>> fdpt_codes_dat = fdpt_codes[depots.KEY_TO_PRE_TOPS]
>>> type(fdpt_codes_dat)
pandas.core.frame.DataFrame
>>> fdpt_codes_dat.head()

```

	Code	Depot name	Region	Main Works site
0	2000	Accrington	London Midland	False
1	2001	Derby Litchurch Lane	London Midland	True
2	2003	Blackburn	London Midland	False
3	2004	Bolton Trinity Street	London Midland	False
4	2006	Burnley	London Midland	False

Depots.collect_tops_codes

`Depots.collect_tops_codes(confirmation_required=True, verbose=False)`

Collect **two-character TOPS codes** from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

data of two-character TOPS codes and date of when the data was last updated

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> tct_codes = depots.collect_tops_codes()
To collect data of two character TOPS codes
? [No] | Yes: yes
>>> type(tct_codes)
dict
>>> list(tct_codes.keys())
['Two character TOPS codes', 'Last updated date']

>>> depots.KEY_TO_TOPS
'Two character TOPS codes'

>>> tct_codes_dat = tct_codes[depots.KEY_TO_TOPS]
>>> type(tct_codes_dat)
pandas.core.frame.DataFrame
>>> tct_codes_dat.head()

```

	Code	Notes
0	AB ...	Closed 1987
1	AB ...	

(continues on next page)

(continued from previous page)

```

2  AC  ...  Became WH from 1994
3  AC  ...
4  AD  ...

[5 rows x 5 columns]
```

Depots.fetch_1950_system_codes

`Depots.fetch_1950_system_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of 1950 system (pre-TOPS) codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of 1950 system (pre-TOPS) codes and date of when the data was last updated

Return type

dict

Examples:

```

>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> s1950_codes = depots.fetch_1950_system_codes()
>>> type(s1950_codes)
dict
>>> list(s1950_codes.keys())
['1950 system (pre-TOPS) codes', 'Last updated date']

>>> depots.KEY_TO_1950_SYSTEM
'1950 system (pre-TOPS) codes'

>>> s1950_codes_dat = s1950_codes[depots.KEY_TO_1950_SYSTEM]
>>> type(s1950_codes_dat)
pandas.core.frame.DataFrame
>>> s1950_codes_dat.head()
   Code  Depot name  Notes
0  1A      Willesden  From 1950. Became WN from 6 May 1973
1  1B      Camden    From 1950. To 3 January 1966
2  1C      Watford   From 1950. Became WJ from 6 May 1973
3  1D  Devons Road, Bow  Previously 13B to 9 June 1950. Became 1J from...
4  1D      Marylebone  Previously 14F to 31 August 1963. Became ME f...
```

Depots.fetch_codes

`Depots.fetch_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of depot codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of depot codes and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> depots_codes = depots.fetch_codes()

>>> type(depots_codes)
dict
>>> list(depots_codes.keys())
['Depots', 'Last updated date']

>>> depots.KEY
'Depots'

>>> depots_codes_dat = depots_codes[depots.KEY]
>>> type(depots_codes_dat)
dict
>>> list(depots_codes_dat.keys())
['1950 system (pre-TOPS) codes',
 'Four digit pre-TOPS codes',
 'GWR codes',
 'Two character TOPS codes']

>>> depots.KEY_TO_PRE_TOPS
'Four digit pre-TOPS codes'
>>> depots_codes_dat[depots.KEY_TO_PRE_TOPS].head()
   Code      Depot name      Region  Main Works site
0  2000      Accrington  London Midland          False
1  2001  Derby Litchurch Lane  London Midland           True
2  2003         Blackburn  London Midland          False
3  2004  Bolton Trinity Street  London Midland          False
4  2006         Burnley    London Midland          False
```

Depots.fetch_gwr_codes

`Depots.fetch_gwr_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of [Great Western Railway \(GWR\)](#) depot codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of GWR depot codes and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> gwr_codes = depots.fetch_gwr_codes()
>>> type(gwr_codes)
dict
>>> list(gwr_codes.keys())
['GWR codes', 'Last updated date']

>>> depots.KEY_TO_GWR
'GWR codes'

>>> gwr_codes_dat = gwr_codes[depots.KEY_TO_GWR]
>>> type(gwr_codes_dat)
dict
>>> list(gwr_codes_dat.keys())
['Alphabetical codes', 'Numerical codes']

>>> gwr_alpha_codes = gwr_codes_dat['Alphabetical codes']
>>> type(gwr_alpha_codes)
pandas.core.frame.DataFrame
>>> gwr_alpha_codes.head()
   Code  Depot name
0  ABEEG    Aberbeeg
1   ABG    Aberbeeg
2   AYN  Abercynon
3  ABDR   Aberdare
4   ABH  Aberystwyth
```

Depots.fetch_pre_tops_codes

`Depots.fetch_pre_tops_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of four-digit pre-TOPS codes.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of four-digit pre-TOPS codes and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> fdpt_codes = depots.fetch_pre_tops_codes()
>>> type(fdpt_codes)
dict
>>> list(fdpt_codes.keys())
['Four digit pre-TOPS codes', 'Last updated date']

>>> depots.KEY_TO_PRE_TOPS
'Four digit pre-TOPS codes'

>>> fdpt_codes_dat = fdpt_codes[depots.KEY_TO_PRE_TOPS]
>>> type(fdpt_codes_dat)
pandas.core.frame.DataFrame
>>> fdpt_codes_dat.head()
```

	Code	Depot name	Region	Main Works site
0	2000	Accrington	London Midland	False
1	2001	Derby Litchurch Lane	London Midland	True
2	2003	Blackburn	London Midland	False
3	2004	Bolton Trinity Street	London Midland	False
4	2006	Burnley	London Midland	False

Depots.fetch_tops_codes

`Depots.fetch_tops_codes(update=False, dump_dir=None, verbose=False)`

Fetch data of **two-character TOPS codes**.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or None*) – pathname of a directory where the data file is dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of two-character TOPS codes and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Depots # from pyrcs import Depots

>>> depots = Depots()

>>> tct_codes = depots.fetch_tops_codes()
>>> type(tct_codes)
dict
>>> list(tct_codes.keys())
['Two character TOPS codes', 'Last updated date']

>>> depots.KEY_TO_TOPS
'Two character TOPS codes'

>>> tct_codes_dat = tct_codes[depots.KEY_TO_TOPS]
>>> type(tct_codes_dat)
pandas.core.frame.DataFrame
>>> tct_codes_dat.head()
   Code  ...      Notes
0  AB   ...  Closed 1987
1  AB   ...
2  AC   ...  Became WH from 1994
3  AC   ...
4  AD   ...

[5 rows x 5 columns]
```

feature

Collect codes of infrastructure features.

This category includes:

- HABD and WILD
- Water troughs
- Telegraph codes
- Driver/guard buzzer codes

Class

<code>Features([data_dir, update, verbose])</code>	A class for collecting codes of several infrastructure features.
--	--

Features

class `pyrcs.other_assets.feature.Features(data_dir=None, update=False, verbose=True)`

A class for collecting codes of several infrastructure features.

Parameters

- **data_dir** (*str* or *None*) – name of data directory, defaults to *None*
- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *True*

Variables

- **catalogue** (*dict*) – catalogue of the data
- **last_updated_date** (*str*) – last updated date
- **data_dir** (*str*) – path to the data directory
- **current_data_dir** (*str*) – path to the current data directory

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features
>>> feats = Features()
>>> print(feats.NAME)
Infrastructure features
```

Attributes

<code>KEY</code>	Key of the <code>dict</code> -type data
<code>KEY_TO_BUZZER</code>	Key of the dict-type data of <i>'buzzer codes'</i>
<code>KEY_TO_HABD_WILD</code>	Key of the dict-type data of <i>'HABD'</i> and <i>'WILD'</i>
<code>KEY_TO_LAST_UPDATED_DATE</code>	Key of the data of the last updated date
<code>KEY_TO_TELEGRAPH</code>	Key of the dict-type data of <i>'telegraph codes'</i>
<code>KEY_TO_TROUGH</code>	Key of the dict-type data of <i>'water troughs'</i>
<code>NAME</code>	Name of the data

Features.KEY

`Features.KEY = 'Features'`

Key of the `dict`-type data

Features.KEY_TO_BUZZER

`Features.KEY_TO_BUZZER = 'Buzzer codes'`

Key of the dict-type data of *'buzzer codes'*

Features.KEY_TO_HABD_WILD

`Features.KEY_TO_HABD_WILD = 'HABD and WILD'`

Key of the dict-type data of *'HABD'* and *'WILD'*

Features.KEY_TO_LAST_UPDATED_DATE

`Features.KEY_TO_LAST_UPDATED_DATE = 'Last updated date'`

Key of the data of the last updated date

Features.KEY_TO_TELEGRAPH

`Features.KEY_TO_TELEGRAPH = 'Telegraphic codes'`

Key of the dict-type data of *'telegraph codes'*

Features.KEY_TO_TROUGH

`Features.KEY_TO_TROUGH = 'Water troughs'`

Key of the dict-type data of *'water troughs'*

Features.NAME

`Features.NAME = 'Infrastructure features'`

Name of the data

Methods

<code>collect_buzzer_codes([...])</code>	Collect data of buzzer codes from source web page.
<code>collect_habds_and_wilds([...])</code>	Collect codes of HABDs and WILDs from source web page.
<code>collect_telegraph_codes([...])</code>	Collect data of telegraph code words from source web page.
<code>collect_water_troughs([...])</code>	Collect codes of water troughs locations from source web page.
<code>fetch_buzzer_codes([update, dump_dir, verbose])</code>	Fetch data of buzzer codes .
<code>fetch_codes([update, dump_dir, verbose])</code>	Fetch codes of infrastructure features.
<code>fetch_habds_and_wilds([update, dump_dir, ...])</code>	Fetch codes of HABDs and WILDs .
<code>fetch_telegraph_codes([update, dump_dir, ...])</code>	Fetch data of telegraph code words .
<code>fetch_water_troughs([update, dump_dir, verbose])</code>	Fetch codes of water troughs locations .

Features.collect_buzzer_codes

`Features.collect_buzzer_codes(confirmation_required=True, verbose=False)`

Collect data of **buzzer codes** from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to `True`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

data of **buzzer codes**, and date of when the data was last updated

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> buz_codes = feats.collect_buzzer_codes()
To collect data of Buzzer codes
? [No]|Yes: yes
>>> type(buz_codes)
dict
>>> list(buz_codes.keys())
['Buzzer codes', 'Last updated date']

>>> feats.KEY_TO_BUZZER
'Buzzer codes'

>>> buz_codes_dat = buz_codes[feats.KEY_TO_BUZZER]
>>> type(buz_codes_dat)
pandas.core.frame.DataFrame
>>> buz_codes_dat.head()
  Code [number of buzzes or groups separated by pauses]  Meaning
0          1                      Stop
1          1-2                    Close doors
2          2                      Ready to start
3          2-2                   Do not open doors
4          3                      Set back

```

Features.collect_habds_and_wilds

Features.collect_habds_and_wilds(*confirmation_required=True, verbose=False*)

Collect codes of **HABDs** and **WILDs** from source web page.

Note:

- HABDs: Hot axle box detectors
- WILDs: Wheel impact load detectors

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of HABDs and WILDs, and date of when the data was last updated

Return type

dict or None

Examples:

```

>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> hw_codes = feats.collect_habds_and_wilds()
To collect data of HABD and WILD
? [No]|Yes: yes
>>> type(hw_codes)
dict
>>> list(hw_codes.keys())
['HABD and WILD', 'Last updated date']

>>> feats.KEY_TO_HABD_WILD
'HABD and WILD'

>>> hw_codes_dat = hw_codes[feats.KEY_TO_HABD_WILD]
>>> type(hw_codes_dat)
dict
>>> list(hw_codes_dat.keys())
['HABD', 'WILD']

>>> habd_dat = hw_codes_dat['HABD']
>>> type(habd_dat)
pandas.core.frame.DataFrame
>>> habd_dat.head()
   ELR  ...                                     Notes
0  BAG2  ...
1  BAG2  ...  installed 29 September 1997, later moved to 74...
2  BAG2  ...                                     previously at 74m 51ch
3  BAG2  ...                                     removed 29 September 1997
4  BAG2  ...  present in 1969, later moved to 89m 00ch

[5 rows x 5 columns]

>>> wild_dat = hw_codes_dat['WILD']
>>> type(wild_dat)
pandas.core.frame.DataFrame
>>> wild_dat.head()
   ELR  ...                                     Notes
0  AYR3  ...
1  BAG2  ...
2  BML1  ...
3  BML1  ...
4  CGJ3  ...  moved to 183m 68ch from 8 September 2018 / mov...

[5 rows x 5 columns]

```

Features.collect_telegraph_codes

Features.collect_telegraph_codes(*confirmation_required=True, verbose=False*)

Collect data of telegraph code words from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of telegraph code words, and date of when the data was last updated

Return type

dict or None

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> tel_codes = feats.collect_telegraph_codes()
To collect data of Telegraphic codes
? [No]|Yes: yes
>>> type(tel_codes)
dict
>>> list(tel_codes.keys())
['Telegraphic codes', 'Last updated date']

>>> feats.KEY_TO_TELEGRAPH
'Telegraphic codes'

>>> tel_codes_dat = tel_codes[feats.KEY_TO_TELEGRAPH]
>>> type(tel_codes_dat)
dict
>>> list(tel_codes_dat.keys())
['Official codes', 'Unofficial codes']

>>> tel_official_codes = tel_codes_dat['Official codes']
>>> type(tel_official_codes)
pandas.core.frame.DataFrame
>>> tel_official_codes.head()
   Code  ...  In use
0  ABACK  ...  cross industry term used in 1939
1  ABASE  ...  GWR, 1939
2  ABREAST  ...  GWR, 1939 / Railway Executive, 1950
3  ABREAST  ...  British Transport Commission, 1958
4  ABSENT  ...  GWR, 1939

[5 rows x 3 columns]

>>> tel_unofficial_codes = tel_codes_dat['Unofficial codes']
>>> type(tel_unofficial_codes)
```

(continues on next page)

(continued from previous page)

```
pandas.core.frame.DataFrame
>>> tel_unofficial_codes.head()
   Code                                Unofficial description
0  CRANKEX                               [See KRANKEX]
1  DRUNKEX  Saturday night special train (usually a DMU) t...
2    GYFO    Strongly urge all speed ('Get your finger out')
3  KRANKEX  Special train with interesting routing or trac...
4  MYSTEX   Special excursion going somewhere no one reall...
```

Features.collect_water_troughs

Features.collect_water_troughs(*confirmation_required=True, verbose=False*)

Collect codes of [water troughs locations](#) from source web page.

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of water trough locations, and date of when the data was last updated

Return type

dict or None

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> wt_codes = feats.collect_water_troughs()
To collect data of Water troughs
? [No]|Yes: yes
>>> type(wt_codes)
dict
>>> list(wt_codes.keys())
['Water troughs', 'Last updated date']

>>> feats.KEY_TO_TROUGH
'Water troughs'

>>> wt_codes_dat = wt_codes[feats.KEY_TO_TROUGH]
>>> type(wt_codes_dat)
pandas.core.frame.DataFrame
>>> wt_codes_dat.head()
   ELR  ... Length (Yard)
0  BEI  ...           NaN
1  BHL  ...      620.000000
2  CGJ2 ...      0.666667
3  CGJ6 ...      561.000000
```

(continues on next page)

(continued from previous page)

```
4 CGJ6 ... 560.000000

[5 rows x 6 columns]
```

Features.fetch_buzzer_codes

Features.fetch_buzzer_codes(update=False, dump_dir=None, verbose=False)

Fetch data of **buzzer codes**.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str* or *None*) – name of a folder where the pickle file is to be saved, defaults to None
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Returns

data of buzzer codes, and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> buz_codes = feats.fetch_buzzer_codes()
>>> type(buz_codes)
dict
>>> list(buz_codes.keys())
['Buzzer codes', 'Last updated date']

>>> feats.KEY_TO_BUZZER
'Buzzer codes'

>>> buz_codes_dat = buz_codes[feats.KEY_TO_BUZZER]
>>> type(buz_codes_dat)
pandas.core.frame.DataFrame
>>> buz_codes_dat.head()
  Code [number of buzzes or groups separated by pauses]  Meaning
0          1                      Stop
1         1-2                   Close doors
2          2                   Ready to start
3         2-2                Do not open doors
4          3                      Set back
```

Features.fetch_codes

Features.fetch_codes(*update=False, dump_dir=None, verbose=False*)

Fetch codes of infrastructure features.

Including:

- HABD and WILD
- Water troughs
- Telegraph codes
- Driver/guard buzzer codes

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **dump_dir** (*str or None*) – name of a folder where the pickle file is to be saved, defaults to None
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

data of features codes and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> feats_codes = feats.fetch_codes()
>>> type(feats_codes)
dict
>>> list(feats_codes.keys())
['Features', 'Last updated date']

>>> feats.KEY
'Features'

>>> feats_codes_dat = feats_codes[feats.KEY]
>>> type(feats_codes_dat)
dict
>>> list(feats_codes_dat.keys())
['Buzzer codes', 'HABD and WILD', 'Telegraphic codes', 'Water troughs']

>>> water_troughs_locations = feats_codes_dat[feats.KEY_TO_TROUGH]
>>> type(water_troughs_locations)
pandas.core.frame.DataFrame
```

(continues on next page)

(continued from previous page)

```
>>> water_troughs_locations.head()
      ELR  ... Length (Yard)
0  BEI    ...           NaN
1  BHL    ...    620.000000
2  CGJ2   ...     0.666667
3  CGJ6   ...    561.000000
4  CGJ6   ...    560.000000

[5 rows x 6 columns]
```

Features.fetch_habds_and_wilds

Features.**fetch_habds_and_wilds**(*update=False, dump_dir=None, verbose=False*)

Fetch codes of **HABDs** and **WILDs**.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to *False*
- **dump_dir** (*str* or *None*) – name of a folder where the pickle file is to be saved, defaults to *None*
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to *False*

Returns

data of hot axle box detectors (HABDs) and wheel impact load detectors (WILDs), and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> hw_codes = feats.fetch_habds_and_wilds()

>>> type(hw_codes)
dict
>>> list(hw_codes.keys())
['HABD and WILD', 'Last updated date']

>>> feats.KEY_TO_HABD_WILD
'HABD and WILD'

>>> hw_codes_dat = hw_codes[feats.KEY_TO_HABD_WILD]
>>> type(hw_codes_dat)
dict
>>> list(hw_codes_dat.keys())
```

(continues on next page)

(continued from previous page)

```
['HABD', 'WILD']

>>> habd_dat = hw_codes_dat['HABD']
>>> type(habd_dat)
pandas.core.frame.DataFrame
>>> habd_dat.head()
   ELR  ...                               Notes
0  BAG2  ...
1  BAG2  ...  installed 29 September 1997, later moved to 74...
2  BAG2  ...                               previously at 74m 51ch
3  BAG2  ...                               removed 29 September 1997
4  BAG2  ...  present in 1969, later moved to 89m 00ch

[5 rows x 5 columns]

>>> wild_dat = hw_codes_dat['WILD']
>>> type(wild_dat)
pandas.core.frame.DataFrame
>>> wild_dat.head()
   ELR  ...                               Notes
0  AYR3  ...
1  BAG2  ...
2  BML1  ...
3  BML1  ...
4  CGJ3  ...  moved to 183m 68ch from 8 September 2018 / mov...

[5 rows x 5 columns]
```

Features.fetch_telegraph_codes

Features.fetch_telegraph_codes(*update=False, dump_dir=None, verbose=False*)

Fetch data of telegraph code words.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str* or *None*) – name of a folder where the pickle file is to be saved, defaults to `None`
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to `False`

Returns

data of telegraph code words, and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features
```

(continues on next page)

(continued from previous page)

```

>>> feats = Features()

>>> tel_codes = feats.fetch_telegraph_codes()
>>> type(tel_codes)
dict
>>> list(tel_codes.keys())
['Telegraphic codes', 'Last updated date']

>>> feats.KEY_TO_TELEGRAPH
'Telegraphic codes'

>>> tel_codes_dat = tel_codes[feats.KEY_TO_TELEGRAPH]
>>> type(tel_codes_dat)
dict
>>> list(tel_codes_dat.keys())
['Official codes', 'Unofficial codes']

>>> tel_official_codes = tel_codes_dat['Official codes']
>>> type(tel_official_codes)
pandas.core.frame.DataFrame
>>> tel_official_codes.head()
   Code  ...                               In use
0  ABACK  ...   cross industry term used in 1939
1  ABASE  ...                               GWR, 1939
2  ABREAST  ...  GWR, 1939 / Railway Executive, 1950
3  ABREAST  ...  British Transport Commission, 1958
4  ABSENT  ...                               GWR, 1939

[5 rows x 3 columns]

>>> tel_unofficial_codes = tel_codes_dat['Unofficial codes']
>>> type(tel_unofficial_codes)
pandas.core.frame.DataFrame
>>> tel_unofficial_codes.head()
   Code                               Unofficial description
0  CRANKEX                               [See KRANKEX]
1  DRUNKEX  Saturday night special train (usually a DMU) t...
2  GYFO      Strongly urge all speed ('Get your finger out')
3  KRANKEX  Special train with interesting routing or trac...
4  MYSTEX   Special excursion going somewhere no one reall...

```

Features.fetch_water_troughs

`Features.fetch_water_troughs(update=False, dump_dir=None, verbose=False)`

Fetch codes of [water troughs](#) locations.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str* or *None*) – name of a folder where the pickle file is to be saved, defaults to `None`
- **verbose** (*bool* or *int*) – whether to print relevant information in console,

defaults to False

Returns

data of water trough locations, and date of when the data was last updated

Return type

dict

Examples:

```
>>> from pyrcs.other_assets import Features # from pyrcs import Features

>>> feats = Features()

>>> # wt_codes = feats.fetch_water_troughs(update=True, verbose=True)
>>> wt_codes = feats.fetch_water_troughs()

>>> type(wt_codes)
dict
>>> list(wt_codes.keys())
['Water troughs', 'Last updated date']

>>> feats.KEY_TO_TROUGH
'Water troughs'

>>> wt_codes_dat = wt_codes[feats.KEY_TO_TROUGH]
>>> type(wt_codes_dat)
pandas.core.frame.DataFrame
>>> wt_codes_dat.head()
  ELR  ... Length (Yard)
0  BEI  ...           NaN
1  BHL  ...      620.000000
2  CGJ2 ...      0.666667
3  CGJ6 ...      561.000000
4  CGJ6 ...      560.000000

[5 rows x 6 columns]
```

3.2 Modules

<i>parser</i>	Parse web-page contents.
<i>converter</i>	Change data into a desired form.
<i>collector</i>	Collect data of railway codes.
<i>utils</i>	Provide a number of helper functions.

3.2.1 parser

Parse web-page contents.

Preprocess contents

<code>parse_tr(trs, ths[, as_dataframe])</code>	Parse a list of parsed HTML <tr> elements.
<code>parse_table(source[, parser, as_dataframe])</code>	Parse HTML <tr> elements for creating a data frame.
<code>parse_date(str_date[, as_date_type])</code>	Parse a date.
<code>parse_location_name(location_name)</code>	Parse location name (and its associated note).

parse_tr

`pyrcs.parser.parse_tr(trs, ths, as_dataframe=False)`

Parse a list of parsed HTML <tr> elements.

See also [PT-1].

Parameters

- **trs** (*bs4.ResultSet*) – contents under <tr> tags of a web page
- **ths** (*list* or *bs4.element.Tag*) – list of column names (usually under a <th> tag) of a requested table
- **as_dataframe** (*bool*) – whether to return the parsed data in tabular form

Returns

a list of lists that each comprises a row of the requested table

Return type

`pandas.DataFrame` or *List[list]*

Example:

```
>>> from pyrcs.parser import parse_tr
>>> import requests
>>> import bs4

>>> example_url = 'http://www.railwaycodes.org.uk/elrs/elra.shtm'
>>> source = requests.get(example_url)
>>> parsed_text = bs4.BeautifulSoup(markup=source.content, features='html.parser')
>>> ths_dat = [th.text for th in parsed_text.find_all('th')]
>>> trs_dat = parsed_text.find_all(name='tr')

>>> tables_list = parse_tr(trs=trs_dat, ths=ths_dat) # returns a list of lists

>>> type(tables_list)
list
>>> len(tables_list) // 100
1
```

(continues on next page)

(continued from previous page)

```
>>> tables_list[0]
['AAL',
 'Ashendon and Aynho Line',
 '0.00 - 18.29',
 'Ashendon Junction',
 'Now NAJ3']
```

parse_table

`pyrcs.parser.parse_table(source, parser='html.parser', as_dataframe=False)`

Parse HTML <tr> elements for creating a data frame.

Parameters

- **source** (*requests.Response*) – response object to connecting a URL to request a table
- **parser** (*str*) – 'html.parser' (default), 'html5lib' or 'lxml'
- **as_dataframe** (*bool*) – whether to return the parsed data in tabular form

Returns

a list of lists each comprising a row of the requested table (see also `pyrcs.utils.parse_tr()`) and a list of column names of the requested table

Return type

tuple[list, list] or `pandas.DataFrame` or list

Examples:

```
>>> from pyrcs.parser import parse_table
>>> import requests

>>> source_dat = requests.get(url='http://www.railwaycodes.org.uk/elrs/elra.shtm')

>>> columns_dat, records_dat = parse_table(source_dat)

>>> columns_dat
['ELR', 'Line name', 'Mileages', 'Datum', 'Notes']
>>> type(records_dat)
list
>>> len(records_dat) // 100
1
>>> records_dat[0]
['AAL',
 'Ashendon and Aynho Line',
 '0.00 - 18.29',
 'Ashendon Junction',
 'Now NAJ3']
```


parse_date

`pyrcs.parser.parse_date(str_date, as_date_type=False)`

Parse a date.

Parameters

- **str_date** (*str*) – string-type date
- **as_date_type** (*bool*) – whether to return the date as `datetime.date`, defaults to `False`

Returns

parsed date as a string or `datetime.date`

Return type

`str` or `datetime.date`

Examples:

```
>>> from pyrcs.parser import parse_date

>>> str_date_dat = '2020-01-01'

>>> parsed_date_dat = parse_date(str_date_dat)
>>> parsed_date_dat
'2020-01-01'

>>> parsed_date_dat = parse_date(str_date_dat, as_date_type=True)
>>> parsed_date_dat
datetime.date(2020, 1, 1)
```

parse_location_name

`pyrcs.parser.parse_location_name(location_name)`

Parse location name (and its associated note).

Parameters

location_name (*str* or *None*) – location name (in raw data)

Returns

location name and note (if any)

Return type

tuple

Examples:

```
>>> from pyrcs.parser import parse_location_name

>>> dat_and_note = parse_location_name('Abbey Wood')
>>> dat_and_note
('Abbey Wood', '')
```

(continues on next page)

(continued from previous page)

```

>>> dat_and_note = parse_location_name(None)
>>> dat_and_note
(' ', ' ')

>>> dat_and_note = parse_location_name('Abercynon (formerly Abercynon South)')
>>> dat_and_note
('Abercynon', 'formerly Abercynon South')

>>> location_dat = 'Allerton (reopened as Liverpool South Parkway)'
>>> dat_and_note = parse_location_name(location_dat)
>>> dat_and_note
('Allerton', 'reopened as Liverpool South Parkway')

>>> location_dat = 'Ashford International [domestic portion]'
>>> dat_and_note = parse_location_name(location_dat)
>>> dat_and_note
('Ashford International', 'domestic portion')

```

Extract information

<code>get_site_map([update, ...])</code>	Fetch the site map from the package data.
<code>get_last_updated_date(url[, parsed, ...])</code>	Get last update date.
<code>get_financial_year(date)</code>	Convert calendar year of a given date to Network Rail financial year.
<code>get_catalogue(url[, update, ...])</code>	Get the catalogue for a class.
<code>get_category_menu(url[, update, ...])</code>	Get a menu of the available classes.
<code>get_page_catalogue(url[, head_tag_name, ...])</code>	Get the catalogue of the main page of a data cluster.
<code>get_heading_text(heading_tag[, elem_tag_name])</code>	Get the text of a given heading tag.
<code>get_page_catalogue(url[, head_tag_name, ...])</code>	Get the catalogue of the main page of a data cluster.
<code>get_hypertext(hypertext_tag[, ...])</code>	Get text that is with a hyperlink.
<code>get_introduction(url[, delimiter, verbose])</code>	Get contents of the Introduction page.

get_site_map

`pyrcs.parser.get_site_map(update=False, confirmation_required=True, verbose=False)`

Fetch the [site map](#) from the package data.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to `True`

- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

dictionary of site map data

Return type

`collections.OrderedDict` or `None`

Examples:

```
>>> from pyrcs.parser import get_site_map

>>> site_map_dat = get_site_map()

>>> type(site_map_dat)
collections.OrderedDict
>>> list(site_map_dat.keys())
['Home',
 'Line data',
 'Other assets',
 '"Legal/financial" lists',
 'Miscellaneous']
>>> site_map_dat['Home']
{'index.shtml': 'http://www.railwaycodes.org.uk/index.shtml'}
```

get_last_updated_date

`pyrcs.parser.get_last_updated_date(url, parsed=True, as_date_type=False, verbose=False)`

Get last update date.

Parameters

- **url** (*str*) – URL link of a requested web page
- **parsed** (*bool*) – whether to reformat the date, defaults to True
- **as_date_type** (*bool*) – whether to return the date as `datetime.date`, defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

date of when the specified web page was last updated

Return type

`str` or `datetime.date` or `None`

Examples:

```
>>> from pyrcs.parser import get_last_updated_date

>>> url_a = 'http://www.railwaycodes.org.uk/crs/CRSa.shtm'
>>> last_upd_date = get_last_updated_date(url_a, parsed=True, as_date_type=False)
```

(continues on next page)

(continued from previous page)

```

>>> type(last_upd_date)
str

>>> last_upd_date = get_last_updated_date(url_a, parsed=True, as_date_type=True)
>>> type(last_upd_date)
datetime.date

>>> ldm_url = 'http://www.railwaycodes.org.uk/linedatamenu.shtm'
>>> last_upd_date = get_last_updated_date(url=ldm_url)
>>> print(last_upd_date)
None

```

get_financial_year

`pyrcs.parser.get_financial_year(date)`

Convert calendar year of a given date to Network Rail financial year.

Parameters

date (*datetime.datetime*) – date

Returns

Network Rail financial year of the given date

Return type

int

Example:

```

>>> from pyrcs.parser import get_financial_year
>>> import datetime

>>> financial_year = get_financial_year(date=datetime.datetime(2021, 3, 31))
>>> financial_year
2020

```

get_catalogue

`pyrcs.parser.get_catalogue(url, update=False, confirmation_required=True, json_it=True, verbose=False)`

Get the catalogue for a class.

Parameters

- **url** (*str*) – URL of the main page of a data cluster
- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True

- **json_it** (*bool*) – whether to save the catalogue as a JSON file, defaults to `True`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`

Returns

catalogue in the form {'<title>': '<URL>'}

Return type

dict or None

Examples:

```
>>> from pyrcs.parser import get_catalogue

>>> elr_cat = get_catalogue(url='http://www.railwaycodes.org.uk/elrs/elr0.shtm')
>>> type(elr_cat)
dict
>>> list(elr_cat.keys())[:5]
['Introduction', 'A', 'B', 'C', 'D']
>>> list(elr_cat.keys())[-5:]
['Lines without codes',
 'ELR/LOR converter',
 'LUL system',
 'DLR system',
 'Canals']

>>> line_data_cat = get_catalogue(url='http://www.railwaycodes.org.uk/linedatamenu.shtm')
>>> type(line_data_cat)
dict
>>> list(line_data_cat.keys())
['ELRs and mileages',
 'Electrification masts and related features',
 'CRS, NLC, TIPLOC and STANOX Codes',
 'Line of Route (LOR/PRIIDE) codes',
 'Line names',
 'Track diagrams']
```

get_category_menu

`pyrcs.parser.get_category_menu(url, update=False, confirmation_required=True, json_it=True, verbose=False)`

Get a menu of the available classes.

Parameters

- **url** (*str*) – URL of the menu page
- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to `True`

- **json_it** (*bool*) – whether to save the catalogue as a .json file, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

a category menu

Return type

dict or None

Example:

```
>>> from pyrcs.parser import get_category_menu

>>> menu = get_category_menu('http://www.railwaycodes.org.uk/linedatamenu.shtm')

>>> type(menu)
dict
>>> list(menu.keys())
['Line data']
```

get_page_catalogue

`pyrcs.parser.get_page_catalogue(url, head_tag_name='nav', head_tag_txt='Jump to: ', feature_tag_name='h3', verbose=False)`

Get the catalogue of the main page of a data cluster.

Parameters

- **url** (*str*) – URL of the main page of a data cluster
- **head_tag_name** (*str*) – tag name of the feature list at the top of the page, defaults to 'nav'
- **head_tag_txt** (*str*) – text that is contained in the head_tag, defaults to 'Jump to: '
- **feature_tag_name** (*str*) – tag name of the headings of each feature, defaults to 'h3'
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False

Returns

catalogue of the main page of a data cluster

Return type

pandas.DataFrame

Example:

```

>>> from pyrcs.parser import get_page_catalogue
>>> from pyhelpers.settings import pd_preferences

>>> pd_preferences(max_columns=1)

>>> elec_url = 'http://www.railwaycodes.org.uk/electrification/mast_prefix2.shtm'

>>> elec_catalogue = get_page_catalogue(elec_url)
>>> elec_catalogue

```

	Feature	...
0	Beamish Tramway	...
1	Birkenhead Tramway	...
2	Black Country Living Museum	...
3	Blackpool Tramway	...
4	Brighton and Rottingdean Seashore Electric Rai...	...
..
17	Seaton Tramway	...
18	Sheffield Supertram	...
19	Snaefell Mountain Railway	...
20	Summerlee, Museum of Scottish Industrial Life	...
21	Tyne & Wear Metro	...

```

[22 rows x 3 columns]

>>> elec_catalogue.columns.to_list()
['Feature', 'URL', 'Heading']

```

get_heading_text

`pyrcs.parser.get_heading_text(heading_tag, elem_tag_name='em')`

Get the text of a given heading tag.

Parameters

- **heading_tag** (`bs4.element.Tag`) – tag of a heading
- **elem_tag_name** (`str`) – tag name of an element in the heading_tag, defaults to 'em'

Returns

cleansed text of the given heading_tag

Return type

str

Examples:

```

>>> from pyrcs.parser import get_heading_text
>>> from pyrcs.line_data import Electrification

>>> elec = Electrification()

>>> url = elec.catalogue[elec.KEY_TO_INDEPENDENT_LINES]
>>> source = requests.get(url=url, headers=fake_requests_headers())
>>> soup = bs4.BeautifulSoup(markup=source.content, features='html.parser')

```

(continues on next page)

(continued from previous page)

```
>>> h3 = soup.find('h3')

>>> h3_text = get_heading_text(heading_tag=h3, elem_tag_name='em')
>>> h3_text
'Beamish Tramway'
```

get_hypertext

`pyrcs.parser.get_hypertext(hypertext_tag, hyperlink_tag_name='a', md_style=True)`

Get text that is with a hyperlink.

Parameters

- **hypertext_tag** (*bs4.element.Tag* or *bs4.element.PageElement*) – tag of hypertext (i.e. text that is with a hyperlink)
- **hyperlink_tag_name** (*str*) –
- **md_style** (*bool*) – whether to return the obtained hypertext in markdown style, defaults to True

Returns

hypertext

Return type

str

Examples:

```
>>> from pyrcs.parser import get_hypertext
>>> from pyrcs.line_data import Electrification
>>> import bs4
>>> import requests

>>> elec = Electrification()

>>> url = elec.catalogue[elec.KEY_TO_INDEPENDENT_LINES]
>>> source = requests.get(url)
>>> soup = bs4.BeautifulSoup(source.content, 'html.parser')

>>> h3 = soup.find('h3')

>>> p = h3.find_all_next('p')[8]
>>> p
<p>Croydon Tramlink mast references can be found on the <a href="http://www.croydon-traml...

>>> hyper_txt = get_hypertext(hypertext_tag=p, md_style=True)
>>> hyper_txt
'Croydon Tramlink mast references can be found on the [Croydon Tramlink Unofficial Site](...
```


get_introduction

`pyrcs.parser.get_introduction(url, delimiter='\n', verbose=True)`

Get contents of the Introduction page.

Parameters

- **url** (*str*) – URL of a web page (usually the main page of a data cluster)
- **delimiter** (*str*) – delimiter used for separating paragraphs, defaults to '\n'
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to True

Returns

introductory texts on the given web page

Return type

str

Examples:

```
>>> from pyrcs.parser import get_introduction

>>> bridges_url = 'http://www.railwaycodes.org.uk/bridges/bridges0.shtm'

>>> intro_text = get_introduction(url=bridges_url)
>>> intro_text
"There are thousands of bridges over and under the railway system. These pages attempt to..."
```

3.2.2 converter

Change data into a desired form.

Convert mileage data

<code>fix_mileage(mileage)</code>	Fix mileage data (associated with an ELR).
<code>yard_to_mileage(yard[, as_str])</code>	Convert yards to Network Rail mileages.
<code>mileage_to_yard(mileage)</code>	Convert Network Rail mileages to yards.
<code>mile_chain_to_mileage(mile_chain)</code>	Convert mileage data in the form '<miles>.<chains>' to Network Rail mileage.
<code>mileage_to_mile_chain(mileage)</code>	Convert Network Rail mileage to the form '<miles>.<chains>'.
<code>mile_yard_to_mileage(mile, yard[, as_numeric])</code>	Convert mile and yard to Network Rail mileage.
<code>mileage_str_to_num(mileage)</code>	Convert string-type Network Rail mileage to numerical-type one.
<code>mileage_num_to_str(mileage)</code>	Convert numerical-type Network Rail mileage to string-type one.
<code>shift_mileage_by_yard(mileage, shift_yards)</code>	Shift Network Rail mileage by given yards.

fix_mileage

`pyrcs.converter.fix_mileage(mileage)`

Fix mileage data (associated with an ELR).

Parameters

mileage (*str or float or None*) – Network Rail mileage

Returns

fixed mileage data in the conventional format used by Network Rail

Return type

str

Examples:

```
>>> from pyrcs.converter import fix_mileage

>>> fixed_mileage = fix_mileage(mileage=29.011)
>>> fixed_mileage
'29.0110'

>>> fixed_mileage = fix_mileage(mileage='.1100')
>>> fixed_mileage
'0.1100'
```

yard_to_mileage

`pyrcs.converter.yard_to_mileage(yard, as_str=True)`

Convert yards to Network Rail mileages.

Parameters

- **yard** (*int or float or None*) – yard data
- **as_str** (*bool*) – whether to return as a string value, defaults to True

Returns

Network Rail mileage in the form '<miles>.<yards>' or <miles>.<yards>

Return type

str or float

Examples:

```
>>> from pyrcs.converter import yard_to_mileage

>>> mileage_dat = yard_to_mileage(yard=396)
>>> mileage_dat
'0.0396'

>>> mileage_dat = yard_to_mileage(yard=396, as_str=False)
>>> mileage_dat
0.0396
```

(continues on next page)

(continued from previous page)

```
>>> mileage_dat = yard_to_mileage(yard=None)
>>> mileage_dat
''

>>> mileage_dat = yard_to_mileage(yard=12320)
>>> mileage_dat
'7.0000'
```

mileage_to_yard

`pyrcs.converter.mileage_to_yard(mileage)`

Convert Network Rail mileages to yards.

Parameters

mileage (*float or int or str*) – Network Rail mileage

Returns

yards

Return type

int

Examples:

```
>>> from pyrcs.converter import mileage_to_yard

>>> yards_dat = mileage_to_yard(mileage='0.0396')
>>> yards_dat
396

>>> yards_dat = mileage_to_yard(mileage=0.0396)
>>> yards_dat
396

>>> yards_dat = mileage_to_yard(mileage=1.0396)
>>> yards_dat
2156
```

mile_chain_to_mileage

`pyrcs.converter.mile_chain_to_mileage(mile_chain)`

Convert mileage data in the form '<miles>.<chains>' to Network Rail mileage.

Parameters

mile_chain (*str or numpy.nan or None*) – mileage data presented in the form '<miles>.<chains>'

Returns

Network Rail mileage in the form '<miles>.<yards>'

Return type

str

Examples:

```
>>> from pyrcs.converter import mile_chain_to_mileage

>>> # AAM 0.18 Tewkesbury Junction with ANZ (84.62)
>>> mileage_data = mile_chain_to_mileage(mile_chain='0.18')
>>> mileage_data
'0.0396'

>>> # None, nan or ''
>>> mileage_data = mile_chain_to_mileage(mile_chain=None)
>>> mileage_data
''
```

mileage_to_mile_chain`pyrcs.converter.mileage_to_mile_chain(mileage)`

Convert Network Rail mileage to the form '<miles>.<chains>'.

Parameters

mileage (*str or numpy.nan or None*) – Network Rail mileage data presented in the form '<miles>.<yards>'

Returns

data presented in the form '<miles>.<chains>'

Return type

str

Examples:

```
>>> from pyrcs.converter import mileage_to_mile_chain

>>> mile_chain_data = mileage_to_mile_chain(mileage='0.0396')
>>> mile_chain_data
'0.18'

>>> mile_chain_data = mileage_to_mile_chain(mileage=1.0396)
>>> mile_chain_data
'1.18'

>>> # None, nan or ''
>>> miles_chains_dat = mileage_to_mile_chain(mileage=None)
>>> miles_chains_dat
''
```

mile_yard_to_mileage

`pyrcs.converter.mile_yard_to_mileage(mile, yard, as_numeric=True)`

Convert mile and yard to Network Rail mileage.

Parameters

- `mile` (*float or int*) – mile
- `yard` (*float or int*) – yard
- `as_numeric` (*bool*) – whether to return a numeric value, defaults to `True`

Returns

Network Rail mileage

Return type

str or float

Examples:

```
>>> from pyrcs.converter import mile_yard_to_mileage
>>> m, y = 10, 1500
>>> mileage_data = mile_yard_to_mileage(mile=m, yard=y)
>>> mileage_data
10.15
>>> mileage_data = mile_yard_to_mileage(mile=m, yard=y, as_numeric=False)
>>> mileage_data
'10.1500'
```

mileage_str_to_num

`pyrcs.converter.mileage_str_to_num(mileage)`

Convert string-type Network Rail mileage to numerical-type one.

Parameters

`mileage` (*str*) – string-type Network Rail mileage in the form '`<miles>.<yards>`'

Returns

numerical-type Network Rail mileage

Return type

float

Examples:

```
>>> from pyrcs.converter import mileage_str_to_num
>>> mileage_num = mileage_str_to_num(mileage='0.0396')
>>> mileage_num
0.0396
```

(continues on next page)

(continued from previous page)

```
>>> mileage_num = mileage_str_to_num(mileage='')
>>> mileage_num
nan
```

`mileage_num_to_str`

`pyrcs.converter.mileage_num_to_str(mileage)`

Convert numerical-type Network Rail mileage to string-type one.

Parameters

mileage (*float or None*) – numerical-type Network Rail mileage

Returns

string-type Network Rail mileage in the form '<miles>.<yards>'

Return type

str

Examples:

```
>>> from pyrcs.converter import mileage_num_to_str

>>> mileage_str = mileage_num_to_str(mileage=0.0396)
>>> mileage_str
'0.0396'

>>> mileage_str = mileage_num_to_str(mileage=None)
>>> mileage_str
''
```

`shift_mileage_by_yard`

`pyrcs.converter.shift_mileage_by_yard(mileage, shift_yards, as_numeric=True)`

Shift Network Rail mileage by given yards.

Parameters

- **mileage** (*float or int or str*) – mileage (associated with an ELR) used by Network Rail
- **shift_yards** (*int or float*) – yards by which the given mileage is shifted
- **as_numeric** (*bool*) – whether to return a numeric type result, defaults to True

Returns

shifted mileage

Return type

float or str

Examples:

```
>>> from pyrcs.converter import shift_mileage_by_yard

>>> n_mileage = shift_mileage_by_yard(mileage='0.0396', shift_yards=220)
>>> n_mileage
0.0616

>>> n_mileage = shift_mileage_by_yard(mileage='0.0396', shift_yards=220.99)
>>> n_mileage
0.0617

>>> n_mileage = shift_mileage_by_yard(mileage=10, shift_yards=220)
>>> n_mileage
10.022
```

Convert other data

<code>fix_stanox(stanox)</code>	Fix the format of a given STANOX (station number) code.
<code>kilometer_to_yard(km)</code>	Make kilometer-to-yard conversion.

fix_stanox

`pyrcs.converter.fix_stanox(stanox)`

Fix the format of a given STANOX (station number) code.

Parameters

stanox (*str or int or None*) – STANOX code

Returns

standard STANOX code

Return type

str

Examples:

```
>>> from pyrcs.converter import fix_stanox

>>> fixed_stanox = fix_stanox(stanox=65630)
>>> fixed_stanox
'65630'

>>> fixed_stanox = fix_stanox(stanox='2071')
>>> fixed_stanox
'02071'

>>> fixed_stanox = fix_stanox(stanox=2071)
>>> fixed_stanox
'02071'
```

kilometer_to_yard

`pyrcs.converter.kilometer_to_yard(km)`

Make kilometer-to-yard conversion.

Parameters

`km` (*int or float or None*) – kilometer

Returns

yard

Return type

float

Example:

```
>>> from pyrcs.converter import kilometer_to_yard

>>> kilometer_to_yard(1)
1093.6132983377079
```

3.2.3 collector

Collect data of railway codes.

The current release only includes [line data](#) and [other assets](#).

<code>LineData</code> ([update, verbose])	A class representation of all modules of the subpackage <code>line_data</code> for collecting line data .
<code>OtherAssets</code> ([update, verbose])	A class representation of all modules of the subpackage <code>other_assets</code> for collecting other assets .

LineData

`class pyrcs.collector.LineData(update=False, verbose=True)`

A class representation of all modules of the subpackage `line_data` for collecting [line data](#).

Parameters

- `update` (*bool*) – whether to do an update check (for the package data), defaults to False
- `verbose` (*bool or int*) – whether to print relevant information in console, defaults to True

Variables

- `connected` (*bool*) – whether the Internet / the website can be connected
- `catalogue` (*dict*) – catalogue of the data

- **ELRMileages** (*object*) – instance of the class ELRMileages
- **Electrification** (*object*) – instance of the class Electrification
- **LocationIdentifiers** (*object*) – instance of the class LocationIdentifiers
- **LOR** (*object*) – instance of the class LOR
- **LineNames** (*object*) – instance of the class LineNames
- **TrackDiagrams** (*object*) – instance of the class TrackDiagrams
- **Bridges** (*object*) – instance of the class Bridges

Examples:

```
>>> from pyrcs import LineData

>>> ld = LineData()

>>> # To get data of location codes
>>> location_codes = ld.LocationIdentifiers.fetch_codes()
>>> type(location_codes)
dict
>>> list(location_codes.keys())
['LocationID', 'Other systems', 'Additional notes', 'Last updated date']

>>> location_codes_dat = location_codes[ld.LocationIdentifiers.KEY]
>>> type(location_codes_dat)
pandas.core.frame.DataFrame
>>> location_codes_dat.head()
      Location CRS  ... STANME_Note STANOX_Note
0              Aachen  ...
1      Abbeyhill Junction  ...
2      Abbeyhill Signal E811  ...
3      Abbeyhill Turnback Sidings  ...
4  Abbey Level Crossing (Staffordshire)  ...

[5 rows x 12 columns]

>>> # To get data of line names
>>> line_names_codes = ld.LineNames.fetch_codes()
>>> type(line_names_codes)
dict
>>> list(line_names_codes.keys())
['Line names', 'Last updated date']

>>> line_names_codes_dat = line_names_codes[ld.LineNames.KEY]
>>> type(line_names_codes_dat)
pandas.core.frame.DataFrame
>>> line_names_codes_dat.head()
      Line name  ... Route_note
0      Abbey Line  ...      None
1    Airedale Line  ...      None
2      Argyle Line  ...      None
3    Arun Valley Line  ...      None
4  Atlantic Coast Line  ...      None
```

(continues on next page)

(continued from previous page)

[5 rows x 3 columns]

Attributes

<i>NAME</i>	Name of data
<i>URL</i>	URL of the main web page of the data

LineData.NAME

`LineData.NAME = 'Line data'`

Name of data

LineData.URL

`LineData.URL = 'http://www.railwaycodes.org.uk/linedatamenu.shtm'`

URL of the main web page of the data

Methods

<i>update</i> ([confirmation_required, verbose, ...])	Update pre-packed of the line data .
---	--

LineData.update

`LineData.update(confirmation_required=True, verbose=False, interval=5, init_update=False)`Update pre-packed of the [line data](#).

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False
- **interval** (*int*) – time gap (in seconds) between the updating of different classes, defaults to 5
- **init_update** (*bool*) – whether to update the data for instantiation of each subclass, defaults to False

Example:

```
>>> from pyrcs.collector import LineData
>>> ld = LineData()
>>> ld.update(verbose=True)
```

OtherAssets

class `pyrcs.collector.OtherAssets`(*update=False, verbose=True*)

A class representation of all modules of the subpackage `other_assets` for collecting `other` assets.

Parameters

- **update** (*bool*) – whether to do an update check (for the package data), defaults to False
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to True

Variables

- **connected** (*bool*) – whether the Internet / the website can be connected
- **catalogue** (*dict*) – catalogue of the data
- **SignalBoxes** (*object*) – instance of the class `SignalBoxes`
- **Tunnels** (*object*) – instance of the class `Tunnels`
- **Viaducts** (*object*) – instance of the class `Viaducts`
- **Stations** (*object*) – instance of the class `Stations`
- **Depots** (*object*) – instance of the class `Depots`
- **Features** (*object*) – instance of the class `Features`

Examples:

```
>>> from pyrcs import OtherAssets
>>> oa = OtherAssets()
>>> # To get data of railway stations
>>> rail_stn_locations = oa.Stations.fetch_locations()
>>> type(rail_stn_locations)
dict
>>> list(rail_stn_locations.keys())
['Mileages, operators and grid coordinates', 'Last updated date']
>>> rail_stn_locations_dat = rail_stn_locations[oa.Stations.KEY_TO_STN]
>>> type(rail_stn_locations_dat)
pandas.core.frame.DataFrame
>>> rail_stn_locations_dat.head()
```

(continues on next page)

(continued from previous page)

```

      Station ... Former Operator
0      Abbey Wood ... London & South Eastern Railway from 1 April 20...
1      Abbey Wood ...
2      Aber ... Keolis Amey Operations/Gweithrediadau Keolis A...
3      Abercynon ... Keolis Amey Operations/Gweithrediadau Keolis A...
4      Abercynon North ... [Cardiff Railway Company from 13 October 1996 ...

[5 rows x 13 columns]

>>> # To get data of signal boxes
>>> signal_boxes_codes = oa.SignalBoxes.fetch_prefix_codes()

>>> type(signal_boxes_codes)
dict
>>> list(signal_boxes_codes.keys())
['Signal boxes', 'Last updated date']

>>> signal_boxes_codes_dat = signal_boxes_codes[oa.SignalBoxes.KEY]
>>> type(signal_boxes_codes_dat)
pandas.core.frame.DataFrame
>>> signal_boxes_codes_dat.head()
   Code      Signal Box ...      Closed      Control to
0  AF  Abbey Foregate Junction ...  16 February 1992  Nuneaton (NN)
1  AJ      Abbey Junction ...  16 February 1992  Nuneaton (NN)
2  R      Abbey Junction ...  16 February 1992  Nuneaton (NN)
3  AW      Abbey Wood ...  13 July 1975  Dartford (D)
4  AE      Abbey Works East ...  1 November 1987  Port Talbot (PT)

[5 rows x 8 columns]

```

Attributes

<i>NAME</i>	Name of data
<i>URL</i>	URL of the main web page of the data

OtherAssets.NAME

```
OtherAssets.NAME = 'Other assets'
```

Name of data

OtherAssets.URL

```
OtherAssets.URL = 'http://www.railwaycodes.org.uk/otherassetsmenu.shtm'
```

URL of the main web page of the data

Methods

<code>update</code>	([confirmation_required, verbose, ...])	Update pre-packed data of the other assets .
---------------------	---	--

OtherAssets.update

`OtherAssets.update(confirmation_required=True, verbose=False, interval=5, init_update=False)`

Update pre-packed data of the [other assets](#).

Parameters

- **confirmation_required** (*bool*) – whether to confirm before proceeding, defaults to True
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to False
- **interval** (*int*) – time gap (in seconds) between the updating of different classes, defaults to 5
- **init_update** (*bool*) – whether to update the data for instantiation of each subclass, defaults to False

Example:

```
>>> from pyrcs.collector import OtherAssets
>>> oa = OtherAssets()
>>> oa.update(verbose=True)
```

3.2.4 utils

Provide a number of helper functions.

Validate inputs

<code>is_home_connectable()</code>	Check whether the Railway Codes website is connectable.
<code>is_str_float(x)</code>	Check if a string-type variable can express a float-type value.
<code>validate_initial(x[, as_is])</code>	Get a valid initial letter as an input.
<code>validate_page_name(cls, page_no, valid_page_no)</code>	Get
<code>collect_in_fetch_verbose(data_dir, verbose)</code>	Create a new parameter that indicates whether to print relevant information in console (used only if it is necessary to re-collect data when trying to fetch the data).
<code>fetch_all_verbose(data_dir, verbose)</code>	Create a new parameter that indicates whether to print relevant information in console (used only when trying to fetch all data of a cluster).

is_home_connectable

`pyrcs.utils.is_home_connectable()`

Check whether the Railway Codes website is connectable.

Returns

whether the Railway Codes website is connectable

Return type

bool

Example:

```
>>> from pyrcs.utils import is_home_connectable
>>> is_home_connectable()
True
```

is_str_float

`pyrcs.utils.is_str_float(x)`

Check if a string-type variable can express a float-type value.

Parameters

x (*str*) – a string-type variable

Returns

whether `str_val` can express a float value

Return type

bool

Examples:

```
>>> from pyrcs.utils import is_str_float

>>> is_str_float('')
False

>>> is_str_float('a')
False

>>> is_str_float('1')
True

>>> is_str_float('1.1')
True
```

validate_initial

`pyrcs.utils.validate_initial(x, as_is=False)`

Get a valid initial letter as an input.

Parameters

- **x** (*str*) – any string variable (which is supposed to be an initial letter)
- **as_is** (*bool*) – whether to return the validated letter as is the input

Returns

validated initial letter

Return type

str

Examples:

```
>>> from pyrcs.utils import validate_initial

>>> validate_initial('x')
'X'

>>> validate_initial('x', as_is=True)
'x'

>>> validate_initial('xyz')
AssertionError: `x` must be a single letter.
```

validate_page_name

`pyrcs.utils.validate_page_name(cls, page_no, valid_page_no)`

Get

Parameters

- `cls` –
- `page_no` –
- `valid_page_no` –

Returns

collect_in_fetch_verbose

`pyrcs.utils.collect_in_fetch_verbose(data_dir, verbose)`

Create a new parameter that indicates whether to print relevant information in console (used only if it is necessary to re-collect data when trying to fetch the data).

Parameters

- `data_dir` (*str* or *None*) – name of a folder where the pickle file is to be saved
- `verbose` (*bool* or *int*) – whether to print relevant information in console

Returns

whether to print relevant information in console when collecting data

Return type

bool or int

Example:

```
>>> from pyrcs.utils import collect_in_fetch_verbose
>>> collect_in_fetch_verbose(data_dir="data", verbose=True)
False
```

fetch_all_verbose

`pyrcs.utils.fetch_all_verbose(data_dir, verbose)`

Create a new parameter that indicates whether to print relevant information in console (used only when trying to fetch all data of a cluster).

Parameters

- `data_dir` (*str* or *None*) – name of a folder where the pickle file is to be saved
- `verbose` (*bool* or *int*) – whether to print relevant information in console

Returns

whether to print relevant information in console when collecting data

Return type

bool or int

Example:

```
>>> from pyrcs.utils import fetch_all_verbose

>>> fetch_all_verbose(data_dir="data", verbose=True)
False
```

Print messages

<code>confirm_msg(data_name)</code>	Create a confirmation message (for data collection).
<code>print_collect_msg(data_name, verbose, ..., end])</code>	Print a message about the status of collecting data.
<code>print_conn_err([verbose])</code>	Print a message about unsuccessful attempts to establish a connection to the Internet.
<code>print_inst_conn_err([update, verbose, e])</code>	Print a message about unsuccessful attempts to establish a connection to the Internet (for an instance of a class).
<code>print_void_msg(data_name, verbose)</code>	Print a message about the status of collecting data (only when the data collection process fails).

confirm_msg

`pyrcs.utils.confirm_msg(data_name)`

Create a confirmation message (for data collection).

Parameters

data_name (*str*) – name of data, e.g. "Railway Codes"

Returns

a confirmation message

Return type

str

Example:

```
>>> from pyrcs.utils import confirm_msg

>>> msg = confirm_msg(data_name="Railway Codes")
>>> print(msg)
To collect data of Railway Codes
?
```

`print_collect_msg`

`pyrcs.utils.print_collect_msg(data_name, verbose, confirmation_required, end=' ... ')`

Print a message about the status of collecting data.

Parameters

- **data_name** (*str*) – name of the data being collected
- **verbose** (*bool* or *int*) – whether to print relevant information in console
- **confirmation_required** (*bool*) – whether to confirm before proceeding
- **end** (*str*) – string appended after the last value, defaults to " ... ".

Example:

```
>>> from pyrcs.utils import print_collect_msg

>>> print_collect_msg("Railway Codes", verbose=2, confirmation_required=False)
Collecting the data of "Railway Codes" ...
```

`print_conn_err`

`pyrcs.utils.print_conn_err(verbose=False)`

Print a message about unsuccessful attempts to establish a connection to the Internet.

Parameters

- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False

Example:

```
>>> from pyrcs.utils import print_conn_err

>>> # If Internet connection is ready, nothing would be printed
>>> print_conn_err(verbose=True)
```

`print_inst_conn_err`

`pyrcs.utils.print_inst_conn_err(update=False, verbose=False, e=None)`

Print a message about unsuccessful attempts to establish a connection to the Internet (for an instance of a class).

Parameters

- **update** (*bool*) – mostly complies with update in a parent function that uses this function, defaults to False
- **verbose** (*bool* or *int*) – whether to print relevant information in console, defaults to False
- **e** (*Exception* or *None*) – error message

Example:

```
>>> from pyrcs.utils import print_inst_conn_err

>>> print_inst_conn_err(verbose=True)
The Internet connection is not available.
```

print_void_msg

`pyrcs.utils.print_void_msg(data_name, verbose)`

Print a message about the status of collecting data (only when the data collection process fails).

Parameters

- **data_name** (*str*) – name of the data being collected
- **verbose** (*bool* or *int*) – whether to print relevant information in console

Example:

```
>>> from pyrcs.utils import print_void_msg

>>> print_void_msg(data_name="Railway Codes", verbose=True)
No data of "Railway Codes" has been freshly collected.
```

Save and retrieve pre-packed data

<code>init_data_dir</code> (cls, data_dir, category[, cluster])	Specify an initial data directory for (an instance of) a class for a data cluster.
<code>make_file_pathname</code> (cls, data_name[, ext, ...])	Make a pathname for saving data as a file of a certain format.
<code>fetch_location_names_errata</code> ([k, regex, ...])	Create a dictionary for rectifying location names.
<code>save_data_to_file</code> (cls, data, data_name, ext)	Save the collected data as a file, depending on the given parameters.
<code>fetch_data_from_file</code> (cls, method, data_name, ...)	Fetch/load desired data from a backup file, depending on the given parameters.

init_data_dir

`pyrcs.utils.init_data_dir(cls, data_dir, category, cluster=None, **kwargs)`

Specify an initial data directory for (an instance of) a class for a data cluster.

Parameters

- **cls** (*object*) – (an instance of) a class for a certain data cluster
- **data_dir** (*str* or *None*) – name of a folder where the pickle file is to be saved

- **category** (*str*) – name of a data category, e.g. "line-data"
- **cluster** (*str* or *None*) – replacement for `cls.KEY`
- **kwargs** – [optional] parameters of the function `cd_data()`

Returns

pathnames of a default data directory and a current data directory

Return type

tuple[*str*, *os.PathLike*[*str*]]

Example:

```
>>> from pyrcs.utils import init_data_dir
>>> from pyrcs.line_data import Bridges
>>> import os

>>> bridges = Bridges()

>>> dat_dir, current_dat_dir = init_data_dir(bridges, data_dir="data", category="line-data")
>>> os.path.relpath(dat_dir)
'data'
>>> os.path.relpath(current_dat_dir)
'data'
```

make_file_pathname

`pyrcs.utils.make_file_pathname(cls, data_name, ext='.pickle', data_dir=None)`

Make a pathname for saving data as a file of a certain format.

Parameters

- **cls** (*object*) – (an instance of) a class for a certain data cluster
- **data_name** (*str*) – key to the dict-type data of a certain code cluster
- **ext** (*str*) – file extension, defaults to ".pickle"
- **data_dir** (*str* or *None*) – name of a folder where the data is saved, defaults to *None*

Returns

a pathname for saving the data

Return type

str

Example:

```
>>> from pyrcs.utils import make_file_pathname
>>> from pyrcs.line_data import Bridges
>>> import os

>>> bridges = Bridges()
```

(continues on next page)

(continued from previous page)

```
>>> example_pathname = make_file_pathname(bridges, data_name="example-data", ext=".pickle")
>>> os.path.relpath(example_pathname)
'pyrcs\data\line-data\bridges\example-data.pickle'
```

fetch_location_names_errata

`pyrcs.utils.fetch_location_names_errata(k=None, regex=False, as_dataframe=False, column_name=None)`

Create a dictionary for rectifying location names.

Parameters

- **k** (*str or int or float or bool or None*) – key of the created dictionary, defaults to None
- **regex** (*bool*) – whether to create a dictionary for replacement based on regular expressions, defaults to False
- **as_dataframe** (*bool*) – whether to return the created dictionary as a `pandas.DataFrame`, defaults to False
- **column_name** (*str or list or None*) – (if `as_dataframe=True`) column name of the errata data as a dataframe

Returns

dictionary for rectifying location names

Return type

dict or `pandas.DataFrame`

Examples:

```
>>> from pyrcs.utils import fetch_location_names_errata

>>> repl_dict = fetch_location_names_errata()

>>> type(repl_dict)
dict
>>> list(repl_dict.keys())[:5]
['"Tyndrum Upper" (Upper Tyndrum)',
'AISH EMERGENCY CROSSOVER',
'ATLBRJN',
'Aberdeen Craiginches',
'Aberdeen Craiginches T.C.']

>>> repl_dict = fetch_location_names_errata(regex=True, as_dataframe=True)

>>> type(repl_dict)
pandas.core.frame.DataFrame
>>> repl_dict.head()
              new_value
re.compile(' \ (DC lines\)' )    [DC lines]
re.compile(' And | \+ ' )        &
```

(continues on next page)

(continued from previous page)

```
re.compile('-By-')           -by-
re.compile('-In-')           -in-
re.compile('-En-Le-')        -en-le-
```

save_data_to_file

`pyrcs.utils.save_data_to_file(cls, data, data_name, ext, dump_dir=None, verbose=False, **kwargs)`

Save the collected data as a file, depending on the given parameters.

Parameters

- **cls** (*object*) – (an instance of) a class for a certain data cluster
- **data** (*pandas.DataFrame or list or dict*) – data collected for a certain cluster
- **data_name** (*str*) – key to the dict-type data of a certain cluster
- **ext** (*bool or str*) – whether to save the data as a file, or file extension
- **dump_dir** (*str or None*) – pathname of a directory where the data file is to be dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console, defaults to `False`
- **kwargs** – [optional] parameters of the function `pyhelpers.store.save_data()`

fetch_data_from_file

`pyrcs.utils.fetch_data_from_file(cls, method, data_name, ext, update, dump_dir, verbose, data_dir=None, save_data_kwargs=None, **kwargs)`

Fetch/load desired data from a backup file, depending on the given parameters.

Parameters

- **cls** (*object*) – (an instance of) a class for a certain data cluster
- **method** (*str*) – name of a method of the `cls`, which is used for collecting the data
- **data_name** (*str*) – key to the dict-type data of a certain cluster
- **ext** (*bool or str*) – whether to save the data as a file, or file extension
- **update** (*bool*) – whether to do an update check (for the package data), defaults to `False`
- **dump_dir** (*str or os.PathLike[str] or None*) – pathname of a directory where the data file is to be dumped, defaults to `None`
- **verbose** (*bool or int*) – whether to print relevant information in console

- **data_dir** (*str* or *os.PathLike[str]* or *None*) – pathname of a directory where the data is fetched, defaults to *None*
- **save_data_kwargs** (*dict* or *None*) – equivalent of *kwargs* used by the function `pyrcs.utils.save_data_to_file()`, defaults to *None*
- **kwargs** (*any*) – [optional] parameters of the `cls.``method``` being called

Returns

data fetched for the desired cluster

Return type

dict or *None*

Chapter 4

License

PyRCS is licensed under [GNU General Public License v3](#) or later (GPLv3+).

Chapter 5

Use of data

For the use of the data pre-packed with, and collected by, PyRCS, please refer to this link: <http://www.railwaycodes.org.uk/misc/contributing.shtm>

Chapter 6

Acknowledgement

PyRCS uses data available from the [Railway Codes](#) website. The time and effort that the website's editor and [all contributors](#) put in making the site and data available are fully credited.

Chapter 7

Tutorial

To demonstrate how PyRCS works, this brief tutorial provides a quick guide with examples of getting the following three categories of codes, which are frequently used in the railway system in the UK:

- [Location identifiers](#) (CRS, NLC, TIPLOC and STANOX codes);
- [Engineer's Line References \(ELRs\)](#) and their associated mileage files;
- [Railway station data](#) (mileages, operators and grid coordinates).

7.1 Location identifiers

The location identifiers, including CRS, NLC, TIPLOC and STANOX codes, are categorised as [line data](#) on the [Railway Codes](#) website. To get these codes via PyRCS, we can use the class `LocationIdentifiers`, which is contained in the sub-package `line_data`. Let's firstly import the class and create an instance:

```
>>> from pyrcs.line_data import LocationIdentifiers # from pyrcs import LocationIdentifiers

>>> lid = LocationIdentifiers()

>>> lid.NAME
'CRS, NLC, TIPLOC and STANOX codes'
```

Note: An alternative way of creating the instance is through the class `LineData` (see below).

```
>>> from pyrcs.collector import LineData # from pyrcs import LineData

>>> ld = LineData()
>>> lid_ = ld.LocationIdentifiers

>>> lid.NAME == lid_.NAME
True
```

Note:

- The instance `ld` refers to all classes under the category of [line data](#).
- Here `lid_` is equivalent to `lid`.

7.1.1 Location identifiers given a specific initial letter

Now we can get the codes (in a `pandas.DataFrame` type) for all locations beginning with a given letter, by using the method `LocationIdentifiers.collect_codes_by_initial()`. For example, to get the codes for locations whose names begin with 'A' (or 'a'):

```
>>> loc_id_a = lid.collect_codes_by_initial(initial='A') # The input is case-insensitive

>>> type(loc_id_a)
dict
>>> list(loc_id_a.keys())
['A', 'Additional notes', 'Last updated date']
```

As demonstrated above, `loc_id_a` is a [dictionary](#) (in `dict` type), which has the following *keys*:

- 'A'
- 'Additional notes'
- 'Last updated date'

The corresponding *values* are:

- `loc_id_a['A']` - CRS, NLC, TIPLOC and STANOX codes for the locations whose names begin with 'A' (referring to the table presented on the web page [Locations beginning A](#));
- `loc_id_a['Additional notes']` - Additional information on the web page (if available);
- `loc_id_a['Last updated date']` - The date when the web page [Locations beginning A](#) was last updated.

A snapshot of the data contained in `loc_id_a` is demonstrated below:

```
>>> loc_id_a['A'].head()
      Location CRS      NLC ... TIPLOC_Note STANME_Note STANOX_Note
0          Aachen  081601 ...
1  Abbey & West Dereham  705300 ...
2    Abbeyhill Junction  937800 ...
3  Abbeyhill Signal E811  937802 ...
4  Abbeyhill Turnback Sidings  937801 ...

[5 rows x 12 columns]

>>> print("Last updated date: {}".format(loc_id_a['Last updated date']))
Last updated date: 2022-02-27
```

7.1.2 All available location identifiers

In addition to the 'A' group of locations, we can use the method `LocationIdentifiers.fetch_codes()` to get the codes of all locations (with the initial letters ranging from 'A' to 'Z') available in this category:

```
>>> loc_codes = lid.fetch_codes()

>>> type(loc_codes)
dict
>>> list(loc_codes.keys())
['LocationID', 'Other systems', 'Additional notes', 'Last updated date']
```

`loc_codes` is also in a [dictionary](#), of which the *keys* are as follows:

- 'LocationID'
- 'Other systems'
- 'Additional notes'
- 'Latest update date'

The corresponding *values* are:

- `loc_codes['LocationID']` - CRS, NLC, TIPLOC and STANOX codes for all locations available on the relevant web pages ranging from 'A' to 'Z';
- `loc_codes['Other systems']` - Relevant codes of the [Other systems](#);
- `loc_codes['Additional notes']` - Additional notes and information (if available);
- `loc_codes['Latest update date']` - The latest 'Last updated date' among all initial-specific codes.

A snapshot of the data contained in `loc_codes` is demonstrated below:

```
>>> loc_codes['LocationID'].head(10)
      Location  CRS  ... STANME_Note STANOX_Note
0          Aachen  ...
1  Abbey & West Dereham  ...
2    Abbeyhill Junction  ...
3  Abbeyhill Signal E811  ...
4  Abbeyhill Turnback Sidings  ...
5  Abbey Level Crossing (Staffordshire)  ...
6          Abbey Mills  ...
7    Abbey Road DLR  ZAL  ...
8    Abbey Wood  ABW  ...
9  Abbey Wood Alsike Road Junction  ...

[10 rows x 12 columns]

>>> other_sys_codes = loc_codes['Other systems'] # Relevant codes of the 'Other systems'
>>> type(other_sys_codes)
collections.defaultdict
>>> list(other_sys_codes.keys())
['C  ras Iompair   ireann (Republic of Ireland)',
 'Crossrail',
```

(continues on next page)

(continued from previous page)

```

'Croydon Tramlink',
'Docklands Light Railway',
'Manchester Metrolink',
'Translink (Northern Ireland)',
'Tyne & Wear Metro']

>>> crossrail_codes = other_sys_codes['Crossrail'] # Take 'Crossrail' as an example
>>> type(crossrail_codes)
dict
>>> list(crossrail_codes.keys())
['Codes shown on development signalling plans']
>>> crossrail_codes_dat = crossrail_codes['Codes shown on development signalling plans']
>>> type(crossrail_codes_dat)
pandas.core.frame.DataFrame
>>> crossrail_codes_dat.head()

```

	Location	...	Timetable planning rule	code
0	Abbey Wood	...		ABX
1	Abbey Wood Bolthole Berth/Crossrail Sidings	...		ABB
2	Abbey Wood Sidings	...		XWN
3	Bond Street	...		BDS
4	Canary Wharf	...		CWX

```

[5 rows x 4 columns]

```

7.2 ELRs and mileages

Engineer's Line References (ELRs) are also frequently seen among various data in Britain's railway system. To get the codes of ELRs (and their associated mileage files), we can use the class `ELRMileages`:

```

>>> from pyrcs.line_data import ELRMileages # from pyrcs import ELRMileages

>>> em = ELRMileages()

>>> em.NAME
"Engineer's Line References (ELRs)"

```

7.2.1 Engineer's Line References (ELRs)

Similar to the location identifiers, the codes of ELRs on the [Railway Codes](#) website are also alphabetically arranged given their initial letters. We can use the method `ELRMileages.collect_elr_by_initial()` to get the data of ELRs which begin with a specific initial letter. Let's take 'A' as an example:

```

>>> elrs_a = em.collect_elr_by_initial(initial='A') # Data of ELRs beginning with 'A'

>>> type(elrs_a)
dict
>>> list(elrs_a.keys())
['A', 'Last updated date']

```

`elrs_a` is a [dictionary](#) and has the following *keys*:

- 'A'
- 'Last updated date'

The corresponding *values* are:

- `elrs_a['A']` - Data of ELRs that begin with 'A' (referring to the table presented on the web page [ELRs beginning with A](#));
- `elrs_a['Last updated date']` - The date when the web page [ELRs beginning with A](#) was last updated.

A snapshot of the data contained in `elrs_a` is demonstrated below:

```
>>> elrs_a['A'].tail()
   ELR      Line name      Mileages      Datum Notes
186 AYR4  Dalry Junction to Barassie Junction  22.53 - 33.08  Bridge Street Station
187 AYR5  Barassie Junction to Lochgreen Junction  0.00 - 2.15  Barrasie Junction
188 AYR6      Lochgreen Junction to Ayr  35.05 - 40.49  Bridge Street Station
189 AYS      Ashburys Yard Sidings  1.32 - 2.50  Manchester Piccadilly
190 AYT      Aberystwyth Branch  0.00 - 41.15  Pencader Junction

[5 rows x 5 columns]
```

```
>>> print("Last updated date: {}".format(elrs_a['Last updated date']))
Last updated date: 2022-02-19
```

To get the data of all ELRs (with the initial letters ranging from 'A' to 'Z') available in this category, we can use the method `ELRMileages.fetch_elr()`:

```
>>> elrs_data = em.fetch_elr()

>>> type(elrs_data)
dict
>>> list(elrs_data.keys())
['ELRs and mileages', 'Last updated date']
```

In like manner, `elrs_data` is also a [dictionary](#), of which the *keys* are:

- 'ELRs and mileages'
- 'Latest update date'

The corresponding *values* are:

- `elrs_dat['ELRs and mileages']` - Codes of all available ELRs (with the initial letters ranging from 'A' to 'Z');
- `elrs_dat['Latest update date']` - The latest 'Last updated date' among all the initial-specific codes.

A snapshot of the data contained in `elrs_data` is demonstrated below:

```
>>> elrs_data['ELRs and mileages'].tail(10)
   ELR  ...      Notes
4539 ZZF4  ...  Remainder now 0.00 - 0.58 from Sighthill East ...
```

(continues on next page)

(continued from previous page)

```

4540 ZZF5 ...
4541     ...
4542 ZDEL ...
4543 ZDEL ...
4544 ZGW1 ...
4545 ZGW2 ...
4546 ZZY  ...
4547 ZZZ  ...
4548 ZZZ9 ...

[10 rows x 5 columns]

```

7.2.2 Mileage file of a given ELR

Further to the codes of ELRs, each ELR is associated with a mileage file, which specifies the major mileages for the ELR. To get the mileage data, we can use the method `ELRMileages.fetch_mileage_file()`.

For example, let's try to get the [mileage file](#) for 'AAM':

```

>>> em_amm = em.fetch_mileage_file(elr='AAM')

>>> type(em_amm)
dict
>>> list(em_amm.keys())
['ELR', 'Line', 'Sub-Line', 'Mileage', 'Notes']

```

As demonstrated above, `em_amm` is a [dictionary](#) and has the following *keys*:

- 'ELR'
- 'Line'
- 'Sub-Line'
- 'Mileage'
- 'Notes'

The corresponding *values* are:

- `em_amm['ELR']` - The given ELR, which, in this example, is 'AAM';
- `em_amm['Line']` - Name of the line associated with the given ELR;
- `em_amm['Sub-Line']` - Name of the sub line (if any) associated with the given ELR;
- `em_amm['Mileage']` - Major mileages for the given ELR;
- `em_amm['Notes']` - Additional information/notes (if any).

A snapshot of the data contained in `em_amm` is demonstrated below:

```

>>> em_amm['Line']
'Ashchurch and Malvern Line'

```

(continues on next page)

(continued from previous page)

```
>>> em_amm['Mileage'].head(10)
   Mileage  Mileage_Note  Miles_Chains  ...  Link_1_Mile_Chain  Link_2_ELR  Link_2_Mile_Chain
0    0.0000              0.00    ...              79.45
1    0.0154              0.07    ...
2    0.0396              0.18    ...              84.62
3    1.1012              1.46    ...
4    1.1408              1.64    ...
5    5.0330              5.15    ...
6    7.0374              7.17    ...
7   11.1298             11.59    ...
8   13.0638             13.29    ...             129.50

[9 rows x 11 columns]
```

7.3 Railway station data

The [railway station data](#) (including the station name, ELR, mileage, status, owner, operator, degrees of longitude and latitude, and grid reference) is categorised as one of the [other assets](#) on the [Railway Codes](#) website. To deal with data in this category, PyRCS offers a sub-package *other_assets*, from which we can use the contained class *Stations* to get the [railway station data](#):

Now let's import the class and create an instance of it:

```
>>> from pyrcs.other_assets import Stations # from pyrcs import Stations

>>> stn = Stations()

>>> stn.NAME
'Railway station data'
```

Note:

- Alternatively, the instance *stn* can also be defined through the class *OtherAssets*, which contains all classes under the category of [other assets](#) (see below).

```
>>> from pyrcs.collector import OtherAssets # from pyrcs import OtherAssets

>>> oa = OtherAssets()
>>> stn_ = oa.Stations

>>> stn.NAME == stn_.NAME
True
```

Note:

- The instances *stn_* and *stn* are of the same class *Stations*.

7.3.1 Railway station locations given a specific initial letter

To get the location data of railway stations whose names start with a given letter, say 'A', we can use the method `Stations.collect_locations_by_initial()`:

```
>>> stn_loc_a = stn.collect_locations_by_initial('A')

>>> type(stn_loc_a)
dict
>>> list(stn_loc_a.keys())
['A', 'Last updated date']
```

As demonstrated above, the dictionary `stn_loc_a` include the following *keys*:

- 'A'
- 'Last updated date'

The corresponding *values* are:

- `stn_loc_a['A']` - Mileages, operators and grid coordinates of railway stations whose names begin with 'A' (referring to the table presented on the web page of [Stations beginning with A](#));
- `stn_loc_a['Last updated date']` - The date when the web page [Stations beginning with A](#) was last updated.

A snapshot of the data contained in `stn_loc_a` is demonstrated below:

```
>>> stn_loc_a['A'].head()
   Station  ...                               Former Operator
0  Abbey Wood  ...  London & South Eastern Railway from 1 April 20...
1  Abbey Wood  ...
2    Aber     ...  Keolis Amey Operations/Gweithrediadau Keolis A...
3  Abercynon  ...  Keolis Amey Operations/Gweithrediadau Keolis A...
4  Abercynon North  ...  [Cardiff Railway Company from 13 October 1996 ...

[5 rows x 13 columns]

>>> print("Last updated date: {}".format(stn_loc_a['Last updated date']))
Last updated date: 2022-03-08
```

7.3.2 All available railway station locations

To get the location data of all railway stations (with the initial letters ranging from 'A' to 'Z') available in this category, we can use the method `Stations.fetch_locations()`:

```
>>> stn_loc_data = stn.fetch_locations()

>>> type(stn_loc_data)
dict
>>> list(stn_loc_data.keys())
['Mileages, operators and grid coordinates', 'Last updated date']
```

The dictionary `stn_loc_data` include the following *keys*:

- 'Mileages, operators and grid coordinates'

- 'Latest update date'

The corresponding *values* are:

- `stn_loc_data['Mileages, operators and grid coordinates']` - Location data of all railway stations available on the relevant web pages ranging from 'A' to 'Z';
- `stn_loc_data['Latest update date']` - The latest 'Last updated date' among all initial-specific codes.

A snapshot of the data contained in `stn_loc_data` is demonstrated below:

```
>>> stn_loc_data['Mileages, operators and grid coordinates'].head(10)
   Station  ...                               Former Operator
0  Abbey Wood  ...  London & South Eastern Railway from 1 April 20...
1  Abbey Wood  ...
2    Aber     ...  Keolis Amey Operations/Gweithrediadau Keolis A...
3  Abercynon  ...  Keolis Amey Operations/Gweithrediadau Keolis A...
4  Abercynon North  ...  [Cardiff Railway Company from 13 October 1996 ...
5    Aberdare  ...  Keolis Amey Operations/Gweithrediadau Keolis A...
6    Aberdeen  ...  Abellio ScotRail from 1 April 2015 to 31 March...
7    Aberdour  ...  Abellio ScotRail from 1 April 2015 to 31 March...
8  Aberdovey  ...  Keolis Amey Operations/Gweithrediadau Keolis A...
9  Abererch   ...  Keolis Amey Operations/Gweithrediadau Keolis A...

[10 rows x 13 columns]
```

```
>>> print("Last updated date: {}".format(stn_loc_data['Last updated date']))
Last updated date: 2022-03-09
```

This is the end of the *tutorial*.

Any issues regarding the use of the package are all welcome and should be logged/reported onto the [Bug Tracker](#).

For more details and examples, check *sub-packages and modules*.

Python Module Index

P

- `pyrcs`, 3
- `pyrcs.collector`, 125
- `pyrcs.converter`, 118
- `pyrcs.line_data`, 3
 - `pyrcs.line_data.bridge`, 52
 - `pyrcs.line_data.elec`, 14
 - `pyrcs.line_data.elr_mileage`, 4
 - `pyrcs.line_data.line_name`, 46
 - `pyrcs.line_data.loc_id`, 28
 - `pyrcs.line_data.lor_code`, 38
 - `pyrcs.line_data.trk_diagr`, 50
- `pyrcs.other_assets`, 56
 - `pyrcs.other_assets.depot`, 83
 - `pyrcs.other_assets.feature`, 95
 - `pyrcs.other_assets.sig_box`, 56
 - `pyrcs.other_assets.station`, 79
 - `pyrcs.other_assets.tunnel`, 70
 - `pyrcs.other_assets.viaduct`, 75
- `pyrcs.parser`, 108
- `pyrcs.utils`, 130

Index

B

Bridges (class in *pyrcs.line_data.bridge*), 52

C

collect_1950_system_codes() (*pyrcs.other_assets.depot.Depots* method), 86
collect_bell_codes() (*pyrcs.other_assets.sig_box.SignalBoxes* method), 59
collect_buzzer_codes() (*pyrcs.other_assets.feature.Features* method), 97
collect_codes() (*pyrcs.line_data.bridge.Bridges* method), 54
collect_codes() (*pyrcs.line_data.line_name.LineNames* method), 48
collect_codes_by_initial() (*pyrcs.line_data.loc_id.LocationIdentifiers* method), 31
collect_codes_by_page() (*pyrcs.other_assets.tunnel.Tunnels* method), 72
collect_codes_by_page() (*pyrcs.other_assets.viaduct.Viaducts* method), 77
collect_codes_by_prefix() (*pyrcs.line_data.lor_code.LOR* method), 41
collect_elr_by_initial() (*pyrcs.line_data.elr_mileage.ELRMileages* method), 6
collect_elr_lor_converter() (*pyrcs.line_data.lor_code.LOR* method), 42
collect_etz_codes() (*pyrcs.line_data.elec.Electrification* method), 17
collect_explanatory_note() (*pyrcs.line_data.loc_id.LocationIdentifiers* method), 32
collect_gwr_codes() (*pyrcs.other_assets.depot.Depots* method), 87
collect_habds_and_wilds() (*pyrcs.other_assets.feature.Features* method), 98
collect_in_fetch_verbose() (in module *pyrcs.utils*), 133
collect_indep_lines_codes() (*pyrcs.line_data.elec.Electrification* method), 18
collect_ireland_codes() (*pyrcs.other_assets.sig_box.SignalBoxes* method), 60
collect_locations_by_initial() (*pyrcs.other_assets.station.Stations* method), 81
collect_mileage_file() (*pyrcs.line_data.elr_mileage.ELRMileages* method), 7
collect_national_network_codes() (*pyrcs.line_data.elec.Electrification* method), 20
collect_non_national_rail_codes() (*pyrcs.other_assets.sig_box.SignalBoxes* method), 61

collect_ohns_codes() (*pyrcs.line_data.elec.Electrification* method), 21
collect_other_systems_codes() (*pyrcs.line_data.loc_id.LocationIdentifiers* method), 33
collect_pre_tops_codes() (*pyrcs.other_assets.depot.Depots* method), 88
collect_prefix_codes() (*pyrcs.other_assets.sig_box.SignalBoxes* method), 62
collect_telegraph_codes() (*pyrcs.other_assets.feature.Features* method), 100
collect_tops_codes() (*pyrcs.other_assets.depot.Depots* method), 89
collect_water_troughs() (*pyrcs.other_assets.feature.Features* method), 101
collect_wr_mas_dates() (*pyrcs.other_assets.sig_box.SignalBoxes* method), 63
confirm_msg() (in module *pyrcs.utils*), 134

D

Depots (class in *pyrcs.other_assets.depot*), 83

E

Electrification (class in *pyrcs.line_data.elec*), 14
ELRMileages (class in *pyrcs.line_data.elr_mileage*), 4

F

Features (class in *pyrcs.other_assets.feature*), 95
fetch_1950_system_codes() (*pyrcs.other_assets.depot.Depots* method), 90
fetch_all_verbose() (in module *pyrcs.utils*), 133
fetch_bell_codes() (*pyrcs.other_assets.sig_box.SignalBoxes* method), 65
fetch_buzzer_codes() (*pyrcs.other_assets.feature.Features* method), 102
fetch_codes() (*pyrcs.line_data.bridge.Bridges* method), 55
fetch_codes() (*pyrcs.line_data.elec.Electrification* method), 22
fetch_codes() (*pyrcs.line_data.line_name.LineNames* method), 49
fetch_codes() (*pyrcs.line_data.loc_id.LocationIdentifiers* method), 34
fetch_codes() (*pyrcs.line_data.lor_code.LOR* method), 43
fetch_codes() (*pyrcs.other_assets.depot.Depots* method), 91
fetch_codes() (*pyrcs.other_assets.feature.Features* method), 103
fetch_codes() (*pyrcs.other_assets.tunnel.Tunnels* method), 74

[fetch_codes\(\)](#) (*pyrcs.other_assets.viaduct.Viaducts method*), 78
[fetch_data_from_file\(\)](#) (*in module pyrcs.utils*), 139
[fetch_elr\(\)](#) (*pyrcs.line_data.elr_mileage.ELRMileages method*), 9
[fetch_elr_lor_converter\(\)](#) (*pyrcs.line_data.lor_code.LOR method*), 44
[fetch_etz_codes\(\)](#) (*pyrcs.line_data.elec.Electrification method*), 23
[fetch_explanatory_note\(\)](#) (*pyrcs.line_data.loc_id.LocationIdentifiers method*), 35
[fetch_gwr_codes\(\)](#) (*pyrcs.other_assets.depot.Depots method*), 92
[fetch_habds_and_wilds\(\)](#) (*pyrcs.other_assets.feature.Features method*), 104
[fetch_indep_lines_codes\(\)](#) (*pyrcs.line_data.elec.Electrification method*), 24
[fetch_ireland_codes\(\)](#) (*pyrcs.other_assets.sig_box.SignalBoxes method*), 66
[fetch_location_names_errata\(\)](#) (*in module pyrcs.utils*), 138
[fetch_locations\(\)](#) (*pyrcs.other_assets.station.Stations method*), 82
[fetch_mileage_file\(\)](#) (*pyrcs.line_data.elr_mileage.ELRMileages method*), 10
[fetch_national_network_codes\(\)](#) (*pyrcs.line_data.elec.Electrification method*), 25
[fetch_non_national_rail_codes\(\)](#) (*pyrcs.other_assets.sig_box.SignalBoxes method*), 67
[fetch_ohns_codes\(\)](#) (*pyrcs.line_data.elec.Electrification method*), 26
[fetch_other_systems_codes\(\)](#) (*pyrcs.line_data.loc_id.LocationIdentifiers method*), 36
[fetch_pre_tops_codes\(\)](#) (*pyrcs.other_assets.depot.Depots method*), 93
[fetch_prefix_codes\(\)](#) (*pyrcs.other_assets.sig_box.SignalBoxes method*), 68
[fetch_telegraph_codes\(\)](#) (*pyrcs.other_assets.feature.Features method*), 105
[fetch_tops_codes\(\)](#) (*pyrcs.other_assets.depot.Depots method*), 94
[fetch_water_troughs\(\)](#) (*pyrcs.other_assets.feature.Features method*), 106
[fetch_wr_mas_dates\(\)](#) (*pyrcs.other_assets.sig_box.SignalBoxes method*), 69
[fix_mileage\(\)](#) (*in module pyrcs.converter*), 119
[fix_stanox\(\)](#) (*in module pyrcs.converter*), 124

G

[get_catalogue\(\)](#) (*in module pyrcs.parser*), 113
[get_category_menu\(\)](#) (*in module pyrcs.parser*), 114
[get_conn_mileages\(\)](#) (*pyrcs.line_data.elr_mileage.ELRMileages method*), 12
[get_financial_year\(\)](#) (*in module pyrcs.parser*), 113
[get_heading_text\(\)](#) (*in module pyrcs.parser*), 116
[get_hypertext\(\)](#) (*in module pyrcs.parser*), 117
[get_indep_line_catalogue\(\)](#) (*pyrcs.line_data.elec.Electrification method*), 27
[get_introduction\(\)](#) (*in module pyrcs.parser*), 118

[get_keys_to_prefixes\(\)](#) (*pyrcs.line_data.lor_code.LOR method*), 45
[get_last_updated_date\(\)](#) (*in module pyrcs.parser*), 112
[get_page_catalogue\(\)](#) (*in module pyrcs.parser*), 115
[get_page_urls\(\)](#) (*pyrcs.line_data.lor_code.LOR method*), 46
[get_site_map\(\)](#) (*in module pyrcs.parser*), 111

I

[init_data_dir\(\)](#) (*in module pyrcs.utils*), 136
[is_home_connectable\(\)](#) (*in module pyrcs.utils*), 131
[is_str_float\(\)](#) (*in module pyrcs.utils*), 131

K

[KEY](#) (*pyrcs.line_data.bridge.Bridges attribute*), 53
[KEY](#) (*pyrcs.line_data.elec.Electrification attribute*), 15
[KEY](#) (*pyrcs.line_data.elr_mileage.ELRMileages attribute*), 5
[KEY](#) (*pyrcs.line_data.line_name.LineNames attribute*), 48
[KEY](#) (*pyrcs.line_data.loc_id.LocationIdentifiers attribute*), 29
[KEY](#) (*pyrcs.line_data.lor_code.LOR attribute*), 39
[KEY](#) (*pyrcs.line_data.trk_diagr.TrackDiagrams attribute*), 51
[KEY](#) (*pyrcs.other_assets.depot.Depots attribute*), 84
[KEY](#) (*pyrcs.other_assets.feature.Features attribute*), 96
[KEY](#) (*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 57
[KEY](#) (*pyrcs.other_assets.station.Stations attribute*), 81
[KEY](#) (*pyrcs.other_assets.tunnel.Tunnels attribute*), 72
[KEY](#) (*pyrcs.other_assets.viaduct.Viaducts attribute*), 77
[KEY_ELC](#) (*pyrcs.line_data.lor_code.LOR attribute*), 40
[KEY_P](#) (*pyrcs.line_data.lor_code.LOR attribute*), 40
[KEY_TO_1950_SYSTEM](#) (*pyrcs.other_assets.depot.Depots attribute*), 85
[KEY_TO_ADDITIONAL_NOTES](#) (*pyrcs.line_data.loc_id.LocationIdentifiers attribute*), 29
[KEY_TO_BELL_CODES](#) (*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 57
[KEY_TO_BUZZER](#) (*pyrcs.other_assets.feature.Features attribute*), 96
[KEY_TO_ENERGY_TARIFF_ZONES](#) (*pyrcs.line_data.elec.Electrification attribute*), 15
[KEY_TO_GWR](#) (*pyrcs.other_assets.depot.Depots attribute*), 85
[KEY_TO_HABD_WILD](#) (*pyrcs.other_assets.feature.Features attribute*), 96
[KEY_TO_INDEPENDENT_LINES](#) (*pyrcs.line_data.elec.Electrification attribute*), 16
[KEY_TO_IRELAND](#) (*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 57
[KEY_TO_LAST_UPDATED_DATE](#) (*pyrcs.line_data.bridge.Bridges attribute*), 53
[KEY_TO_LAST_UPDATED_DATE](#) (*pyrcs.line_data.elec.Electrification attribute*), 16
[KEY_TO_LAST_UPDATED_DATE](#) (*pyrcs.line_data.elr_mileage.ELRMileages attribute*), 5
[KEY_TO_LAST_UPDATED_DATE](#) (*pyrcs.line_data.line_name.LineNames attribute*), 48
[KEY_TO_LAST_UPDATED_DATE](#) (*pyrcs.line_data.loc_id.LocationIdentifiers attribute*), 30
[KEY_TO_LAST_UPDATED_DATE](#) (*pyrcs.line_data.lor_code.LOR attribute*), 40

KEY_TO_LAST_UPDATED_DATE
(*pyrcs.line_data.trk_diagr.TrackDiagrams attribute*), 51

KEY_TO_LAST_UPDATED_DATE (*pyrcs.other_assets.depot.Depots attribute*), 85

KEY_TO_LAST_UPDATED_DATE
(*pyrcs.other_assets.feature.Features attribute*), 96

KEY_TO_LAST_UPDATED_DATE
(*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 58

KEY_TO_LAST_UPDATED_DATE
(*pyrcs.other_assets.station.Stations attribute*), 81

KEY_TO_LAST_UPDATED_DATE
(*pyrcs.other_assets.tunnel.Tunnels attribute*), 72

KEY_TO_LAST_UPDATED_DATE
(*pyrcs.other_assets.viaduct.Viaducts attribute*), 77

KEY_TO_MSCEN (*pyrcs.line_data.loc_id.LocationIdentifiers attribute*), 30

KEY_TO_NATIONAL_NETWORK
(*pyrcs.line_data.elec.Electrification attribute*), 16

KEY_TO_NON_NATIONAL_RAIL
(*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 58

KEY_TO_OHNS (*pyrcs.line_data.elec.Electrification attribute*), 16

KEY_TO_OTHER_SYSTEMS
(*pyrcs.line_data.loc_id.LocationIdentifiers attribute*), 30

KEY_TO_PRE_TOPS (*pyrcs.other_assets.depot.Depots attribute*), 85

KEY_TO_STN (*pyrcs.other_assets.station.Stations attribute*), 81

KEY_TO_TELEGRAPH (*pyrcs.other_assets.feature.Features attribute*), 96

KEY_TO_TOPS (*pyrcs.other_assets.depot.Depots attribute*), 85

KEY_TO_TROUGH (*pyrcs.other_assets.feature.Features attribute*), 97

KEY_TO_WRMASD (*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 58

kilometer_to_yard() (in module *pyrcs.converter*), 125

L

LineData (class in *pyrcs.collector*), 125

LineNames (class in *pyrcs.line_data.line_name*), 47

LocationIdentifiers (class in *pyrcs.line_data.loc_id*), 28

LOR (class in *pyrcs.line_data.lor_code*), 38

M

make_file_pathname() (in module *pyrcs.utils*), 137

make_xref_dict() (*pyrcs.line_data.loc_id.LocationIdentifiers method*), 37

mile_chain_to_mileage() (in module *pyrcs.converter*), 120

mile_yard_to_mileage() (in module *pyrcs.converter*), 122

mileage_num_to_str() (in module *pyrcs.converter*), 123

mileage_str_to_num() (in module *pyrcs.converter*), 122

mileage_to_mile_chain() (in module *pyrcs.converter*), 121

mileage_to_yard() (in module *pyrcs.converter*), 120

module

- pyrcs*, 3
- pyrcs.collector*, 125
- pyrcs.converter*, 118
- pyrcs.line_data*, 3
- pyrcs.line_data.bridge*, 52
- pyrcs.line_data.elec*, 14

- pyrcs.line_data.elr_mileage*, 4
- pyrcs.line_data.line_name*, 46
- pyrcs.line_data.loc_id*, 28
- pyrcs.line_data.lor_code*, 38
- pyrcs.line_data.trk_diagr*, 50
- pyrcs.other_assets*, 56
- pyrcs.other_assets.depot*, 83
- pyrcs.other_assets.feature*, 95
- pyrcs.other_assets.sig_box*, 56
- pyrcs.other_assets.station*, 79
- pyrcs.other_assets.tunnel*, 70
- pyrcs.other_assets.viaduct*, 75
- pyrcs.parser*, 108
- pyrcs.utils*, 130

N

NAME (*pyrcs.collector.LineData attribute*), 127

NAME (*pyrcs.collector.OtherAssets attribute*), 129

NAME (*pyrcs.line_data.bridge.Bridges attribute*), 53

NAME (*pyrcs.line_data.elec.Electrification attribute*), 16

NAME (*pyrcs.line_data.elr_mileage.ELRMileages attribute*), 5

NAME (*pyrcs.line_data.line_name.LineNames attribute*), 48

NAME (*pyrcs.line_data.loc_id.LocationIdentifiers attribute*), 30

NAME (*pyrcs.line_data.lor_code.LOR attribute*), 40

NAME (*pyrcs.line_data.trk_diagr.TrackDiagrams attribute*), 51

NAME (*pyrcs.other_assets.depot.Depots attribute*), 85

NAME (*pyrcs.other_assets.feature.Features attribute*), 97

NAME (*pyrcs.other_assets.sig_box.SignalBoxes attribute*), 58

NAME (*pyrcs.other_assets.station.Stations attribute*), 81

NAME (*pyrcs.other_assets.tunnel.Tunnels attribute*), 72

NAME (*pyrcs.other_assets.viaduct.Viaducts attribute*), 77

O

OtherAssets (class in *pyrcs.collector*), 128

P

parse_date() (in module *pyrcs.parser*), 110

parse_length() (*pyrcs.other_assets.tunnel.Tunnels static method*), 75

parse_location_name() (in module *pyrcs.parser*), 110

parse_table() (in module *pyrcs.parser*), 109

parse_tr() (in module *pyrcs.parser*), 108

print_collect_msg() (in module *pyrcs.utils*), 135

print_conn_err() (in module *pyrcs.utils*), 135

print_inst_conn_err() (in module *pyrcs.utils*), 135

print_void_msg() (in module *pyrcs.utils*), 136

pyrcs

- module, 3

pyrcs.collector

- module, 125

pyrcs.converter

- module, 118

pyrcs.line_data

- module, 3

pyrcs.line_data.bridge

- module, 52

pyrcs.line_data.elec

- module, 14

[pyrcs.line_data.elr_mileage](#)
 module, 4
[pyrcs.line_data.line_name](#)
 module, 46
[pyrcs.line_data.loc_id](#)
 module, 28
[pyrcs.line_data.lor_code](#)
 module, 38
[pyrcs.line_data.trk_diagr](#)
 module, 50
[pyrcs.other_assets](#)
 module, 56
[pyrcs.other_assets.depot](#)
 module, 83
[pyrcs.other_assets.feature](#)
 module, 95
[pyrcs.other_assets.sig_box](#)
 module, 56
[pyrcs.other_assets.station](#)
 module, 79
[pyrcs.other_assets.tunnel](#)
 module, 70
[pyrcs.other_assets.viaduct](#)
 module, 75
[pyrcs.parser](#)
 module, 108
[pyrcs.utils](#)
 module, 130

S

[save_data_to_file\(\)](#) (in module [pyrcs.utils](#)), 139
[search_conn\(\)](#) ([pyrcs.line_data.elr_mileage.ELRMileages](#) static method), 13
[shift_mileage_by_yard\(\)](#) (in module [pyrcs.converter](#)), 123
[SHORT_NAME](#) ([pyrcs.line_data.lor_code.LOR](#) attribute), 40
[SignalBoxes](#) (class in [pyrcs.other_assets.sig_box](#)), 56
[Stations](#) (class in [pyrcs.other_assets.station](#)), 80

T

[TrackDiagrams](#) (class in [pyrcs.line_data.trk_diagr](#)), 50
[Tunnels](#) (class in [pyrcs.other_assets.tunnel](#)), 71

U

[update\(\)](#) ([pyrcs.collector.LineData](#) method), 127
[update\(\)](#) ([pyrcs.collector.OtherAssets](#) method), 130
[URL](#) ([pyrcs.collector.LineData](#) attribute), 127
[URL](#) ([pyrcs.collector.OtherAssets](#) attribute), 129
[URL](#) ([pyrcs.line_data.bridge.Bridges](#) attribute), 53
[URL](#) ([pyrcs.line_data.elec.Electrification](#) attribute), 16
[URL](#) ([pyrcs.line_data.elr_mileage.ELRMileages](#) attribute), 5
[URL](#) ([pyrcs.line_data.line_name.LineNames](#) attribute), 48
[URL](#) ([pyrcs.line_data.loc_id.LocationIdentifiers](#) attribute), 30
[URL](#) ([pyrcs.line_data.lor_code.LOR](#) attribute), 40
[URL](#) ([pyrcs.line_data.trk_diagr.TrackDiagrams](#) attribute), 52
[URL](#) ([pyrcs.other_assets.depot.Depots](#) attribute), 85
[URL](#) ([pyrcs.other_assets.sig_box.SignalBoxes](#) attribute), 58
[URL](#) ([pyrcs.other_assets.station.Stations](#) attribute), 81
[URL](#) ([pyrcs.other_assets.tunnel.Tunnels](#) attribute), 72

[URL](#) ([pyrcs.other_assets.viaduct.Viaducts](#) attribute), 77

V

[validate_initial\(\)](#) (in module [pyrcs.utils](#)), 132
[validate_page_name\(\)](#) (in module [pyrcs.utils](#)), 133
[Viaducts](#) (class in [pyrcs.other_assets.viaduct](#)), 76

Y

[yard_to_mileage\(\)](#) (in module [pyrcs.converter](#)), 119